

B43504B9337M002

B43504B9337M002 Information

Heisener.com Gidal tervce date terv	 B43504B9337M002 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 330UF 20% 400V SNAP Radial, Can - Snap-In - 3 Lead For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43504B9337M002 Specifications

Manufacturer Part Number B43504B9337M002 Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In - 3 Lead Series B43504 Capacitance 330µF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 270 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization General Purpose Ripple Current - Low Frequency I.51 A @ 100Hz Ripple Current - High Frequency - Impedance 330 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Keport error	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43504Capacitance330µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)270 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance330 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeFhrough HolePackage / CaseKadia, Can - Snap-In - 3 Lead	Manufacturer Part Number	B43504B9337M002
Auminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43504Capacitance330µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)270 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance330 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeFurough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-In - 3 LeadSeriesB43504Capacitance330µFTolerance±0%Voltage - Rated400VESR (Equivalent Series Resistance)270 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance330 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Pockage / CaseRadial, Can - Snap-In - 3 Lead	Category	Capacitors
SeriesB43504Capacitance330µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)270 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - High Frequency-Ingedance330 mOhmsSize / Dimension1.378° Dia (35.00mm)Size / Dimension1.457" (37.00mm)Height - Seated (Max)-Mounting TypeThrough HolePoackage / CaseSatial, Can - Snap-In - 3 Lead		Aluminum Electrolytic Capacitors
Capacitance330µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)270 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency.Inpedance330 mOhmsSize / Dimension.330 mOhmsSize / Dimension.330 mOhmsHeight - Seated (Max).457" (37.00mm)Surface Mount Land Size.Mounting TypeThrough HolePackage / CaseKadi, Can - Snap-In - 3 Lead	Package	Radial, Can - Snap-In - 3 Lead
Totance±20%Voltage - Rated400VESR (Equivalent Series Resistance)270 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency.Impedance330 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max).Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In - 3 Lead	Series	B43504
Voltage - Rated400VESR (Equivalent Series Resistance)270 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.51A @ 100HzInpedance330 mOhmsIcad Spacing0.394" (10.00mm)Size / Dimension1.457" (37.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeFrequencyPackage / CaseRatial, Can - Snap-In - 3 Lead	Capacitance	330µF
C270 mOhm @ 100HzESR (Equivalent Series Resistance)270 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.51 A @ 100HzRipple Current - High Frequency330 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.457" (37.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeFackage / CasePackage / CaseRadial, Can - Snap-In - 3 Lead	Tolerance	±20%
Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.51A @ 100HzRipple Current - High Frequency-Impedance330 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.457" (37.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Voltage - Rated	400V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.51A @ 100HzRipple Current - High Frequency-Impedance330 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	ESR (Equivalent Series Resistance)	270 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.51A @ 100HzRipple Current - High Frequency-Impedance330 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Lifetime @ Temp.	3000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.51A @ 100HzRipple Current - High Frequency-Impedance330 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency1.51A @ 100HzRipple Current - High Frequency-Impedance330 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Polarization	Polar
In a constraint of the product of t	Applications	General Purpose
Impedance330 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Ripple Current - Low Frequency	1.51A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Ripple Current - High Frequency	-
Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Impedance	330 mOhms
Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Size / Dimension	1.378" Dia (35.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Height - Seated (Max)	1.457" (37.00mm)
Package / Case Radial, Can - Snap-In - 3 Lead	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report error	Package / Case	Radial, Can - Snap-In - 3 Lead
		Report errors?

B43504B9337M002 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43504B9337M002 Payment Methods





If you have any question about B43504B9337M002, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com