

# B43504C2687M2

Request a Quote

#### B43504C2687M2 Information

Heisener.com	Part Number	B43504C2687M2
	Manufacturer	EPCOS (TDK)
	Category	Capacitors Aluminum Electrolytic Capacitors
	Description	CAP ALUM 680UF 20% 250V SNAP
	Package	Radial, Can - Snap-In - 3 Lead
		For the pricing/inventory/lead time, please contact
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### B43504C2687M2 Specifications

Manufacturer EPCOS (TDK)   Category Capacitors   Aluminum Electrolytic Capacitors Radial, Can - Snap-In - 3 Lead   Package Radial, Can - Snap-In - 3 Lead   Series B43504   Capacitance 680µF   Tolerance ±20%   Voltage - Rated 250V   ESR (Equivalent Series Resistance) 190 mOhm @ 100Hz   Lifetime @ Temp. 3000 Hrs @ 105°C   Operating Temperature -40°C ~ 105°C   Polarization Polar   Applications General Purpose   Ripple Current - Low Frequency -   Impedance 230 mOhms   Lead Spacing 0.394" (10.00mm)   Size / Dimension 1.181" Dia (30.00mm)   Height - Seated (Max) 1.457" (37.00mm)   Surface Mount Land Size -   Mounting Type Through Hole   Package / Case Radial, Can - Snap-In - 3 Lead	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadPackageB43504Capacitance680µFCapacitance±20%Voltage - Rated250VESR (Equivalent Series Resistance)190 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency196A @ 100HzRipple Current - High Frequency-Impedance230 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Manufacturer Part Number	B43504C2687M2
Aluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43504Capacitance680μFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)190 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency.Ripple Current - High Frequency-Impedance230 mOhmsLad Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max).457" (37.00mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In - 3 Lead	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-In - 3 LeadSeriesB43504Capacitance680μFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)190 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance230 mOhmsLad Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In - 3 Lead	Category	Capacitors
SeriesB43504Capacitance680µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)190 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency.96A @ 100HzLiadquee230 mOhmsLiadquee.300 mOhmsLiadquee.300 mOhmsRipple Current - High Frequency.181" Dia (30.00mm)Size / Dimension1.457" (37.00mm)Height - Seated (Max).40°CSurface Mount Land Size.Mounting TypeThrough HolePackage / CaseKadial, Can - Snap-In - 3 Lead		Aluminum Electrolytic Capacitors
Capacitance680µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)190 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency.Impedance230 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max).Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Package	Radial, Can - Snap-In - 3 Lead
Tolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)190 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency.Impedance230 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.457" (37.00mm)Height - Seated (Max).Surface Mount Land Size-Pokage / CaseRatial, Can - Snap-In - 3 Lead	Series	B43504
Voltage - Rated250VESR (Equivalent Series Resistance)190 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.96A @ 100HzLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Size / Dimension1.457" (37.00mm)Height - Seated (Max)-Mounting TypeFuroupt - J LeadPackage / CaseRadial, Can - Snap-In - 3 Lead	Capacitance	680µF
ESR190 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.96A @ 100HzBipple Current - High Frequency-Impedance230 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Tolerance	$\pm 20\%$
Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.96A @ 100HzRipple Current - High Frequency-Impedance230 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeFackage / CaseRadial, Can - Snap-In - 3 Lead	Voltage - Rated	250V
Operating Temperature -40°C ~ 105°C   Polarization Polar   Applications General Purpose   Ripple Current - Low Frequency 1.96A @ 100Hz   Ripple Current - High Frequency -   Impedance 230 mOhms   Lead Spacing 0.394" (10.00mm)   Size / Dimension 1.181" Dia (30.00mm)   Height - Seated (Max) 1.457" (37.00mm)   Surface Mount Land Size -   Mounting Type Fhough Hole   Package / Case Radial, Can - Snap-In - 3 Lead	ESR (Equivalent Series Resistance)	190 mOhm @ 100Hz
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.96A @ 100HzRipple Current - High Frequency-Impedance230 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Lifetime @ Temp.	3000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.96A @ 100HzRipple Current - High Frequency-Impedance230 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Operating Temperature	$-40^{\circ}\mathrm{C} \sim 105^{\circ}\mathrm{C}$
Ripple Current - Low Frequency1.96A @ 100HzRipple Current - High Frequency-Impedance230 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Polarization	Polar
In PropositionInternational of the second secon	Applications	General Purpose
Impedance230 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Ripple Current - Low Frequency	1.96A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Ripple Current - High Frequency	-
Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Impedance	230 mOhms
Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Size / Dimension	1.181" Dia (30.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Height - Seated (Max)	1.457" (37.00mm)
Package / Case Radial, Can - Snap-In - 3 Lead	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In - 3 Lead
		Report errors?

#### B43504C2687M2 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### B43504C2687M2 Payment Methods





If you have any question about B43504C2687M2, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com