

B43504E0337M002

B43504E0337M002 Information

	Manufacturer Category Description	B43504E0337M002 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 330UF 20% 420V SNAP Radial, Can - Snap-In - 3 Lead For the pricing/inventory/lead time, please contact	Request a Quote	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com		Request a Quote



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43504E0337M002 Specifications

Manufacturer Part NumberB43504E0337M002ManufacturerEPCOS (TDK)CategoryCapacitorsCategoryCapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43504Capacitance330µFTolerance-20%Voltage - Rated420VESR (Equivalent Series Resistance)410 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeRipple Current - High Frequency1.52A @ 100HzRipple Current - High Frequency3.394" (10.00mm)Size / Dimension3.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max).465" (37.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead		
CategoryCapacitorsAckageAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43504Capacitance330µFTolerance±20%Voltage - Rated420VESR (Equivalent Series Resistance)410 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency1.52A @ 100HzRipple Current - High Frequency-Impedance490 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.455" (37.20mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeThrough Hole	Manufacturer Part Number	B43504E0337M002
Auminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43504Capacitance330µFTolerance±20%Voltage - Rated420VESR (Equivalent Series Resistance)410 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency1.52A @ 100HzRipple Current - High Frequency-Impedance490 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeThrough Hole	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-In - 3 LeadSeriesB43504Capacitance330µFTolerance±20%Voltage - Rated420VESR (Equivalent Series Resistance)410 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency1.52A @ 100HzInpedance490 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.465" (37.20mm)Mounting TypeThrough Hole	Category	Capacitors
SeriesB43504Capacitance330µFTolerance±20%Voltage - Rated420VESR (Equivalent Series Resistance)410 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.52A @ 100HzInpedance490 mOhmsLead Spacing0.394" (10.00mn)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeThrough Hole		Aluminum Electrolytic Capacitors
Capacitance330µFTolerance±20%Voltage - Rated420VESR (Equivalent Series Resistance)410 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance490 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)-Mounting TypeFrough Hole	Package	Radial, Can - Snap-In - 3 Lead
Tolerance±20%Voltage - Rated420VESR (Equivalent Series Resistance)410 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.52A @ 100HzImpedance490 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)-Mounting TypeThrough Hole	Series	B43504
Voltage - Rated420VESR (Equivalent Series Resistance)410 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.52A @ 100HzRipple Current - High Frequency-Impedance490 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.455" (37.20mm)Height - Seated (Max)-Mounting TypeThrough Hole	Capacitance	330µF
ESR (Equivalent Series Resistance)410 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.52A @ 100HzRipple Current - High Frequency-Impedance490 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.465" (37.20mm)Height - Seated (Max)-Mounting TypeThrough Hole	Tolerance	±20%
Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.52A @ 100HzRipple Current - High Frequency-Impedance490 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.465" (37.20mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeThrough Hole	Voltage - Rated	420V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.52A @ 100HzRipple Current - High Frequency-Impedance490 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeThrough Hole	ESR (Equivalent Series Resistance)	410 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.52A @ 100HzRipple Current - High Frequency-Impedance490 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeThrough Hole	Lifetime @ Temp.	3000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.52A @ 100HzRipple Current - High Frequency-Impedance490 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeThrough Hole	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency1.52A @ 100HzRipple Current - High Frequency-Impedance490 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeThrough Hole	Polarization	Polar
In a radiusRipple Current - High Frequency-Impedance490 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeThrough Hole	Applications	General Purpose
Impedance490 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeThrough Hole	Ripple Current - Low Frequency	1.52A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeThrough Hole	Ripple Current - High Frequency	-
Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeThrough Hole	Impedance	490 mOhms
Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeThrough Hole	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough Hole	Size / Dimension	1.378" Dia (35.00mm)
Mounting Type Through Hole	Height - Seated (Max)	1.465" (37.20mm)
	Surface Mount Land Size	-
Package / Case Radial, Can - Snap-In - 3 Lead	Mounting Type	Through Hole
-	Package / Case	Radial, Can - Snap-In - 3 Lead
Report en		Report errors?

B43504E0337M002 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43504E0337M002 Payment Methods





If you have any question about B43504E0337M002, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com