



### B43504E187M67 Information

Manufact
Category

Part Number B43504E187M67 Manufacturer EPCOS (TDK)

ategory Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP ALUM 180UF 20% 420V SNAP

Package Radial, Can - Snap-In

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **B43504E187M67 Specifications**

Manufacturer Part Number         B43504E187M67           Manufacturer         EPCOS (TDK)           Category         Capacitors           Package         Radial, Can - Snap-In           Series         B43504           Capacitance         180µF           Tolerance         ±20%           Voltage - Rated         420V           ESR (Equivalent Series Resistance)         750 mOhm @ 100Hz           Lifetime @ Temp.         3000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Oplarization         General Purpose           Ripple Current - Low Frequency         960mA @ 100Hz           Ripple Current - High Frequency         -           Impedance         890 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.181" Dia (30.00mm)           Height - Seated (Max)         1.268" (32.20mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In           Report errors?	•	
Category         Capacitors           Package         Radial, Can - Snap-In           Series         B43504           Capacitance         180µF           Tolerance         ±20%           Voltage - Rated         420V           ESR (Equivalent Series Resistance)         750 mOhm @ 100Hz           Lifetime @ Temp.         3000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         960mA @ 100Hz           Ripple Current - High Frequency         -           Impedance         890 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.181" Dia (30.00mm)           Height - Seated (Max)         1.268" (32.20mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In	Manufacturer Part Number	B43504E187M67
Aluminum Electrolytic Capacitors	Manufacturer	EPCOS (TDK)
Package         Radial, Can - Snap-In           Series         B43504           Capacitance         180μF           Tolerance         ±20%           Voltage - Rated         420V           ESR (Equivalent Series Resistance)         750 mOhm @ 100Hz           Lifetime @ Temp.         3000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         960mA @ 100Hz           Ripple Current - High Frequency         -           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.181" Dia (30.00mm)           Height - Seated (Max)         1.268" (32.20mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In	Category	Capacitors
Series         B43504           Capacitance         180µF           Tolerance         ±20%           Voltage - Rated         420V           ESR (Equivalent Series Resistance)         750 mOhm @ 100Hz           Lifetime @ Temp.         3000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         960mA @ 100Hz           Ripple Current - High Frequency         -           Impedance         890 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.181" Dia (30.00mm)           Height - Seated (Max)         1.268" (32.20mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance       180μF         Tolerance       ±20%         Voltage - Rated       420V         ESR (Equivalent Series Resistance)       750 mOhm @ 100Hz         Lifetime @ Temp.       3000 Hrs @ 105°C         Operating Temperature       -40°C ~ 105°C         Polarization       Polar         Applications       General Purpose         Ripple Current - Low Frequency       960mA @ 100Hz         Ripple Current - High Frequency       -         Impedance       890 mOhms         Lead Spacing       0.394" (10.00mm)         Size / Dimension       1.181" Dia (30.00mm)         Height - Seated (Max)       1.268" (32.20mm)         Surface Mount Land Size       -         Mounting Type       Through Hole         Package / Case       Radial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance ±20%  Voltage - Rated 420V  ESR (Equivalent Series Resistance) 750 mOhm @ 100Hz  Lifetime @ Temp. 3000 Hrs @ 105°C  Operating Temperature -40°C ~ 105°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 960mA @ 100Hz  Ripple Current - High Frequency -  Impedance 890 mOhms  Lead Spacing 0.394" (10.00mm)  Size / Dimension 1.181" Dia (30.00mm)  Height - Seated (Max) 1.268" (32.20mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In	Series	B43504
Voltage - Rated  ESR (Equivalent Series Resistance)  Lifetime @ Temp.  Operating Temperature  Polar  Applications  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  By 0 mOhms  Lead Spacing  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Package / Case  750 mOhm @ 100Hz  750 mOhm @ 100Hz  60eneral Purpose  General Purpose  960mA @ 100Hz  -  100mm  1181" Dia (30.00mm)  1181" Dia (30.00mm)  1180" (32.20mm)  Through Hole  Radial, Can - Snap-In	Capacitance	180μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  3000 Hrs @ 105°C  Operating Temperature  -40°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  890 mOhms  Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.181" Dia (30.00mm)  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  -40°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  890 mOhms  Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.181" Dia (30.00mm)  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In	Voltage - Rated	420V
Operating Temperature  -40°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  890 mOhms  Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.181" Dia (30.00mm)  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In	ESR (Equivalent Series Resistance)	750 mOhm @ 100Hz
Polarization Applications General Purpose Ripple Current - Low Frequency Po60mA @ 100Hz Ripple Current - High Frequency Impedance 890 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.268" (32.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Lifetime @ Temp.	3000 Hrs @ 105°C
Applications  Ripple Current - Low Frequency  960mA @ 100Hz  Ripple Current - High Frequency  - Impedance  890 mOhms  Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.181" Dia (30.00mm)  Height - Seated (Max)  1.268" (32.20mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 890 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.268" (32.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Polarization	Polar
Ripple Current - High Frequency Impedance 890 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.268" (32.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Applications	General Purpose
Impedance890 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	960mA @ 100Hz
Lead Spacing 0.394" (10.00mm)  Size / Dimension 1.181" Dia (30.00mm)  Height - Seated (Max) 1.268" (32.20mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension 1.181" Dia (30.00mm)  Height - Seated (Max) 1.268" (32.20mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In	Impedance	890 mOhms
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Size / Dimension	1.181" Dia (30.00mm)
Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Height - Seated (Max)	1.268" (32.20mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
		Report errors?

#### B43504E187M67 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### B43504E187M67 Payment Methods



















## **B43504E187M67 Shipping Methods**













If you have any question about B43504E187M67, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com