

B43504E2128M67

B43504E2128M67 Information

Contact service cashs here	 B43504E2128M67 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 1200UF 20% 200V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43504E2128M67 Specifications

Manufacturer Part Number B43504E2128M67 Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series B43504 Capacitance 1200µF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 110 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization General Purpose Applications General Purpose Ripple Current - Low Frequency - Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 5.654" (42.00mm) Surface Mount Land Size - Mounting Type Pholep Package / Case Kadial, Can - Snap-In	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43504Capacitance1200µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)110 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency2.7A @ 100HzRipple Current - High Frequency-Lied Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max).Surface Mount Land Size-Mounting TypeFrough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43504E2128M67
Auminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43504Capacitance1200µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)110 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency2.7A @ 100HzRipple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.554" (42.00mm)Height - Seated (Max).Surface Mount Land Size-Mounting TypeFurough HolePackage / CaseRadial, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43504Capacitance1200µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)110 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency.Lined Spacing.304" (10.00mm)Siz / Dimension1.181" Dia (30.00mm)Siz / Dimension.181" Dia (30.00mm)Siz / Dimension.Height - Seated (Max).Surface Mount Land Size-Mounting TypeFolared Matical StatePackage / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43504Capacitance1200µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)110 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance1200µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)110 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±2%Voltage - Rated200VESR (Equivalent Series Resistance)110 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarzationPolarApplicationsGeneral PurposeRipple Current - High Frequency2.7A @ 100HzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.654" (42.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In	Series	B43504
Voltage - Rated200VESR (Equivalent Series Resistance)110 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.7A @ 100HzRipple Current - High Frequency-Lead Spacing0.394" (10.00mm)Size / Dimension1.654" (42.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Pounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Capacitance	1200µF
ESR 10 mOhm @ 100Hz ESR (Equivalent Series Resistance) 3000 Hrs @ 105°C Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polar Folar Applications General Purpose Ripple Current - Low Frequency 2.7A @ 100Hz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Forage Acade Package / Case Radial, Can - Snap-In	Tolerance	$\pm 20\%$
Lifetime @ Temp.3000 Hrs @ 105°CDeperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.7A @ 100HzRipple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.654" (42.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In	Voltage - Rated	200V
Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.7A @ 100Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Fhrough Hole Package / Case Radial, Can - Snap-In	ESR (Equivalent Series Resistance)	110 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.7A @ 100HzRipple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.654" (42.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	3000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency2.7A @ 100HzRipple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max).654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 105°C
InInRipple Current - Low Frequency2.7A @ 100HzRipple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a constraint of a constrain	Applications	General Purpose
Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	2.7A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	-
Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	1.181" Dia (30.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.654" (42.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors	Package / Case	Radial, Can - Snap-In
		Report errors?

B43504E2128M67 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43504E2128M67 Payment Methods



If you have any question about B43504E2128M67, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com