

# B43504E2228M60

Request a Quote

#### B43504E2228M60 Information

Heisener.com	Part Number	B43504E2228M60	
	Manufacturer	EPCOS (TDK)	6
	Category	Capacitors Aluminum Electrolytic Capacitors	Š
	Description	CAP ALUM 2200UF 20% 200V SNAP	93
	Package	Radial, Can - Snap-In	- P 6
		For the pricing/inventory/lead time, please contact	Ľ
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	R

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



#### B43504E2228M60 Specifications

Manufacturer Part NumberB43504E2228M60ManufacturerEPCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43504Capacitance2200µFTolerance2200µFVoltage - Rated200VESR (Equivalent Series Resistance)600 Mm @ 100HzOperating Temperature40°C ~ 105°COperating Temperature6000 Hm @ 105°COplarizationsGeneral PurposeRipple Current - Low Frequency4.4A @ 100HzImpedance.Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Size / Dimension.Munting Type.Mounting TypeThrough HolePourMounting TypePace.Menor terme.Mounting Type.Pace.Pace.Menor terme.Menor terme.Mounting Type.Pace.Menor terme.Menor terme.Menor terme.Menor terme.Mounting Type.Menor terme.Menor terme. </th <th>-</th> <th></th>	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43504Capacitance2200µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)60 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Sirface Mount Land Size-Mounting TypeFnough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43504E2228M60
IdentifyAluminut Electrolytic CapacitonsPackageRadial, Can - Snap-InSeriesB43504Capacitance200µFTolerance±20%Voltage - Rated00VESR (Equivalent Series Resistance)60 mOhm @ 100HzDerating Temper3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - High Frequency-Impedance-Lad Spacing0.394" (10.00mm)Size / Dimension3.038" bia (35.00mm)Size / Dimension2.047" (52.00mm)Hight - Seated (Max)-Mounting TypeFinogh HolePackage / CaseMail, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43504Capacitance200µFTolerance±20%Voltage - Rated00VESR (Equivalent Series Resistance)60 mOhm @ 100HzDerating @ Temp.3000 Hrs @ 105°COperating Temperature440°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency4.4A @ 100HzRippe Current - High Frequency-Lead Spacing0.394" (10.0mm)Size / Dimension1.378" Dia (35.00mm)Hight - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Hounting TypeFnoughtelPackage / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43504Capacitance2200µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)60 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency-Ingedance-Size / Dimension1.378" Dia (35.00mm)Size / Dimension2.047" (52.00mm)Height - Seated (Max)-Mounting TypeThrough HolePoackage / CaseRatial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance2200µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)60 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency4.4A @ 100HzInpedance-Ingedance.394" (10.00mm)Size / Dimension3.394" (10.00mm)Bight - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadi, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)60 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.4A @ 100HzRipple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Series	B43504
Voltage - Rated200VESR (Equivalent Series Resistance)60 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency4.4A @ 100HzImpedance-Icad Spacing0.394" (10.00mm)Size / Dinension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Capacitance	2200µF
Construction60 mOhm @ 100HzESR (Equivalent Series Resistance)60 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.4A @ 100HzRipple Current - High Frequency-Inneedance-Icad Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeFackage / CasePackage / CaseRadial, Can - Snap-In	Tolerance	$\pm 20\%$
Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.4A @ 100HzRipple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In	Voltage - Rated	200V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.4A @ 100HzRipple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	60 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.4A @ 100HzRipple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	3000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency4.4A @ 100HzRipple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 105°C
InInRipple Current - Low Frequency4.4A @ 100HzRipple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a randomRipple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Applications	General Purpose
Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	4.4A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	-
Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	1.378" Dia (35.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	2.047" (52.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report error	Package / Case	Radial, Can - Snap-In
Report en en		Report errors?

#### B43504E2228M60 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

## B43504E2228M60 Payment Methods





If you have any question about B43504E2228M60, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com