

B43504E2228M67

Request a Quote

B43504E2228M67 Information

Heisener.com	Part Number	B43504E2228M67	
	Manufacturer	EPCOS (TDK)	
	Category	Capacitors Aluminum Electrolytic Capacitors	
	Description	CAP ALUM 2200UF 20% 200V SNAP	
	Package	Radial, Can - Snap-In	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us	
		Website: https://www.heisener.com	
		E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43504E2228M67 Specifications

Manufacturer Part NumberB43504E228M67ManufacturerEPCOS (TDK)CategoryCapacitorsAluninum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43504Capacitance2200µFTolerance2200µFVoltage - Rated200VESK (Equivalent Series Resistance)60 mOhm © 100HzDifferium @ Tempe.3000 Hrs @ 105°COperating Temperature4.40° < 105°CApplicationsGenera PurposeRipple Current - Low Frequency4.4A @ 100HzRipple Current - High Frequency3.34" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Hight- Scated (Max)2.047" (52.00mm)Surface Mount Land Size-Hounting TypeHiney HelePackage / CaseStalal, Can - Snap-In	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43504Capacitance2200µFTolerance±20%Voltage - Rated00VESR (Equivalent Series Resistance)60 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Impedance-Liad Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeFinough HolePackage / CaseRatial, Can - Snap-In	Manufacturer Part Number	B43504E2228M67
IdentifyAluminum Electrolytic CapacitonsPackageRadial, Can - Snap-InSeriesB43504Capacitance200µFTolerance200µVoltage - Rated00VESR (Equivalent Series Resistance)60 mOhm @ 100HzOperating Temperature3000 Hrs @ 105°COperating Temperature60 mOhm @ 00HzApplicationsPolarRipple Current - Low Frequency4.4A @ 100HzRipple Current - High Frequency0.394° (10.0mm)Size / Dimension1.378° Dia (35.00mm)Size / Dimension2.047° (52.00mm)Hight - Seated (Max)2.047° (52.00mm)Surface Mount Land Size-Hounting TypeRadial, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43504Capacitance200µFTolerance±20%Voltage - Rated00VESR (Equivalent Series Resistance)60 mOhm @ 100HzDerating @ Tempe.3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency4.4 A @ 100HzRipple Current - High Frequency0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Size / Dimension0.447" (52.00mm)Height - Seated (Max)0.447" (52.00mm)Surface Mount Land Size-Pockage / CaseMail, Can - Snap-In	Category	Capacitors
SeriesB43504Capacitance2200µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)60 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.4A @ 100HzImpedance-Isze / Dimension1.378" Dia (35.00mm)Size / Dimension2.047" (52.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance2200µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)60 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Mingdance-Ized Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Bight - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)60 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.4A @ 100HzRipple Current - High Frequency-Innedance-Icad Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Series	B43504
Voltage - Rated200VESR (Equivalent Series Resistance)60 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.4A @ 100HzInpedance-Icad Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Hounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Capacitance	2200µF
ConstraintG0 mOhm @ 100HzESR (Equivalent Series Resistance)60 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.4A @ 100HzRipple Current - High Frequency-Impedance-Icad Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeFackage / CasePackage / CaseRatial, Can - Snap-In	Tolerance	$\pm 20\%$
Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.4A @ 100HzRipple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeFackage / CasePackage / CaseRadial, Can - Snap-In	Voltage - Rated	200V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.4A @ 100HzRipple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	60 mOhm @ 100Hz
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.4A @ 100HzRipple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	3000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency4.4A @ 100HzRipple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency4.4A @ 100HzRipple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a randomRipple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Applications	General Purpose
Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	4.4A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	-
Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	1.378" Dia (35.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	2.047" (52.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
	Package / Case	Radial, Can - Snap-In
Report err		Report errors?

B43504E2228M67 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE ELARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43504E2228M67 Payment Methods



If you have any question about B43504E2228M67, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com