

B43504E2228M87

Request a Quote

B43504E2228M87 Information

| Heisener.com | Part Number | B43504E2228M87 | |
|---------------------|--------------|---|--|
| | Manufacturer | EPCOS (TDK) | |
| | Category | Capacitors Aluminum Electrolytic Capacitors | |
| | Description | CAP ALUM 2200UF 20% 200V SNAP | |
| | Package | Radial, Can - Snap-In | |
| | | For the pricing/inventory/lead time, please contact | |
| For Reference Only | | us | |
| | | Website: https://www.heisener.com | |
| I of Reference Only | | E-mail: salesdept@heisener.com | |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43504E2228M87 Specifications

| Manufacturer Part NumberB43504E228M87ManufacturerEPCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43504Capacitance2200µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)60 mOhm @ 100HzDerating Temperature-40°C ~ 105°COperating Temperature4.40°C ~ 105°CApplicationsGeneral PurposeRipple Current - Low Frequency4.4A @ 100HzRipple Current - High Frequency.Size / Dimension1.378° Dia (S00mm)Size / Dimension2.047" (S2.00mm)Surface Mount Land Size-Mounting TypeBadia Can - Snan-In | - | |
|--|------------------------------------|----------------------------------|
| CategoryCapacitorsAluninum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43504Capacitance200µFTolerance±0%Voltage - Rated00VESR (Equivalent Series Resistance)60 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature440°C ~ 105°CPolarizationFolareal PurposeApplicationsGeneral PurposeRipple Current - Low Frequency4.4A @ 100HzRipple Current - High Frequency-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Kize / Dimension2.047" (52.00mm)Hight - Seated (Max)-Mounting TypeThrough Hole | Manufacturer Part Number | B43504E2228M87 |
| IdentifyAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43504Capacitance200µFTolerance200µFYoltage - Rated200VESR (Equivalent Series Resistance)60 mOhm @ 100HzDerating Temper3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency4.4 @ 100HzInpedance.Lead Spacing3.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Mounting TypeThrough Hole | Manufacturer | EPCOS (TDK) |
| PackageRadial, Can - Snap-InSeriesB43504Capacitance200µFTolerance±20%Voltage - Rated200VSSR (Equivalent Series Resistance)60 mOhm @ 100HzDerating Temper3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency4.4A @ 100HzInpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Mounting TypeThrough Hole | Category | Capacitors |
| SeriesB43504Capacitance2200µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)60 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough Hole | | Aluminum Electrolytic Capacitors |
| Capacitance2200μFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)60 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)-Mounting TypeThrough Hole | Package | Radial, Can - Snap-In |
| Totance±20%Voltage - Rated200VESR (Equivalent Series Resistance)60 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough Hole | Series | B43504 |
| Voltage - Rated200VESR (Equivalent Series Resistance)60 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency4.4A @ 100HzRipple Current - High Frequency-Impedance0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough Hole | Capacitance | 2200µF |
| For ESR (Equivalent Series Resistance)60 mOhm @ 100HzESR (Equivalent Series Resistance)60 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.4A @ 100HzRipple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough Hole | Tolerance | ±20% |
| Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.4A @ 100HzRipple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough Hole | Voltage - Rated | 200V |
| Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.4A @ 100HzRipple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough Hole | ESR (Equivalent Series Resistance) | 60 mOhm @ 100Hz |
| PolarizationPolarPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency4.4A @ 100HzRipple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough Hole | Lifetime @ Temp. | 3000 Hrs @ 105°C |
| ApplicationsGeneral PurposeRipple Current - Low Frequency4.4A @ 100HzRipple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough Hole | Operating Temperature | -40°C ~ 105°C |
| Ripple Current - Low Frequency4.4A @ 100HzRipple Current - High Frequency-Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough Hole | Polarization | Polar |
| In a constraint of the second secon | Applications | General Purpose |
| Impedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough Hole | Ripple Current - Low Frequency | 4.4A @ 100Hz |
| Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough Hole | Ripple Current - High Frequency | - |
| Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough Hole | Impedance | - |
| Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough Hole | Lead Spacing | 0.394" (10.00mm) |
| Surface Mount Land Size-Mounting TypeThrough Hole | Size / Dimension | 1.378" Dia (35.00mm) |
| Mounting Type Through Hole | Height - Seated (Max) | 2.047" (52.00mm) |
| | Surface Mount Land Size | - |
| Package / Case Radial Can - Snap-In | Mounting Type | Through Hole |
| ruotugo, cuso | Package / Case | Radial, Can - Snap-In |
| Report e | | Report errors? |

B43504E2228M87 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

B43504E2228M87 Payment Methods

B43504E2228M87 Shipping Methods



If you have any question about B43504E2228M87, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com