

B43504E2397M002

Request a Quote

B43504E2397M002 Information

Heisener.com		B43504E2397M002 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 390UF 20% 200V SNAP Radial, Can - Snap-In - 3 Lead	
For Reference Only	Package	Radial, Can - Snap-In - 3 Lead For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43504E2397M002 Specifications

Manufacturer Part NumberB43504E2397M002ManufacturerEPCOS (TDK)CategoryCapacitorsAluninum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43504Capacitance390µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)300 ofthrs @ 100HzDerating Temperature3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationPolarApplicationsCanceral PurposeRipple Current - High Frequency1.2A @ 100HzLada Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Hight - Scated (Max)1.200" (32.00mm)Surface Mount Land Size-Mounting TypeFineugacePackage / CaseMounting Tap-In - 3 Lead	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43504Capacitance390µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)330 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency1.2A @ 100HzRipple Current - High Frequency0.394" (10.0mm)Lead Spacing0.394" (10.0mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Manufacturer Part Number	B43504E2397M002
Auminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43504Capacitance390µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)330 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency1.2A @ 100HzRipple Current - High Frequency-Impedance400 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.20" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-In - 3 LeadSeriesB43504Capacitance390µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)330 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency1.2A @ 100HzImpedance400 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Category	Capacitors
SeriesB43504Capacitance390µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)330 nOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.2A @ 100HzInpedance400 mOhmsLead Spacing0.394" (10.00mn)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole		Aluminum Electrolytic Capacitors
Capacitance390µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)300 nDnm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.2A @ 100HzImpedance400 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Package	Radial, Can - Snap-In - 3 Lead
Tolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)330 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.2A @ 100HzImpedance400 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Series	B43504
Voltage - Rated200VESR (Equivalent Series Resistance)330 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.2A @ 100HzRipple Current - High Frequency-Impedance400 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Capacitance	390µF
For BSR (Equivalent Series Resistance)330 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.2A @ 100HzRipple Current - High Frequency-Impedance400 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Tolerance	±20%
Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.2A @ 100HzRipple Current - High Frequency-Impedance400 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Voltage - Rated	200V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.2A @ 100HzRipple Current - High Frequency-Impedance400 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	ESR (Equivalent Series Resistance)	330 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.2A @ 100HzRipple Current - High Frequency-Impedance400 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Lifetime @ Temp.	3000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.2A @ 100HzRipple Current - High Frequency-Impedance400 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Operating Temperature	-40° C ~ 105° C
Ripple Current - Low Frequency1.2A @ 100HzRipple Current - High Frequency-Impedance400 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Polarization	Polar
In a rangeRipple Current - High Frequency-Impedance400 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Applications	General Purpose
Impedance400 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Ripple Current - Low Frequency	1.2A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Ripple Current - High Frequency	-
Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Impedance	400 mOhms
Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough Hole	Size / Dimension	0.866" Dia (22.00mm)
Mounting Type Through Hole	Height - Seated (Max)	1.260" (32.00mm)
	Surface Mount Land Size	-
Package / CaseRadial, Can - Snap-In - 3 Lead	Mounting Type	Through Hole
	Package / Case	Radial, Can - Snap-In - 3 Lead
Report err		Report errors?

B43504E2397M002 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43504E2397M002 Payment Methods





If you have any question about B43504E2397M002, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com