

B43504E2827M007

B43504E2827M007 Information

Heisener.com	 B43504E2827M007 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 820UF 20% 200V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43504E2827M007 Specifications

Manufacturer Part NumberB43504E2827M007ManufacturerEPCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43504Capacitance820µFTolerance200VVoltage - Rated200VESR (Equivalent Series Resistance)160 mOhm @ 100HzDerating Temperature40°C ~ 105°COperating Temperature90aVApplicationsGeneral PurposeRipple Current - Low Frequency2.2A @ 100HzRipple Current - High Frequency190 mOhmsLead Spacing0.394" (10.00mm)Height - Seated (Max)1.850" (47.00mm)	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43504Capacitance\$20µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)160 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature+40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency2.2A @ 100HzRipple Current - High Frequency-Impedance190 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)	
HardwareAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43504Capacitance820µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)160 mOhm @ 100HzDerating Temperature3000 Hrs @ 105°COperating TemperaturePolarApplicationsGeneral PurposeRipple Current - Low Frequency2.2 A @ 100HzInpedance190 mOhmsLad Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)	
PackageRadial, Can - Snap-InSeriesB43504Capacitance820µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)160 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance190 mOhmsLad Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)	
SeriesB43504Capacitance820μFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)160 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency.22A @ 100HzImpedance190 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension984" Dia (25.00mm)	
Capacitance820µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)160 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.2A @ 100HzRipple Current - High Frequency190 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.988" Dia (25.00mm)	
Tolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)160 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.2A @ 100HzRipple Current - High Frequency190 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)	
Voltage - Rated200VESR (Equivalent Series Resistance)160 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.2A @ 100HzRipple Current - High Frequency-Impedance190 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)	
For the constraint of the constr	
Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.2A @ 100HzRipple Current - High Frequency-Impedance190 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)	
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.2A @ 100HzRipple Current - High Frequency-Impedance190 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)	
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.2A @ 100HzRipple Current - High Frequency-Impedance190 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)	
ApplicationsGeneral PurposeRipple Current - Low Frequency2.2A @ 100HzRipple Current - High Frequency-Impedance190 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)	
Ripple Current - Low Frequency2.2A @ 100HzRipple Current - High Frequency-Impedance190 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)	
Ripple Current - High Frequency-Impedance190 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)	
Impedance190 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)	
Lead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)	
Size / Dimension 0.984" Dia (25.00mm)	
Height - Seated (Max) 1.850" (47.00mm)	
Surface Mount Land Size -	
Mounting Type Through Hole	
Package / Case Radial, Can - Snap-In	
Repor	t errors?

B43504E2827M007 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43504E2827M007 Payment Methods





If you have any question about B43504E2827M007, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com