



B43504E337M82 Information

Heisener.com

Part Number B43504E337M82 Manufacturer EPCOS (TDK) Category

Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 330UF 20% 420V SNAP

Radial, Can - Snap-In - 3 Lead **Package**

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43504E337M82 Specifications

| Manufacturer Part Number B43504E337M82 Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In - 3 Lead Series B43504 Capacitance 330μF Tolerance ±20% Voltage - Rated 420V ESR (Equivalent Series Resistance) 410 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.52A @ 100Hz Ripple Current - High Frequency - Impedance 490 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.465" (37.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | | |
|--|------------------------------------|----------------------------------|
| Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In - 3 Lead Series B43504 Capacitance 330µF Tolerance ±20% Voltage - Rated 420V ESR (Equivalent Series Resistance) 410 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.52A @ 100Hz Ripple Current - High Frequency - Impedance 490 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.465" (37.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Manufacturer Part Number | B43504E337M82 |
| Package Radial, Can - Snap-In - 3 Lead Series B43504 Capacitance 330µF Tolerance ±20% Voltage - Rated 420V ESR (Equivalent Series Resistance) 410 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.52A @ 100Hz Ripple Current - High Frequency - Impedance 490 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.465" (37.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Manufacturer | EPCOS (TDK) |
| Package Radial, Can - Snap-In - 3 Lead Series B43504 Capacitance 330µF Tolerance ±20% Voltage - Rated 420V ESR (Equivalent Series Resistance) 410 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.52A @ 100Hz Ripple Current - High Frequency - Impedance 490 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.465" (37.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Category | Capacitors |
| Series B43504 Capacitance 330µF Tolerance ±20% Voltage - Rated 420V ESR (Equivalent Series Resistance) 410 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.52A @ 100Hz Ripple Current - High Frequency - Impedance 490 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.465" (37.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | | Aluminum Electrolytic Capacitors |
| Capacitance 330μF Tolerance ±20% Voltage - Rated 420V ESR (Equivalent Series Resistance) 410 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.52A @ 100Hz Ripple Current - High Frequency - Impedance 490 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.465" (37.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Package | Radial, Can - Snap-In - 3 Lead |
| Tolerance ±20% Voltage - Rated 420V ESR (Equivalent Series Resistance) 410 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.52A @ 100Hz Ripple Current - High Frequency - Impedance 490 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.465" (37.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Series | B43504 |
| Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 3000 Hrs @ 105°C -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 1.32A @ 100Hz 490 mOhms Lead Spacing 3.394" (10.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Capacitance | 330μF |
| ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 490 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Riono Hrs @ 100Hz 410 mOhm @ 100Hz 400 mOhms 1.52A @ 100Hz 1.52 | Tolerance | ±20% |
| Lifetime @ Temp. Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.52A @ 100Hz Ripple Current - High Frequency Impedance 490 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Voltage - Rated | 420V |
| Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.52A @ 100Hz Ripple Current - High Frequency - Impedance 490 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.465" (37.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | ESR (Equivalent Series Resistance) | 410 mOhm @ 100Hz |
| Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.52A @ 100Hz Ripple Current - High Frequency - Impedance 490 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.465" (37.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Lifetime @ Temp. | 3000 Hrs @ 105°C |
| Applications General Purpose Ripple Current - Low Frequency 1.52A @ 100Hz Ripple Current - High Frequency - Impedance 490 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.465" (37.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Operating Temperature | -40°C ~ 105°C |
| Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 490 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.465" (37.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Polarization | Polar |
| Ripple Current - High Frequency Impedance 490 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.465" (37.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Applications | General Purpose |
| Impedance490 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead | Ripple Current - Low Frequency | 1.52A @ 100Hz |
| Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.465" (37.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Ripple Current - High Frequency | - |
| Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.465" (37.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Impedance | 490 mOhms |
| Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Lead Spacing | 0.394" (10.00mm) |
| Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Size / Dimension | 1.378" Dia (35.00mm) |
| Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Height - Seated (Max) | 1.465" (37.20mm) |
| Package / Case Radial, Can - Snap-In - 3 Lead | Surface Mount Land Size | - |
| | Mounting Type | Through Hole |
| Report errors? | Package / Case | Radial, Can - Snap-In - 3 Lead |
| | | Report errors? |

B43504E337M82 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43504E337M82 Payment Methods



















B43504E337M82 Shipping Methods













If you have any question about B43504E337M82, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com