



### B43505C9227M80 Information

Heisener.com

For Reference Only

Part Number B43505C9227M80
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

**Description** CAP ALUM 220UF 20% 400V SNAP

Package Radial, Can - Snap-In

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **B43505C9227M80 Specifications**

Manufacturer Part Number         B43505C9227M80           Manufacturer         EPCOS (TDK)           Category         Capacitors           Aluminum Electrolytic Capacitors           Package         Radial, Can - Snap-In           Series         B43505           Capacitance         220µF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         400 mOhm @ 100Hz           Lifetime @ Temp.         5000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         1.3A @ 100Hz           Ripple Current - High Frequency         -           Impedance         500 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         1.268" (32.20mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Report errors?	*	
Category         Capacitors           Package         Radial, Can - Snap-In           Series         B43505           Capacitance         220µF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         400 mOhm @ 100Hz           Lifetime @ Temp.         5000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         1.3A @ 100Hz           Ripple Current - High Frequency         -           Impedance         500 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         1.268" (32.20mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In	Manufacturer Part Number	B43505C9227M80
Package         Radial, Can - Snap-In           Series         B43505           Capacitance         220μF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         400 mOhm @ 100Hz           Lifetime @ Temp.         5000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         1.3A @ 100Hz           Ripple Current - High Frequency         -           Impedance         500 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         1.268" (32.20mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In	Manufacturer	EPCOS (TDK)
Package         Radial, Can - Snap-In           Series         B43505           Capacitance         220μF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         400 mOhm @ 100Hz           Lifetime @ Temp.         5000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         1.3A @ 100Hz           Ripple Current - High Frequency         -           Impedance         500 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         1.268" (32.20mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In	Category	Capacitors
Series         B43505           Capacitance         220μF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         400 mOhm @ 100Hz           Lifetime @ Temp.         5000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         1.3A @ 100Hz           Ripple Current - High Frequency         -           Impedance         500 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         1.268" (32.20mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance         220μF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         400 mOhm @ 100Hz           Lifetime @ Temp.         5000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         1.3A @ 100Hz           Ripple Current - High Frequency         -           Impedance         500 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         1.268" (32.20mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance ±20%  Voltage - Rated 400V  ESR (Equivalent Series Resistance) 400 mOhm @ 100Hz  Lifetime @ Temp. 5000 Hrs @ 105°C  Operating Temperature -40°C ~ 105°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 1.3A @ 100Hz  Ripple Current - High Frequency -  Impedance 500 mOhms  Lead Spacing 0.394" (10.00mm)  Size / Dimension 1.378" Dia (35.00mm)  Height - Seated (Max) 1.268" (32.20mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In	Series	B43505
Voltage - Rated  ESR (Equivalent Series Resistance)  Lifetime @ Temp.  5000 Hrs @ 105°C  Operating Temperature  -40°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  Lead Spacing  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Package / Case  400 m Ohm @ 100Hz  5000 Hrs @ 105°C  -40°C ~ 105°C  General Purpose  1.3A @ 100Hz  50n m Ohms  1.3A @ 100Hz  1.3A @ 100	Capacitance	220µF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  5000 Hrs @ 105°C  Operating Temperature  -40°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  1.3A @ 100Hz  Ripple Current - High Frequency  Impedance  500 mOhms  Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.378" Dia (35.00mm)  Height - Seated (Max)  1.268" (32.20mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  -40°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  Lead Spacing  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Package / Case  5000 Hrs @ 105°C  -40°C ~ 105°C	Voltage - Rated	400V
Operating Temperature -40°C ~ 105°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 1.3A @ 100Hz  Ripple Current - High Frequency -  Impedance 500 mOhms  Lead Spacing 0.394" (10.00mm)  Size / Dimension 1.378" Dia (35.00mm)  Height - Seated (Max) 1.268" (32.20mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In	ESR (Equivalent Series Resistance)	400 mOhm @ 100Hz
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 1.3A @ 100Hz  Ripple Current - High Frequency -  Impedance 500 mOhms  Lead Spacing 0.394" (10.00mm)  Size / Dimension 1.378" Dia (35.00mm)  Height - Seated (Max) 1.268" (32.20mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In	Lifetime @ Temp.	5000 Hrs @ 105°C
Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  500 mOhms  Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.378" Dia (35.00mm)  Height - Seated (Max)  1.268" (32.20mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance S00 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.268" (32.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Polarization	Polar
Ripple Current - High Frequency Impedance 500 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.268" (32.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Applications	General Purpose
Impedance500 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	1.3A @ 100Hz
Lead Spacing 0.394" (10.00mm)  Size / Dimension 1.378" Dia (35.00mm)  Height - Seated (Max) 1.268" (32.20mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension 1.378" Dia (35.00mm)  Height - Seated (Max) 1.268" (32.20mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In	Impedance	500 mOhms
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size -  Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Size / Dimension	1.378" Dia (35.00mm)
Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Height - Seated (Max)	1.268" (32.20mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
Report trois:		Report errors?

#### B43505C9227M80 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## B43505C9227M80 Payment Methods


































If you have any question about B43505C9227M80, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com