

## B43505E2158M60

#### B43505E2158M60 Information

Heisener.com	 B43505E2158M60 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 1500UF 20% 200V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### B43505E2158M60 Specifications

Manufacturer Part NumberB43505E2158M60ManufacturerEPCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43505Capacitance1500µFTolerance±20%Voltage - Rated90 mOhm @ 100HzESR (Equivalent Series Resistance)90 mOhm @ 100HzOperating Temperature-40°C ~ 105°COplarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency3.9A @ 100HzRipple Current - High Frequency110 mOhmsLead Spacing0.394" (10.00mm)Kize / Dimension1.378" Dia (35.00mm)		
CategoryCapacitorsPackageAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43505Capacitance1500µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)90 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature44°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency3.9A @ 100HzRipple Current - High Frequency-Impedance110 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)	Manufacturer Part Number	B43505E2158M60
Auminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43505Capacitance1500µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)90 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance110 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43505Capacitance1500µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)90 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency.Impedance110 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)	Category	Capacitors
SeriesB43505Capacitance1500μFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)90 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency.Inpedance110 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)		Aluminum Electrolytic Capacitors
Capacitance1500µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)90 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance110 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)	Package	Radial, Can - Snap-In
Tolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)90 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.9A @ 100HzRipple Current - High Frequency-Impedance110 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)	Series	B43505
Voltage - Rated200VESR (Equivalent Series Resistance)90 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.9A @ 100HzRipple Current - High Frequency110 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)	Capacitance	1500µF
ESR (Equivalent Series Resistance)90 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.9A @ 100HzRipple Current - High Frequency-Impedance110 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)	Tolerance	±20%
Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.9A @ 100HzRipple Current - High Frequency-Impedance110 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)	Voltage - Rated	200V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.9A @ 100HzRipple Current - High Frequency-Impedance110 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)	ESR (Equivalent Series Resistance)	90 mOhm @ 100Hz
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.9A @ 100HzRipple Current - High Frequency-Impedance110 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)	Lifetime @ Temp.	5000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency3.9A @ 100HzRipple Current - High Frequency-Impedance110 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)	Operating Temperature	$-40^{\circ}C \sim 105^{\circ}C$
Ripple Current - Low Frequency3.9A @ 100HzRipple Current - High Frequency-Impedance110 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)	Polarization	Polar
Ripple Current - High Frequency-Impedance110 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)	Applications	General Purpose
Impedance110 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)	Ripple Current - Low Frequency	3.9A @ 100Hz
Lead Spacing 0.394" (10.00mm)   Size / Dimension 1.378" Dia (35.00mm)	Ripple Current - High Frequency	-
Size / Dimension 1.378" Dia (35.00mm)	Impedance	110 mOhms
	Lead Spacing	0.394" (10.00mm)
Height - Seated (Max) 2.047" (52.00mm)	Size / Dimension	1.378" Dia (35.00mm)
	Height - Seated (Max)	2.047" (52.00mm)
Surface Mount Land Size -	Surface Mount Land Size	-
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Radial, Can - Snap-In	Package / Case	Radial, Can - Snap-In
Report error		Report errors?

#### B43505E2158M60 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

# B43505E2158M60 Payment Methods WIRE transfer PayPal Methods B43505E2158M60 Shipping Methods Fedex. O OOO TRO

If you have any question about B43505E2158M60, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com