

B43505E2337M002

B43505E2337M002 Information

Cindal terrice clant Terry	Part Number Manufacturer Category Description Package	B43505E2337M002 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 330UF 20% 200V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43505E2337M002 Specifications

Manufacturer Part NumberB43505E2337M002ManufacturerEPCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43505Capacitance330µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)900 mohm @ 100HzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency.Impedance470 mOhmsLided Spacing0.394" (10.00mm)Size / Dimension0.394" (10.00mm)Size / DimensionHeight - Seated (Max)Surface Mount Land SizeMounting TypeThrough HolePace meterMounting TypePace meterMarcu Shap-In	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43505Capacitance330µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)390 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency-1Impedance470 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKalia, Can - Snap-In	Manufacturer Part Number	B43505E2337M002
IdentifyAluminum Electrolytic CapacitonsPackageRadial, Can - Snap-InSeriesB43505Capacitance330µFTolerance±20%Voltage - Rated00VESR (Equivalent Series Resistance)900 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationFolarenApplicationsGeneral PurposeRipple Current - High Frequency-Impedance470 mOhmsLads Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Hight - Seated (Max)-Surface Mount Land Size-Hounting TypeHongh HolePackage / CaseStalia, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43505Capacitance30µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)300 mOhm @ 100HzDerating @ Tempe.5000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency1.3A @ 100HzImpedance0394" (10.00mm)Lead Spacing0.394" (10.00mm)Size / Dimension1.654" (42.00mm)Size / Dimension1.654" (42.00mm)Surface Mount Land Size-Mounting TypeFinopale MathematicaPackage / CaseKail, Can - Snap-In	Category	Capacitors
SeriesB43505Capacitance330µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)390 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - High Frequency-1Indequate3094" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Size / Dimension.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance330µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)390 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance470 mOhmsIngedance0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Bight - Seated (Max).654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKail, Can - Snap-In	Package	Radial, Can - Snap-In
Total±20%Voltage - Rated200VESR (Equivalent Series Resistance)390 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency.Impedance470 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max).Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Series	B43505
Voltage - Rated200VESR (Equivalent Series Resistance)390 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.3A @ 100HzInpedance-Ingedance0.394" (10.00mn)Size / Dimension0.866" Dia (22.00mn)Height - Seated (Max)1.654" (42.00mn)Surface Mount Land Size-Mounting TypeFrequencyPackage / CaseRatial, Can - Snap-In	Capacitance	330µF
C390 mOhm @ 100HzESR (Equivalent Series Resistance)390 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.3A @ 100HzRipple Current - High Frequency-Inneedance470 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.656" Dia (22.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeFackage / Case	Tolerance	±20%
Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.3A @ 100HzRipple Current - High Frequency-Impedance470 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Voltage - Rated	200V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.3A @ 100HzRipple Current - High Frequency-Impedance470 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	390 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.3A @ 100HzRipple Current - High Frequency-Impedance470 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	5000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.3A @ 100HzRipple Current - High Frequency-Impedance470 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40° C ~ 105° C
InInRipple Current - Low Frequency1.3A @ 100HzRipple Current - High Frequency-Impedance470 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a rank	Applications	General Purpose
Impedance470 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	1.3A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	470 mOhms
Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	0.866" Dia (22.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.654" (42.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Depart amo	Package / Case	Radial, Can - Snap-In
Kepon enou		Report errors?

B43505E2337M002 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43505E2337M002 Payment Methods





If you have any question about B43505E2337M002, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com