

B43505E2687M87

Request a Quote

B43505E2687M87 Information

A Heisener.com	Part Number	B43505E2687M87	
	Manufacturer	EPCOS (TDK)	- I
	Category	Capacitors Aluminum Electrolytic Capacitors	
A Constitute taxing	Description	CAP ALUM 680UF 20% 200V SNAP	
	Package	Radial, Can - Snap-In	
	For the pricing/inventory/lead time, please contact		
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	1

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43505E2687M87 Specifications

Manufacturer Part NumberB43505E2687M87ManufacturerEPCOS (TDK)CategoryCapacitorsAckageAluninum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43505Capacitance680µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)900 mOhm @ 100HzLifetime @ Temp.900 mOhm @ 100HzOperating Temperature40°C ~ 105°COpating Temperature60arApplicationsGeneral PurposeRipple Current - High Frequency2.2 A @ 100HzLiad Spacing3.39 mOhmsLied Spacing3.39 mOhmsLied Spacing1.181" Dia (3.00mm)Ster / Dimension1.181" Dia (3.00mm)Hight - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePanemeThrough Hole	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43505Capacitance680µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)190 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency.Impedance300 MnsLiad Spacing301 MonsLied Spacing1.81" Dia (30.00mm)Size / Dimension1.661" (42.20mm)Hight - Seated (Max).Mounting TypeFrough HolePackage / CaseMain Can - Snap-In	Manufacturer Part Number	B43505E2687M87
IdentifyAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43505Capacitance680µFTolerance20%Voltage - Rated200VESR (Equivalent Series Resistance)190 mOhm @ 100HzDerating Temper5000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Hogh Frequency2.2 A @ 100HzRipple Current - High Frequency300 mOhmsLead Spacing0.394° (10.00mm)Size / Dimension1.181° Dia (30.00mm)Hight - Seated (Max).606° (42.20mm)Surface Mount Land Size-Hounting TypeMatial, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43505Capacitance680µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)190 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationReineral PurposeRipple Current - Low Frequency2.2A @ 100HzKipple Current - High Frequency.Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Size / Dimension1.661" (42.20mm)Surface Mount Land Size-Mounting TypeFurough HolePackage / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43505Capacitance680µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)190 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Impedance230 mOhmsSize / Dimension1.181° Dia (30.00mm)Size / Dimension1.661" (42.20mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance680µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)190 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.2A @ 100HzInpedance300 mOhmsIzad Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±0%Voltage - Rated200VESR (Equivalent Series Resistance)190 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.2A @ 100HzImpedance230 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.661" (42.20mm)Height - Seated (Max)-Mounting TypeFurough HolePackage / CaseRatial, Can - Snap-In	Series	B43505
Voltage - Rated200VESR (Equivalent Series Resistance)190 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.2A @ 100HzImpedance300 mOhmsIcad Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.661" (42.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Capacitance	680µF
For ESR (Equivalent Series Resistance)190 mOhm @ 100HzESR (Equivalent Series Resistance)190 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.2A @ 100HzRipple Current - High Frequency-Impedance230 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.661" (42.20mm)Surface Mount Land Size-Mounting TypeFurogationPackage / CaseRatial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.2A @ 100HzRipple Current - High Frequency-Impedance230 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)5.661" (42.20mm)Surface Mount Land Size-Mounting TypeFackage / Case	Voltage - Rated	200V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.2A @ 100HzRipple Current - High Frequency-Impedance230 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeFrequencyPackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	190 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.2A @ 100HzRipple Current - High Frequency-Impedance230 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.661" (42.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	5000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency2.2A @ 100HzRipple Current - High Frequency-Impedance230 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.661" (42.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	$-40^{\circ}\mathrm{C} \sim 105^{\circ}\mathrm{C}$
Ripple Current - Low Frequency2.2A @ 100HzRipple Current - High Frequency-Impedance230 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.661" (42.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a randomRipple Current - High Frequency-Impedance230 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.661" (42.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Applications	General Purpose
Impedance230 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.661" (42.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	2.2A @ 100Hz
IILead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.661" (42.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.661" (42.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	230 mOhms
Height - Seated (Max)1.661" (42.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	1.181" Dia (30.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.661" (42.20mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Poport or	Package / Case	Radial, Can - Snap-In
Kepon end		Report errors?

B43505E2687M87 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43505E2687M87 Payment Methods



If you have any question about B43505E2687M87, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com