



B43508A2158M2 Information

Ca Heisener.com

Part Number B43508A2158M2
Manufacturer EPCOS (TDK)

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 1500UF 20% 200V SNAP

Package Radial, Can - Snap-In

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43508A2158M2 Specifications

Manufacturer Part NumberB43508A2158M2ManufacturerEPCOS (TDK)CategoryCapacitorsPackageRadial, Can - Snap-InSeriesB43508Capacitance1500µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)75 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 103°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.69A @ 100HzLipedance110 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series B43508 Capacitance 1500µF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 75 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.69A @ 100Hz Ripple Current - High Frequency - Impedance 110 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.850" (47.00mm) Surface Mount Land Size -	Manufacturer Part Number	B43508A2158M2
PackageRadial, Can - Snap-InSeriesB43508Capacitance1500μFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)75 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.69A @ 100HzRipple Current - High Frequency-Impedance110 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-	Manufacturer	EPCOS (TDK)
Package Radial, Can - Snap-In Series B43508 Capacitance 1500µF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 75 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.69A @ 100Hz Ripple Current - High Frequency - Impedance 110 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.850" (47.00mm) Surface Mount Land Size -	Category	Capacitors
Series B43508 Capacitance 1500µF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 75 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.69A @ 100Hz Ripple Current - High Frequency - Impedance 110 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.850" (47.00mm) Surface Mount Land Size -		Aluminum Electrolytic Capacitors
Capacitance 1500μF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 75 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.69A @ 100Hz Ripple Current - High Frequency - Impedance 110 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.850" (47.00mm) Surface Mount Land Size -	Package	Radial, Can - Snap-In
Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 75 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.69A @ 100Hz Ripple Current - High Frequency - Impedance 110 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.850" (47.00mm) Surface Mount Land Size -	Series	B43508
Voltage - Rated 200V ESR (Equivalent Series Resistance) 75 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.69A @ 100Hz Ripple Current - High Frequency - Impedance 110 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.850" (47.00mm) Surface Mount Land Size -	Capacitance	1500μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 110 mOhms Lead Spacing 3000 Hrs @ 105°C	Tolerance	±20%
Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.69A @ 100Hz Ripple Current - High Frequency - Impedance 110 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.850" (47.00mm) Surface Mount Land Size -	Voltage - Rated	200V
Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 110 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) Surface Mount Land Size -	ESR (Equivalent Series Resistance)	75 mOhm @ 100Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.69A @ 100Hz Ripple Current - High Frequency - Impedance 110 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.850" (47.00mm) Surface Mount Land Size -	Lifetime @ Temp.	3000 Hrs @ 105°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Current - Dimension Lead Spacing 1.181" Dia (30.00mm) Height - Seated (Max) Surface Mount Land Size General Purpose 2.69A @ 100Hz - 110 mOhms 1.10 mOhms 1.110 mOhms	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 0.394" (10.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size 2.69A @ 100Hz - 110 mOhms 1.181" Dia (30.00mm) 1.181" Dia (30.00mm) - Surface Mount Land Size -	Polarization	Polar
Ripple Current - High Frequency - Impedance 110 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.850" (47.00mm) Surface Mount Land Size -	Applications	General Purpose
Impedance 110 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.850" (47.00mm) Surface Mount Land Size -	Ripple Current - Low Frequency	2.69A @ 100Hz
Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.850" (47.00mm) Surface Mount Land Size -	Ripple Current - High Frequency	-
Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-	Impedance	110 mOhms
Height - Seated (Max) Surface Mount Land Size 1.850" (47.00mm) -	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size -	Size / Dimension	1.181" Dia (30.00mm)
	Height - Seated (Max)	1.850" (47.00mm)
M	Surface Mount Land Size	-
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Radial, Can - Snap-In	Package / Case	Radial, Can - Snap-In
Report errors?		Report errors?

B43508A2158M2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43508A2158M2 Payment Methods





















B43508A2158M2 Shipping Methods













If you have any question about B43508A2158M2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com