

# B43508A5687M002

#### B43508A5687M002 Information

Contract Network Com	 B43508A5687M002 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 680UF 20% 450V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### B43508A5687M002 Specifications

Manufacturer Part Number B43508A5687M002   Manufacturer EPCOS (TDK)   Category Capacitors   Aluminum Electrolytic Capacitors   Package Radial, Can - Snap-In   Scries B43508   Capacitance 680µF   Tolerance ±20%   Voltage - Rated ±50∨   ESR (Equivalent Series Resistance) 180 mOhm @ 100Hz   Lifetime @ Temp. 3000 Hrs @ 105°C   Operating Temperature -40°C ~ 105°C   Polarization General Purpose   Applications General Purpose   Ripple Current - Low Frequency -   Lipple Current - High Frequency -   Impedance 260 mOhms   Lead Spacing 0.394" (10.00mm)   Size/ Dimension 1.378" Dia (35.00mm)   Liegt - Stated (Max) 2.244" (57.00mm)   Surface Mount Land Size -   Mounting Type -   Package / Case Kagial, Can - Snap-In	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43508Capacitance680µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)180 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance260 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeFirough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43508A5687M002
IdentifyAluminum Electrolytic CapacitonsPackageRadial, Can - Snap-InSeriesB43508Capacitance680µFTolerance±20%Voltage - RatedA50VESR (Equivalent Series Resistance)180 mOhm @ 100HzLifetime @ remp.3000 Hrs @ 105°COperating Temperature3000 Hrs @ 105°CPolarization6eneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency6.Linedance0.394" (10.00mm)Liad Spacing0.394" (10.00mm)Siz / Dimension1.378" Dia (35.00mm)Hight - Seated (Max)2.444" (57.00mm)Surface Mount Land Size-Mounting TypeFurough HolePackage / CaseMain, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43508Capacitance680µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)180 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature•40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.4A @ 100HzLinedance2000 HrsLinedance1.30°CImpedance2000 HrsLinedance1.378° Dia (35.00mm)Siz / Dimension1.378° Dia (35.00mm)Height - Seated (Max)2.44" (57.00mm)Surface Mount Land Size-Mounting TypeHoraghalePackage / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43508Capacitance680µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)180 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance260 mOhmsLiad Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeFurough HolePackage / CaseRadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance680μFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)180 mOhm @ 100HzESR (Equivalent Series Resistance)3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency-Impedance260 mOhmsLad Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±2%Voltage - Rated450VESR (Equivalent Series Resistance)180 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarzationPolarApplicationsGeneral PurposeRipple Current - High Frequency2.4A @ 100HzImpedance260 mOhnsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeFhrough HolePackage / CaseRadial, Can - Snap-In	Series	B43508
Voltage - Rated450VESR (Equivalent Series Resistance)180 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.4A @ 100HzRipple Current - High Frequency60 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Capacitance	680µF
ESR (Equivalent Series Resistance)180 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.4A @ 100HzLingedance260 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Hight - Seated (Max)2.44" (57.00mm)Surface Mount Land Size-Mounting TypeFurguencyPackage / CaseRatial, Can - Snap-In	Tolerance	$\pm 20\%$
Lifetime @ Temp.3000 Hrs @ 105°CDeperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.4A @ 100HzRipple Current - High Frequency-Impedance260 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In	Voltage - Rated	450V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.4A @ 100HzRipple Current - High Frequency-Impedance260 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeFrough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	180 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.4A @ 100HzRipple Current - High Frequency-Impedance260 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	3000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency2.4A @ 100HzRipple Current - High Frequency-Impedance260 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	$-40^{\circ}\mathrm{C} \sim 105^{\circ}\mathrm{C}$
InInRipple Current - Low Frequency2.4A @ 100HzRipple Current - High Frequency-Impedance260 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a constraint of a constrain	Applications	General Purpose
Impedance260 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	2.4A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	260 mOhms
Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	1.378" Dia (35.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	2.244" (57.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors	Package / Case	Radial, Can - Snap-In
1		Report errors?

#### B43508A5687M002 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### B43508A5687M002 Payment Methods





If you have any question about B43508A5687M002, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com