

B43508A9127M62

lest a Quote

B43508A9127M62 Information

C Heisener.com	Part Number	B43508A9127M62	
	Manufacturer	EPCOS (TDK)	E S
	Category	Capacitors Aluminum Electrolytic Capacitors	
	Description	CAP ALUM 120UF 20% 400V SNAP	
	Package	Radial, Can - Snap-In	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Requ

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43508A9127M62 Specifications

Manufacturer Part NumberB43508A9127M62ManufacturerEPCOS (TDK)CategoryCapacitorsCategoryCapacitorsPackageRadial, Can - Snap-InSeriesB43508Capacitance120µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)3000 Hrs @ 105°COperating Temperature440°C - 105°COperating Temperature600mA @ 100HzApplicationsGeneral PurposeRipple Current - High Frequency690mA @ 100HzKingple Gurrent - High Frequency.Kingple Gurrent - High Frequency.394" (10.00mm)Size / Dimension.394" (10.00mm)Kirder Munt Land Size.Munting Type.Nouting Type.Pane And.Stare Munt Land Size.Stare Mun	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43508Capacitance120µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)1.02 Ohm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency690mA @ 100HzRipple Current - High Frequency-Impedance1.44 OhmsLiad Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeFhrough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43508A9127M62
IdentifyAluminum Electrolytic CapacitonsPackageRadial, Can - Snap - InSeriesB43508Capacitance120µFTolerance-20%Voltage - Rated400VESR (Equivalent Series Resistance)0100 Hrs @ 100 HzLifetime @ Temp.3000 Hrs @ 105 °COperating Temperature-40° C ~ 105 °CPolarizationFolar PurposeApplicationsGeneral PurposeRipple Current - High Frequency6 MonA @ 100 HzLide Spacing-144 OnmsLade Spacing0.394" (1.00mm)Size / Dimension1.260" (3.20mm)Hight - Seated (Max)-Surface Mount Land Size-Hounting TypeMona Fola PurposePolaring Tope Paripose-Starface Mont Land Size-Starface Mont Land Size-Starface Mont Land Size-Starface Mont Land Size-Polaring Type-Polaring	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43508Capacitance120µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)1.02 Ohm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency690mA @ 100HzKipple Current - High Frequency-Impedance1.44 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeFinrough HolePackage / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43508Capacitance120µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)1.02 Ohm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeApplications690mA @ 100HzRipple Current - High Frequency-Ingedance1.44 OhmsSize / Dimension0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Size / Dimension1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance120µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)1.02 Ohm @ 100HzESR (Equivalent Series Resistance)3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency690mA @ 100HzRipple Current - High Frequency.Inpedance1.44 OhmsSize / Dimension0.394° (10.00mm)Size / Dimension0.866° Dia (22.00mm)Height - Seated (Max).Surface Mount Land Size.Mounting TypeThrough HolePackage / CaseKaila (Can - Snap-In	Package	Radial, Can - Snap-In
Yorance±0%Voltage - Rated400VESR (Equivalent Series Resistance)1.02 Ohm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency690mA @ 100HzImpedance1.44 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.200" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Series	B43508
Voltage - Rated400VESR (Equivalent Series Resistance)1.02 Ohm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency690mA @ 100HzImpedance1.44 OhmsIcad Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRadial, Can - Snap-In	Capacitance	120µF
EVE1.02 Ohm @ 100HzESR (Equivalent Series Resistance)1.02 Ohm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency690mA @ 100HzRipple Current - High Frequency-Impedance1.44 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Tolerance	$\pm 20\%$
Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency690mA @ 100HzRipple Current - High Frequency-Impedance1.44 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Voltage - Rated	400V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency690mA @ 100HzRipple Current - High Frequency-Impedance1.44 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRadia, Can - Snap-In	ESR (Equivalent Series Resistance)	1.02 Ohm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency690mA @ 100HzRipple Current - High Frequency-Impedance1.44 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	3000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency690mA @ 100HzRipple Current - High Frequency-Impedance1.44 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	$-40^{\circ}C \sim 105^{\circ}C$
Ripple Current - Low Frequency690mA @ 100HzRipple Current - High Frequency-Impedance1.44 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a constraint of a constrain	Applications	General Purpose
Impedance1.44 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	690mA @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	1.44 Ohms
Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	0.866" Dia (22.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.260" (32.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Papart area	Package / Case	Radial, Can - Snap-In
Report end		Report errors?

B43508A9127M62 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE ELARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43508A9127M62 Payment Methods





If you have any question about B43508A9127M62, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com