

B43508A9127M87

B43508A9127M87 Information

| Heisener.com | B43508A9127M87 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 120UF 20% 400V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact | |
|--------------------|---|-----------------|
| For Reference Only | us Website: https://www.heisener.com E-mail: salesdept@heisener.com | Request a Quote |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43508A9127M87 Specifications

| Manufacturer Part NumberB43508A9127M87ManufacturerEPCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43508Capacitance120µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)1.02 Ohm @ 100HzOperating Temperature3000 Hrs @ 105°CPolarizationPolarApplicationsGenera PurposeRipple Current - Low Frequency600mA @ 100HzRipple Current - High Frequency.Impedance1.44 OhmsLigations0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Size / Dimension0.866" Dia (22.00mm) | - | |
|--|------------------------------------|----------------------------------|
| CategoryCapacitorsPackageRadial, Can - Snap-InSeriesB43508Capacitance120µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)1.02 Ohm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency690mA @ 100HzRipple Current - High Frequency.Impedance1.44 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mn)Hight - Seated (Max)1.268" (32.20mm) | Manufacturer Part Number | B43508A9127M87 |
| IdentifyAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43508Capacitance120µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)1.02 Ohm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - High Frequency690m A @ 100HzInpedance1.44 OhmsLead Spacing0.39" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Hight - Seated (Max)1.268" (32.20mm) | Manufacturer | EPCOS (TDK) |
| Package Radial, Can - Snap-In Series B43508 Capacitance 120µF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 1.02 Ohm @ 100Hz Derating Temperature 3000 Hrs @ 105°C Operating Temperature 40°C ~ 105°C Polarization General Purpose Applications General Purpose Ripple Current - High Frequency 690mA @ 100Hz Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 1.268" (32.20mm) | Category | Capacitors |
| Series B43508 Capacitance 120µF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 1.02 Ohm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Folar Applications General Purpose Ripple Current - High Frequency 690mA @ 100Hz Inneedance 1.44 Ohms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) | | Aluminum Electrolytic Capacitors |
| Capacitance120μFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)1.02 Ohm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - High Frequency690mA @ 100HzImpedance1.44 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.268" (32.20mm) | Package | Radial, Can - Snap-In |
| Tolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)1.02 Ohm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency690mA @ 100HzRipple Current - High Frequency-Impedance1.44 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.268" (32.20mm) | Series | B43508 |
| Voltage - Rated400VESR (Equivalent Series Resistance)1.02 Ohm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency690mA @ 100HzRipple Current - High Frequency-Impedance1.44 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.268" (32.20mm) | Capacitance | 120µF |
| For the constraint of the constr | Tolerance | ±20% |
| Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency690mA @ 100HzRipple Current - High Frequency-Impedance1.44 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.268" (32.20mm) | Voltage - Rated | 400V |
| Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency690mA @ 100HzRipple Current - High Frequency-Impedance1.44 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.268" (32.20mm) | ESR (Equivalent Series Resistance) | 1.02 Ohm @ 100Hz |
| PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency690mA @ 100HzRipple Current - High Frequency-Impedance1.44 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.268" (32.20mm) | Lifetime @ Temp. | 3000 Hrs @ 105°C |
| ApplicationsGeneral PurposeRipple Current - Low Frequency690mA @ 100HzRipple Current - High Frequency-Impedance1.44 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.268" (32.20mm) | Operating Temperature | -40°C ~ 105°C |
| Ripple Current - Low Frequency690mA @ 100HzRipple Current - High Frequency-Impedance1.44 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.268" (32.20mm) | Polarization | Polar |
| In a constraint of the second secon | Applications | General Purpose |
| Impedance1.44 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.268" (32.20mm) | Ripple Current - Low Frequency | 690mA @ 100Hz |
| Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 1.268" (32.20mm) | Ripple Current - High Frequency | - |
| Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 1.268" (32.20mm) | Impedance | 1.44 Ohms |
| Height - Seated (Max) 1.268" (32.20mm) | Lead Spacing | 0.394" (10.00mm) |
| - | Size / Dimension | 0.866" Dia (22.00mm) |
| | Height - Seated (Max) | 1.268" (32.20mm) |
| Surface Mount Land Size - | Surface Mount Land Size | - |
| Mounting Type Through Hole | Mounting Type | Through Hole |
| Package / Case Radial, Can - Snap-In | Package / Case | Radial, Can - Snap-In |
| Report e | | Report errors? |

B43508A9127M87 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43508A9127M87 Payment Methods





If you have any question about B43508A9127M87, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com