

B43508A9567M62

B43508A9567M62 Information

Heisener.com	Part Number Manufacturer Category Description Package	B43508A9567M62 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 560UF 20% 400V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43508A9567M62 Specifications

Manufacturer Part Number B43508A9567M62 Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series B43508 Capacitance 560µF Tolerance 200 MOrm @100Hz Voltage - Rated 400V ESR (Equivalent Series Resistance) 200 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature 40°C ~ 105°C Polarization General Purpose Ripple Current - Low Frequency 196A @ 100Hz Ripple Current - High Frequency - Impedance 310 mOhms Lead Spacing 30394° (10.00mm) Size / Dimension 1.818° bia (30.00mm) Size / Dimension 2.047° (52.00mm) Height - Seated (Max) 2.047° (52.00mm) Size / Dimension - Height - Seated (Max) Auge Hole Mounting Type Radial, Can - Snap-In	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43508Capacitance560µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)220 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency.Impedance310 mOhmsLied Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Size / Dimension2.047" (52.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43508A9567M62
IdentifyAluminur Electrolytic CapacitonsPackageRadial, Can - Snap-InSeriesB43508Capacitance560µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)220 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency.Impedance300 MrsLided Spacing309 MrsStez / Dimension.Size / Dimension.Height - Seated (Max).Surface Mount Land Size.Mounting Type.Package / CaseMail, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43508Capacitance560µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)20 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.96A @ 100HzImpedance303 w" (10.00mm)Lead Spacing0.394" (10.00mm)Size / Dimension1.81" Dia (30.00mm)Size / Dimension2.047" (52.00mm)Height - Seated (Max)-Mounting TypeFnoughtelPackage / CaseKaid, Can - Snap-In	Category	Capacitors
SeriesB43508Capacitance560µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)220 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency1.96A @ 100HzInpedance310 mOhmsSize / Dimension1.81" Dia (30.00mm)Size / Dimension2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKailal, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance560µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)20 mOhm @ 100HzESR (Equivalent Series Resistance)3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency1.96A @ 100HzInpedance310 mOhmsSize / Dimension1.81" Dia (30.00mm)Size / Dimension2.047" (52.00mm)Surface Mount Land Size-<	Package	Radial, Can - Snap-In
Tolerance±0%Yoltage - Rated400VESR (Equivalent Series Resistance)220 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.96A @ 100HzRipple Current - High Frequency310 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Surface Mount Land Size-Mounting TypeFhrough HolePackage / CaseRatial, Can - Snap-In	Series	B43508
Voltage - Rated400VESR (Equivalent Series Resistance)220 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency1.96A @ 100HzImpedance310 mOhmsIcad Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Capacitance	560µF
C220 mOhm @ 100HzESR (Equivalent Series Resistance)220 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.96A @ 100HzRipple Current - High Frequency310 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeFackage / CasePackage / CaseRadial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.96A @ 100HzRipple Current - High Frequency-Impedance310 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Voltage - Rated	400V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.96A @ 100HzRipple Current - High Frequency-Impedance310 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	220 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.96A @ 100HzRipple Current - High Frequency-Impedance310 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	3000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.96A @ 100HzRipple Current - High Frequency-Impedance310 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency1.96A @ 100HzRipple Current - High Frequency-Impedance310 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a constraint of the product of t	Applications	General Purpose
Impedance310 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	1.96A @ 100Hz
IILead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	310 mOhms
Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	1.181" Dia (30.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	2.047" (52.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report error	Package / Case	Radial, Can - Snap-In
		Report errors?

B43508A9567M62 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43508A9567M62 Payment Methods





If you have any question about B43508A9567M62, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com