



#### B43508B2108M62 Information

(A) Heisener.com

Part Number B43508B2108M62
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

**Description** CAP ALUM 1000UF 20% 200V SNAP

Package Radial, Can - Snap-In - 3 Lead

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## B43508B2108M62 Specifications

Manufacturer Part Number         B43508B2108M62           Manufacturer         EPCOS (TDK)           Category         Capacitors           Aluminum Electrolytic Capacitors           Package         Radial, Can - Snap-In - 3 Lead           Series         B43508           Capacitance         1000µF           Tolerance         ±20%           Voltage - Rated         200V           ESR (Equivalent Series Resistance)         120 mOhm @ 100Hz           Lifetime @ Temp.         3000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         1.95A @ 100Hz           Ripple Current - High Frequency         -           Impedance         160 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.181" Dia (30.00mm)           Height - Seated (Max)         1.465" (37.20mm)           Surface Mount Land Size         -		
Category         Capacitors           Aluminum Electrolytic Capacitors           Package         Radial, Can - Snap-In - 3 Lead           Series         B43508           Capacitance         1000µF           Tolerance         ±20%           Voltage - Rated         200V           ESR (Equivalent Series Resistance)         120 mOhm @ 100Hz           Lifetime @ Temp.         3000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         1.95A @ 100Hz           Ripple Current - High Frequency         -           Impedance         160 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.181" Dia (30.00mm)           Height - Seated (Max)         1.465" (37.20mm)	Manufacturer Part Number	B43508B2108M62
PackageRadial, Can - Snap-In - 3 LeadSeriesB43508Capacitance1000μFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)120 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.95A @ 100HzRipple Current - High Frequency-Impedance160 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.465" (37.20mm)	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-In - 3 LeadSeriesB43508Capacitance1000μFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)120 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.95A @ 100HzRipple Current - High Frequency-Impedance160 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.465" (37.20mm)	Category	Capacitors
Series         B43508           Capacitance         1000μF           Tolerance         ±20%           Voltage - Rated         200V           ESR (Equivalent Series Resistance)         120 mOhm @ 100Hz           Lifetime @ Temp.         3000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         1.95A @ 100Hz           Ripple Current - High Frequency         -           Impedance         160 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.181" Dia (30.00mm)           Height - Seated (Max)         1.465" (37.20mm)		Aluminum Electrolytic Capacitors
Capacitance         1000µF           Tolerance         ±20%           Voltage - Rated         200V           ESR (Equivalent Series Resistance)         120 mOhm @ 100Hz           Lifetime @ Temp.         3000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         1.95A @ 100Hz           Ripple Current - High Frequency         -           Impedance         160 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.181" Dia (30.00mm)           Height - Seated (Max)         1.465" (37.20mm)	Package	Radial, Can - Snap-In - 3 Lead
Tolerance ±20%  Voltage - Rated 200V  ESR (Equivalent Series Resistance) 120 mOhm @ 100Hz  Lifetime @ Temp. 3000 Hrs @ 105°C  Operating Temperature -40°C ~ 105°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 1.95A @ 100Hz  Ripple Current - High Frequency -  Impedance 160 mOhms  Lead Spacing 0.394" (10.00mm)  Size / Dimension 1.181" Dia (30.00mm)  Height - Seated (Max) 1.465" (37.20mm)	Series	B43508
Voltage - Rated  ESR (Equivalent Series Resistance)  Lifetime @ Temp.  Operating Temperature  Operating Temperature  -40°C ~ 105°C  Polarization  Polar  Applications  General Purpose  Ripple Current - Low Frequency  1.95A @ 100Hz  Ripple Current - High Frequency  Impedance  160 mOhms  Lead Spacing  0.394" (10.00mm)  Size / Dimension  Height - Seated (Max)  1.465" (37.20mm)	Capacitance	1000μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  3000 Hrs @ 105°C  Operating Temperature  -40°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  1.95A @ 100Hz  Ripple Current - High Frequency  Impedance  160 mOhms  Lead Spacing  0.394" (10.00mm)  Size / Dimension  Height - Seated (Max)  1.465" (37.20mm)	Tolerance	±20%
Lifetime @ Temp. 3000 Hrs @ 105°C  Operating Temperature -40°C ~ 105°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 1.95A @ 100Hz  Ripple Current - High Frequency -  Impedance 160 mOhms  Lead Spacing 0.394" (10.00mm)  Size / Dimension 1.181" Dia (30.00mm)  Height - Seated (Max) 1.465" (37.20mm)	Voltage - Rated	200V
Operating Temperature -40°C ~ 105°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 1.95A @ 100Hz  Ripple Current - High Frequency Impedance 160 mOhms  Lead Spacing 0.394" (10.00mm)  Size / Dimension 1.181" Dia (30.00mm)  Height - Seated (Max) 1.465" (37.20mm)	ESR (Equivalent Series Resistance)	120 mOhm @ 100Hz
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 1.95A @ 100Hz  Ripple Current - High Frequency -  Impedance 160 mOhms  Lead Spacing 0.394" (10.00mm)  Size / Dimension 1.181" Dia (30.00mm)  Height - Seated (Max) 1.465" (37.20mm)	Lifetime @ Temp.	3000 Hrs @ 105°C
Applications  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  Lead Spacing  Current - Dimension  1.181" Dia (30.00mm)  Height - Seated (Max)  General Purpose  1.95A @ 100Hz  -  1.00Hz  1.00Hz  1.10Hz  1	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  160 mOhms  Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.181" Dia (30.00mm)  Height - Seated (Max)  1.465" (37.20mm)	Polarization	Polar
Ripple Current - High Frequency Impedance 160 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.465" (37.20mm)	Applications	General Purpose
Impedance       160 mOhms         Lead Spacing       0.394" (10.00mm)         Size / Dimension       1.181" Dia (30.00mm)         Height - Seated (Max)       1.465" (37.20mm)	Ripple Current - Low Frequency	1.95A @ 100Hz
Lead Spacing       0.394" (10.00mm)         Size / Dimension       1.181" Dia (30.00mm)         Height - Seated (Max)       1.465" (37.20mm)	Ripple Current - High Frequency	-
Size / Dimension         1.181" Dia (30.00mm)           Height - Seated (Max)         1.465" (37.20mm)	Impedance	160 mOhms
Height - Seated (Max) 1.465" (37.20mm)	Lead Spacing	0.394" (10.00mm)
	Size / Dimension	1.181" Dia (30.00mm)
Surface Mount Land Size -	Height - Seated (Max)	1.465" (37.20mm)
	Surface Mount Land Size	-
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Radial, Can - Snap-In - 3 Lead	Package / Case	Radial, Can - Snap-In - 3 Lead
Report errors?		Report errors?

#### **B43508B2108M62 Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### B43508B2108M62 Payment Methods





















## B43508B2108M62 Shipping Methods













If you have any question about B43508B2108M62, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com