

B43508B2128M67

Request a Quote

B43508B2128M67 Information

	D. (N	D42500D2120MC7	
Contraction of the second seco	Part Number	B43508B2128M67	
	Manufacturer	EPCOS (TDK)	
	Category	Capacitors Aluminum Electrolytic Capacitors	
	Description	CAP ALUM 1200UF 20% 200V SNAP	
	Package	Radial, Can - Snap-In	
		For the pricing/inventory/lead time, please contact	
		us	
For Reference Only		Website: https://www.heisener.com	
i or recrement only		E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43508B2128M67 Specifications

Package / Case Radial, Can - Snap-In	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43508Capacitance1200µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)100 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Impedance130 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43508B2128M67
Interpretend of the sector	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43508Capacitance1200μFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)100 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeRiple Current - Low Frequency.34A @ 100HzRiple Current - High Frequency.334A @ 100HzLiad Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Size / Dimension.654" (42.00mm)Height - Seated (Max).Surface Mount Land Size-Pockage / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43508Capacitance1200µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)100 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency.34A @ 100HzLingedance130 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max).654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance1200µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)100 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency-Impedance130 mOhmsLiad Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)100 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance130 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.654" (42.00mm)Height - Seated (Max).Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Series	B43508
Voltage - Rated200VESR (Equivalent Series Resistance)100 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.34A @ 100HzImpedance130 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeFrequencyPackage / CaseRatial, Can - Snap-In	Capacitance	1200µF
ComponentESR (Equivalent Series Resistance)100 mOhm @ 100HzESR (Equivalent Series Resistance)3000 Hrs @ 105°CLifetime @ Temp40°C ~ 105°COperating TemperaturePolarPolarizationGeneral PurposeApplications2.34A @ 100HzRipple Current - Low Frequency2.34A @ 100HzImpedance130 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.3000 Hrs @ 105°CDoperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.34A @ 100HzRipple Current - High Frequency-Impedance130 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.654" (42.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In	Voltage - Rated	200V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.34A @ 100HzRipple Current - High Frequency-Impedance130 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.654" (42.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	100 mOhm @ 100Hz
PolarPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.34A @ 100HzRipple Current - High Frequency-Impedance130 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	3000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency2.34A @ 100HzRipple Current - High Frequency-Impedance130 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	$-40^{\circ}\mathrm{C} \sim 105^{\circ}\mathrm{C}$
Ripple Current - Low Frequency2.34A @ 100HzRipple Current - High Frequency-Impedance130 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a constraint of the product of t	Applications	General Purpose
Impedance130 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	2.34A @ 100Hz
IILead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	130 mOhms
Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	1.181" Dia (30.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.654" (42.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
		Report errors?

B43508B2128M67 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43508B2128M67 Payment Methods





If you have any question about B43508B2128M67, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com