

B43508B2567M67

Request a Quote

B43508B2567M67 Information

Part Number	B43508B2567M67	
Manufacturer	EPCOS (TDK)	
Category	Capacitors Aluminum Electrolytic Capacitors	
Description	CAP ALUM 560UF 20% 200V SNAP	
Package	Radial, Can - Snap-In	
	For the pricing/inventory/lead time, please contact	
	us	
For Reference Only	Website: https://www.heisener.com	
	E-mail: salesdept@heisener.com	
	Manufacturer Category Description	Aluminum Electrolytic Capacitors Description CAP ALUM 560UF 20% 200V SNAP Package Radial, Can - Snap-In For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43508B2567M67 Specifications

Manufacturer Part NumberB43508B2567M67ManufacturerEPCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitonsPackageRadial, Can - Snap-InSeriesB43508Capacitance560µFTolerance20%Voltage - Rated200VESR (Equivalent Series Resistance)101 mOhm @ 100HzOperating Tempenture3000 Hrs @ 105°COperating Tempenture90arApplicationsGeneral PurposeRiple Current - Low Frequency1.47A @ 100HzRippel Current - High Frequency0394* (10.00mm)Lipedance0.394* (10.00mm)Size / Dimension0.394* (0.20mm)Size / Dimension0.3200mm)	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43508Capacitance560µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)210 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationFolarRipple Current - Low FrequencyI.417A @ 100HzRipple Current - High Frequency380 mOhmsLead Spacing0.394" (10.00mm)Size / Dinension0.984" Dia (25.00mm)Hight - Seated (Max)I.260" (32.00mm)	
Huminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43508Capacitance560μFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)210 mOhm @ 100HzDerating Temperature3000 Hrs @ 105°COperating Temperature640°C ~ 105°CApplicationsGeneral PurposeApple Current - High Frequency1.47A @ 100HzInpedance280 mOhmsLead Spacing0.394" (10.00mm)Hight - Seated (Max)1.260" (32.00mm)	
PackageRadial, Can - Snap-InSeriesB43508Capacitance560μFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)210 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature440°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Impedance280 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)	
SeriesB43508Capacitance560µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)210 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency1.47A @ 100HzInpedance280 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)	
Capacitance560μFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)210 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency.Impedance280 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.948" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)	
Tolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)210 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.47A @ 100HzRipple Current - High Frequency-Impedance280 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)	
Voltage - Rated200VESR (Equivalent Series Resistance)210 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency.Impedance280 mOhmsIcad Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)	
ESR (Equivalent Series Resistance)210 mOhm @ 100HzESR (Equivalent Series Resistance)3000 Hrs @ 105°CLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.47A @ 100HzRipple Current - High Frequency-Impedance280 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)	
Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.47A @ 100HzRipple Current - High Frequency-Impedance280 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)	
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.47A @ 100HzRipple Current - High Frequency-Impedance280 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)	
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.47A @ 100HzRipple Current - High Frequency-Impedance280 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)	
ApplicationsGeneral PurposeRipple Current - Low Frequency1.47A @ 100HzRipple Current - High Frequency-Impedance280 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)	
Ripple Current - Low Frequency1.47A @ 100HzRipple Current - High Frequency-Impedance280 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)	
In PropriorIn PropriorRipple Current - High Frequency-Impedance280 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)	
Impedance280 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)	
Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.260" (32.00mm)	
Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.260" (32.00mm)	
Height - Seated (Max) 1.260" (32.00mm)	
-	
Surface Manut Land Cine	
Surface Mount Land Size -	
Mounting Type Through Hole	
Package / Case Radial, Can - Snap-In	
Report	port errors?

B43508B2567M67 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43508B2567M67 Payment Methods





If you have any question about B43508B2567M67, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com