

# B43508B9157M82

#### B43508B9157M82 Information

Heisener.com	 B43508B9157M82 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 150UF 20% 400V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### B43508B9157M82 Specifications

Manufacturer Part NumberB43508B9157M82ManufacturerEPCOS (TDK)CategoryCapacitorsCategoryCapacitorsPackageRadial, Can - Snap-InSeriesB43508Capacitance150µFCopacitance±20%Voltage - Rated400VESR (Equivalent Series Resistance)800 Mhrs @100HzDifferium @ Temp.0000 Hrs @105°COperating Temperature40°C ~ 105°CPolarz70mA @100HzRiple Current - Low FrequencyGeneral PurposeRiple Current - High Frequency.Lied Spacing0.394" (10.00mm)Lied Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Hight - Seated (Max).Surface Mount Land Size.Mounting TypeThrough HolePance Mount Land Size.Pance Mount Land Size	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43508Capacitance150µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)820 mOhm @ 100HzDerating Temperature-40°C ~ 105°COperating Temperature90arApplicationsGeneral PurposeRipple Current - Hogh Frequency70mA @ 100HzRipple Current - High Frequency-Imedance1.15 OhnsLead Spacing0.994" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeFhrough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43508B9157M82
IdentifyAluminum Electrolytic CapacitonsPackageRadial, Can - Snap-InSeriesB43508Capacitance150µFTolerance-20%Voltage - Rated400VESR (Equivalent Series Resistance)820 mOhm @ 100HzOperating Temper3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Hogh Frequency-Kipple Current - High Frequency-Impedance1.15 OhmsLead Spacing0.394° (1.00mm)Size / Dimension0.984° Dia (25.00mm)Size / Dimension-Murintg Type-Houning Type-Package / CaseMaila, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43508Capacitance150µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)820 mOhm @ 100HzDerating Temperature3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency770mA @ 100HzRipple Current - High Frequency0.394" (10.00mm)Lead Spacing0.394" (10.00mm)Size / Dimension1.571" (27.20mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Pockage / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43508Capacitance150µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)820 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency770mA @ 100HzInpedance1.15 OhmsSize / Dimension0.984" Dia (25.00mm)Size / Dimension0.984" Dia (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance150µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)820 mOhm @ 100HzESR (Equivalent Series Resistance)3000 Hrs @ 105°COperating Temperature40°C ~ 105°COperating TemperaturePolarApplicationsGeneral PurposeApple Current - Low Frequency70mA @ 100HzNipple Current - High Frequency-Impedance1.15 OhmsSize / Dimension0.984° 10:00mm)Size / Dimension0.984° Dia (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadia Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±0%Yoltage - Rated400VESR (Equivalent Series Resistance)820 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency770mA @ 100HzImpedance1.15 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Series	B43508
Voltage - Rated400VESR (Equivalent Series Resistance)820 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency770mA @ 100HzImpedance.Inpedance0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeFrequencyPackage / CaseRadial, Can - Snap-In	Capacitance	150µF
CS20 mOhm @ 100HzESR (Equivalent Series Resistance)820 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency770mA @ 100HzRipple Current - High Frequency.Impedance0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size.Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency770mA @ 100HzRipple Current - High Frequency-Impedance1.15 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeFackage / CaseRatial, Can - Snap-InRatial, Can - Snap-In	Voltage - Rated	400V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency770mA @ 100HzRipple Current - High Frequency-Impedance1.15 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeFackage / CasePackage / CaseRadia, Can - Snap-In	ESR (Equivalent Series Resistance)	820 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency770mA @ 100HzRipple Current - High Frequency-Impedance1.15 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	3000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency770mA @ 100HzRipple Current - High Frequency-Impedance1.15 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency770mA @ 100HzRipple Current - High Frequency-Impedance1.15 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a constraint of a constrain	Applications	General Purpose
Impedance1.15 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	770mA @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	1.15 Ohms
Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	0.984" Dia (25.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.071" (27.20mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Demost and	Package / Case	Radial, Can - Snap-In
Keport error		Report errors?

#### B43508B9157M82 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE EUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### B43508B9157M82 Payment Methods





If you have any question about B43508B9157M82, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com