

# B43508B9277M60

#### B43508B9277M60 Information

Heisener.com	 B43508B9277M60 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 270UF 20% 400V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## B43508B9277M60 Specifications

Manufacturer Part NumberB43508B9277M60ManufacturerEPCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43508Capacitance270µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)400 Mom @ 100HzDifferium @ Temp.3000 Hrs @ 105°COperating Temp.400°C + 105°COperating Temp.40°C + 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance640 mOhmsLad Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max).Surface Mount Land Size-Mounting TypeThrough HolePolacing Type-	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43508Capacitance270µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)460 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-116A @ 100HzLied Spacing0.394" (10.00mm)Lied Spacing0.994" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-<	Manufacturer Part Number	B43508B9277M60
IdentifyAluminum Electrolytic CapacitonsPackageRadial, Can - Snap-InSeriesB43508Capacitance270µFTolerance20%Voltage - Rated400VESR (Equivalent Series Resistance)600 mOhm @ 100HzDerating Temper3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Hogh Frequency-Impedance640 mOhmsLad Spacing0.394" (10.0mm)Size / Dimension0.984" Dia (25.0mm)Size / Dimension1.654" (42.0mm)Surface Mount Land Size-Mounting TypeMountes CapacitanesPackage / CaseMaila, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43508Capacitance270µFTolerance20%Voltage - Rated400VESR (Equivalent Series Resistance)460 mOhm @ 100HzDerating @ Temper3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency1.16A @ 100HzRippe Current - High Frequency6.Lad Spacing0.394" (10.00mm)Size / Dimension0.594" Dia (25.00mm)Size / Dimension1.654" (42.00mm)Surface Mount Land Size-Hounting TypeFirough HolePackage / CaseKadia, Can - Snap-In	Category	Capacitors
SeriesB43508Capacitance270µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)460 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency1.16A @ 100HzInpedance640 mOhmsSize / Dimension0.994" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)-Mounting Type-Polaring TypeRough HoleSurface Mount Land Size-Polaring TypeThrough HolePolaring Type-Stare / CaseRadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance270µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)460 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency.116A @ 100HzImpedance640 mOhmsSize / Dimension0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Surface Mount Land Size.Mounting TypeTurough HolePackage / CaseKadia (Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±0%Yoltage - Rated400VESR (Equivalent Series Resistance)460 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.16A @ 100HzImpedance640 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Series	B43508
Voltage - Rated400VESR (Equivalent Series Resistance)460 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.16A @ 100HzImpedance640 mOhmsIcad Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Capacitance	270µF
C460 mOhm @ 100HzESR (Equivalent Series Resistance)460 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.16A @ 100HzRipple Current - High Frequency-Inneedance640 mOhnmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Tolerance	$\pm 20\%$
Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.16A @ 100HzRipple Current - High Frequency-Impedance640 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Voltage - Rated	400V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.16A @ 100HzRipple Current - High Frequency-Impedance640 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadia, Can - Snap-In	ESR (Equivalent Series Resistance)	460 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.16A @ 100HzRipple Current - High Frequency-Impedance640 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	3000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.16A @ 100HzRipple Current - High Frequency-Impedance640 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	$-40^{\circ}\mathrm{C} \sim 105^{\circ}\mathrm{C}$
Ripple Current - Low Frequency1.16A @ 100HzRipple Current - High Frequency-Impedance640 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a constraint of the product of t	Applications	General Purpose
Impedance640 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	1.16A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	640 mOhms
Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	0.984" Dia (25.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.654" (42.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
	Package / Case	Radial, Can - Snap-In
Report error		Report errors?

#### B43508B9277M60 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

## B43508B9277M60 Payment Methods



If you have any question about B43508B9277M60, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com