



B43508B9277M82 Information

Heisener.com

Part Number B43508B9277M82 Manufacturer EPCOS (TDK) Category

Capacitors

Aluminum Electrolytic Capacitors Description CAP ALUM 270UF 20% 400V SNAP

Package Radial, Can - Snap-In

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43508B9277M82 Specifications

Manufacturer Part Number B43508B9277M82 Manufacturer EPCOS (TDK) Category Capacitors Package Radial, Can - Snap-In Series B43508 Capacitance 270μF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 460 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization General Purpose Ripple Current - Low Frequency 1.16A @ 100Hz Ripple Current - High Frequency - Impedance 60m/ms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.661" (42.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	4	
Category Capacitors Package Radial, Can - Snap-In Series B43508 Capacitance 270μF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 460 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.16A @ 100Hz Ripple Current - High Frequency - Impedance 640 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.661" (42.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Manufacturer Part Number	B43508B9277M82
Package Radial, Can - Snap-In Series B43508 Capacitance 270µF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 460 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.16A @ 100Hz Ripple Current - High Frequency - Impedance 640 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.661" (42.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Manufacturer	EPCOS (TDK)
Package Radial, Can - Snap-In Series B43508 Capacitance 270μF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 460 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.16A @ 100Hz Ripple Current - High Frequency - Impedance 640 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.661" (42.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Category	Capacitors
Series B43508 Capacitance 270µF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 460 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.16A @ 100Hz Ripple Current - High Frequency - Impedance 640 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.661" (42.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance 270μF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 460 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.16A @ 100Hz Ripple Current - High Frequency - Impedance 640 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.661" (42.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 460 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.16A @ 100Hz Ripple Current - High Frequency - Impedance 640 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.661" (42.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Series	B43508
Voltage - Rated400 VESR (Equivalent Series Resistance)460 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.16A @ 100HzRipple Current - High Frequency-Impedance640 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.661" (42.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Capacitance	270μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency 1.16A @ 100Hz Ripple Current - High Frequency Impedance 640 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.661" (42.20mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 640 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 3000 Hrs @ 105°C -40°C ~ 105°C Folionics General Purpose 1.16A @ 100Hz - 1.00Hz 1.16A @ 100Hz - 1.16A @ 100Hz - Through Hole Radial, Can - Snap-In	Voltage - Rated	400V
Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.16A @ 100Hz Ripple Current - High Frequency - Impedance 640 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.661" (42.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	ESR (Equivalent Series Resistance)	460 mOhm @ 100Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.16A @ 100Hz Ripple Current - High Frequency - Impedance 640 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.661" (42.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Lifetime @ Temp.	3000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency 1.16A @ 100Hz Ripple Current - High Frequency - Impedance 640 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.661" (42.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 640 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.661" (42.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Polarization	Polar
Ripple Current - High Frequency Impedance 640 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.661" (42.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Applications	General Purpose
Impedance 640 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.661" (42.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Ripple Current - Low Frequency	1.16A @ 100Hz
Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.661" (42.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.661" (42.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Impedance	640 mOhms
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Size / Dimension	0.984" Dia (25.00mm)
Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Height - Seated (Max)	1.661" (42.20mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
		Report errors?

B43508B9277M82 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43508B9277M82 Payment Methods



















B43508B9277M82 Shipping Methods













If you have any question about B43508B9277M82, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com