



### B43508B9477M62 Information

Heisener.com

For Reference Only

Part Number B43508B9477M62
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

**Description** CAP ALUM 470UF 20% 400V SNAP

Package Radial, Can - Snap-In

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## B43508B9477M62 Specifications

Manufacturer Part NumberB43508B9477M62ManufacturerEPCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43508Capacitance470μFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)260 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°C
Category Capacitors Aluminum Electrolytic Capacitors  Package Radial, Can - Snap-In  Series B43508 Capacitance 470µF  Tolerance ±20% Voltage - Rated 400V  ESR (Equivalent Series Resistance) 260 mOhm @ 100Hz
Aluminum Electrolytic Capacitors         Package       Radial, Can - Snap-In         Series       B43508         Capacitance       470μF         Tolerance       ±20%         Voltage - Rated       400V         ESR (Equivalent Series Resistance)       260 mOhm @ 100Hz
PackageRadial, Can - Snap-InSeriesB43508Capacitance470μFTolerance $\pm 20\%$ Voltage - Rated400VESR (Equivalent Series Resistance)260 mOhm @ 100Hz
SeriesB43508Capacitance $470\mu F$ Tolerance $\pm 20\%$ Voltage - Rated $400V$ ESR (Equivalent Series Resistance) $260 \text{ mOhm @ } 100\text{Hz}$
Capacitance $470\mu F$ Tolerance $\pm 20\%$ Voltage - Rated $400V$ ESR (Equivalent Series Resistance) $260 \text{ mOhm } @ 100\text{Hz}$
Tolerance $\pm 20\%$ Voltage - Rated $\pm 400$ V ESR (Equivalent Series Resistance) $\pm 20\%$ 260 mOhm @ 100Hz
Voltage - Rated 400V ESR (Equivalent Series Resistance) 260 mOhm @ 100Hz
ESR (Equivalent Series Resistance) 260 mOhm @ 100Hz
Lifetime @ Town 2000 Hrs @ 105°C
Lifetine & Temp.
Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$
Polarization Polar
Applications General Purpose
Ripple Current - Low Frequency 1.62A @ 100Hz
Ripple Current - High Frequency -
Impedance 370 mOhms
Lead Spacing 0.394" (10.00mm)
Size / Dimension 1.378" Dia (35.00mm)
Height - Seated (Max) 1.457" (37.00mm)
Surface Mount Land Size -
Mounting Type Through Hole
Package / Case Radial, Can - Snap-In
Report errors

#### **B43508B9477M62 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### B43508B9477M62 Payment Methods





















## B43508B9477M62 Shipping Methods













If you have any question about B43508B9477M62, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com