

# B43508B9477M67

#### B43508B9477M67 Information

Heisener.com	 B43508B9477M67 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 470UF 20% 400V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### B43508B9477M67 Specifications

Manufacturer Part NumberB43508B9477M67ManufacturerEPCOS (TDK)CategoryCapacitorsPackageAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43508Capacitance470µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)260 mOhm @ 100HzDerating Temperature40°C ~ 105°COperating Temperature60 and PurposeApplicationsGeneral PurposeRipbe Current - Low Frequency1.62A @ 100HzIngedance370 mOhmsLad Spacing0.394" (10.0mm)Size / Dimension1.378" Dia (35.00mm)Manufacturer Low Stated (Max)1.457" (37.00mm)	
CategoryCapacitorsPackageRadial, Can - Snap-InSeriesRadial, Can - Snap-InSeriesB43508Capacitance470µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)260 mOhm @ 100HzDerating Temper3000 Hrs @ 105°COperating Temperature44°C ~ 105°CPolarizationReinel PurposeRipple Current - High Frequency6Gneral PurposeRipple Current - High Frequency370 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.457" (37.00mm)	
Huminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43508Capacitance470µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)260 mOhm @ 100HzDerating Temper3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeApplications6.2A @ 100HzRipple Current - High Frequency1.62A @ 100HzInpedance370 mOhmsLead Spacing3.94" (10.00mm)Hight - Seated (Max)1.457" (37.00mm)	
PackageRadial, Can - Snap-InSeriesB43508Capacitance470µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)260 mOhm @ 100HzDiferime @ Temp.3000 Hrs @ 105°COperating Temperature44°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - High Frequency.Inpedance370 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.457" (37.00mm)	
Series B43508   Capacitance 470μF   Tolerance ±20%   Voltage - Rated 400V   ESR (Equivalent Series Resistance) 260 mOhm @ 100Hz   Lifetime @ Temp. 3000 Hrs @ 105°C   Operating Temperature -40°C ~ 105°C   Polarization Polar   Applications General Purpose   Ripple Current - High Frequency 1.62A @ 100Hz   Inmedance 370 mOhms   Lead Spacing 0.394" (10.00mm)   Size / Dimension 1.378" Dia (35.00mm)	
Capacitance470µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)260 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency1.62A @ 100HzImpedance370 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.457" (37.00mm)	
Tolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)260 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.62A @ 100HzRipple Current - High Frequency370 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.457" (37.00mm)	
Voltage - Rated400VESR (Equivalent Series Resistance)260 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.62A @ 100HzRipple Current - High Frequency-Impedance370 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.457" (37.00mm)	
ESR (Equivalent Series Resistance)260 mOhm @ 100HzESR (Equivalent Series Resistance)260 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.62A @ 100HzRipple Current - High Frequency-Impedance370 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.457" (37.00mm)	
Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.62A @ 100HzRipple Current - High Frequency-Impedance370 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.457" (37.00mm)	
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.62A @ 100HzRipple Current - High Frequency-Impedance370 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.457" (37.00mm)	
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.62A @ 100HzRipple Current - High Frequency-Impedance370 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.457" (37.00mm)	
ApplicationsGeneral PurposeRipple Current - Low Frequency1.62A @ 100HzRipple Current - High Frequency-Impedance370 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.457" (37.00mm)	
Ripple Current - Low Frequency1.62A @ 100HzRipple Current - High Frequency-Impedance370 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.457" (37.00mm)	
In Provide and	
Impedance370 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.457" (37.00mm)	
Lead Spacing 0.394" (10.00mm)   Size / Dimension 1.378" Dia (35.00mm)   Height - Seated (Max) 1.457" (37.00mm)	
Size / Dimension 1.378" Dia (35.00mm)   Height - Seated (Max) 1.457" (37.00mm)	
Height - Seated (Max) 1.457" (37.00mm)	
-	
Surface Mount Land Size -	
Mounting Type Through Hole	
Package / Case Radial, Can - Snap-In	
Report	ort errors?

#### B43508B9477M67 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### B43508B9477M67 Payment Methods



If you have any question about B43508B9477M67, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com