

B43508C5157M80

B43508C5157M80 Information

Heisener.com	 B43508C5157M80 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 150UF 20% 450V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43508C5157M80 Specifications

Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series B43508 Capacitance 150µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 820 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Impedance 1.15 Ohms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.071" (27.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Kadial, Can - Snap-In	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43508Capacitance150µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)820 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency880mA @ 100HzRipple Current - High Frequency-Impedance1.15 OhmsLied Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43508C5157M80
Aluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43508Capacitance150µFTolerance-20%Voltage - Rated450VESR (Equivalent Series Resistance)820 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationFolaraApplicationsGeneral PurposeRipple Current - High Frequency-Impedance1.15 OhmsLad Spacing0.394" (10.0mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)-Surface Mount Land Size-Package / CaseRadial, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43508Capacitance150µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)820 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeRiple Current - Low Frequency880mA @ 100HzRiple Current - High Frequency-Impedance1.15 OhmsLad Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max).071" (27.20mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43508Capacitance150µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)820 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency880mA @ 100HzLinedance1.15 OhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance150µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)820 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency880mA @ 100HzLingedance1.15 OhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Package	Radial, Can - Snap-In
±2% Yoltage - Rated ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 820 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 880mA @ 100Hz Impedance 1.15 Ohms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.071" (27.20mm) Height - Seated (Max) 1.071" (27.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Series	B43508
Voltage - Rated450VESR (Equivalent Series Resistance)820 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency880mA @ 100HzLead Spacing.Impedance1.15 OhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max).Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Capacitance	150µF
Constraint820 mOhm @ 100HzESR (Equivalent Series Resistance)820 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency880mA @ 100HzRipple Current - High Frequency-Impedance1.15 OhmsLead Spacing0.394" (10.00mm)Size / Dimension1.071" (27.20mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency880mA @ 100HzRipple Current - High Frequency-Impedance1.15 OhmsLead Spacing0.394" (10.00mm)Size / Dimension1.071" (27.20mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Voltage - Rated	450V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency880mA @ 100HzRipple Current - High Frequency-Impedance1.15 OhmsLead Spacing0.394" (10.00mm)Size / Dimension1.081" Dia (30.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeFackage / CaseRadial, Can - Snap-InRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	820 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency880mA @ 100HzRipple Current - High Frequency-Impedance1.15 OhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	3000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency880mA @ 100HzRipple Current - High Frequency-Impedance1.15 OhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40° C ~ 105° C
Ripple Current - Low Frequency880mA @ 100HzRipple Current - High Frequency-Impedance1.15 OhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a constraint of the product of t	Applications	General Purpose
Impedance1.15 OhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	880mA @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	1.15 Ohms
Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	1.181" Dia (30.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.071" (27.20mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
		Report errors?

B43508C5157M80 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43508C5157M80 Payment Methods





If you have any question about B43508C5157M80, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com