

B43508C5187M60

B43508C5187M60 Information

Heisener.com	 B43508C5187M60 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 180UF 20% 450V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43508C5187M60 Specifications

Manufacturer Part NumberB43508C5187M60ManufacturerEPCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43508Capacitance180µFTolerance±20%Voltage - Rated800 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizon90arApplicationsGeneral PurposeRipple Current - High Frequency-Impedance960 mOhmsLided Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Size / Dimension1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePower Mount Size-Mounting TypeThrough HolePancer Mount Size-Power Mount Size-Pancer Mount Size-Power Power Pow		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43508Capacitance180µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)680 mOhm @ 100HzDerating Temperature3000 Hrs @ 105°COperating Temperature90arApplicationsGeneral PurposeRipple Current - Hogh Frequency.Impedance960 mOhmsLiad Spacing0.394" (10.00mm)Size / Dimension1.81" Dia (30.00mm)Height - Seated (Max).260" (32.00mm)Surface Mount Land Size.Mounting TypeAidi, Can - Snap-In	Manufacturer Part Number	B43508C5187M60
IdentifyAluninum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43508Capacitance180µFTolerance±20%Voltage - Rated680 mOhm @ 100HzESR (Equivalent Series Resistance)680 mOhm @ 100HzDerating Temper3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency1.01A @ 100HzRipple Current - High Frequency960 mOhmsLead Spacing0.394" (1.00mm)Size / Dimension1.181" Dia (30.00mm)Hight - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Hounting TypeMaila, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43508Capacitance180µFTolerance±20%Voltage - Rated680 mOhm @ 100HzESR (Equivalent Series Resistance)680 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency.101A @ 100HzImpedance960 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeFurough HolePackage / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43508Capacitance180µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)680 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency1.01A @ 100HzInpedance960 mOhmsSize / Dimension1.181° Dia (30.00mm)Size / Dimension1.260° (32.00mm)Height - Seated (Max)-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance180µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)680 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.01A @ 100HzImpedance960 mOhmsSize / Dimension1.381" Dia (30.00mm)Size / Dimension1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadia, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±0%Voltage - Rated450VESR (Equivalent Series Resistance)680 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.01A @ 100HzRipple Current - High Frequency-Innedance960 mOhmsIcad Spacing0.394" (10.00mm)Size / Dimension1.81" Dia (30.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Series	B43508
Voltage - Rated450VESR (Equivalent Series Resistance)680 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.01A @ 100HzRipple Current - High Frequency960 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeRatial, Can - Snap-In	Capacitance	180µF
C680 mOhm @ 100HzESR (Equivalent Series Resistance)680 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.01A @ 100HzRipple Current - High Frequency960 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeFackage / Case	Tolerance	±20%
Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.01A @ 100HzRipple Current - High Frequency-Impedance960 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeFackage / CasePackage / CaseRadial, Can - Snap-In	Voltage - Rated	450V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.01A @ 100HzRipple Current - High Frequency-Impedance960 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	680 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.01A @ 100HzRipple Current - High Frequency-Impedance960 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	3000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.01A @ 100HzRipple Current - High Frequency-Impedance960 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency1.01A @ 100HzRipple Current - High Frequency-Impedance960 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a rangeRipple Current - High Frequency-Impedance960 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Applications	General Purpose
Impedance960 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	1.01A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	960 mOhms
Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	1.181" Dia (30.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.260" (32.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Deport over	Package / Case	Radial, Can - Snap-In
Report en		Report errors?

B43508C5187M60 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43508C5187M60 Payment Methods



If you have any question about B43508C5187M60, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com