

B43508C5227M60

est a Quote

B43508C5227M60 Information

Heisener.com	Part Number	B43508C5227M60	
	Manufacturer	EPCOS (TDK)	
	Category	Capacitors Aluminum Electrolytic Capacitors	
	Description	CAP ALUM 220UF 20% 450V SNAP	- 291
	Package	Radial, Can - Snap-In	신한
		For the pricing/inventory/lead time, please contact	
		us Wabaita: https://www.baisapar.com	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Reque

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43508C5227M60 Specifications

Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series B43508 Capacitance 20µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 560 mOhm @ 100Hz Diperating Temperature -40°C ~ 105°C Polarization General Purpose Applications General Purpose Ripple Current - Low Frequency - Impedance 0394" (10.00mm) Lead Spacing 1.181" Dia (30.00mm) Size / Dimension 1.260" (32.00mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43508Capacitance220µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)560 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency1.11A @ 100HzRipple Current - High Frequency-Inpedance790 mOhmsLied Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Manufacturer Part Number	B43508C5227M60
Aluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43508Capacitance220µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)60 mOhm @ 100HzDerartig Temper3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarization70 arApplicationsGeneral PurposeRipple Current - Low Frequency1.11A @ 100HzRipple Current - High Frequency-Inpedance0394" (10.00mm)Liad Spacing1.81" Dia (30.00mm)Size / Dimension1.81" Dia (30.00mm)Size / Dimension1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43508Capacitance220µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)560 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency1.11A @ 100HzImpedance.90 mOhmsLiad Spacing.394" (10.00mm)Size / Dimension1.81" Dia (30.00mm)Height - Seated (Max).200" (32.00mm)Surface Mount Land Size.Mounting TypeThrough Hole	Category	Capacitors
SeriesB43508Capacitance220µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)560 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.11A @ 100HzImpedance790 mOhmsLead Spacing0.394" (10.00mm)Size / Dinension1.181" Dia (30.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole		Aluminum Electrolytic Capacitors
Capacitance220µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)560 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency-Impedance790 mOhmsLad Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough Hole	Package	Radial, Can - Snap-In
Tolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)560 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency.Impedance790 mOhmsLad Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Series	B43508
Voltage - Rated450VESR (Equivalent Series Resistance)560 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.11A @ 100HzRipple Current - High Frequency-Impedance790 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)-Mounting TypeThrough Hole	Capacitance	220µF
ESR 560 mOhm @ 100Hz ESR (Equivalent Series Resistance) 560 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.11A @ 100Hz Impedance 790 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.260" (32.00mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole	Tolerance	±20%
Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeApple Current - Low Frequency1.11A @ 100HzRipple Current - High Frequency-Impedance790 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Voltage - Rated	450V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.11A @ 100HzRipple Current - High Frequency-Impedance790 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	ESR (Equivalent Series Resistance)	560 mOhm @ 100Hz
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.11A @ 100HzRipple Current - High Frequency-Impedance790 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Lifetime @ Temp.	3000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.11A @ 100HzRipple Current - High Frequency-Impedance790 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency1.11A @ 100HzRipple Current - High Frequency-Impedance790 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Polarization	Polar
In a constraint of a constrain	Applications	General Purpose
Impedance790 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Ripple Current - Low Frequency	1.11A @ 100Hz
I0.394" (10.00mm)Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Ripple Current - High Frequency	-
Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Impedance	790 mOhms
Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough Hole	Size / Dimension	1.181" Dia (30.00mm)
Mounting Type Through Hole	Height - Seated (Max)	1.260" (32.00mm)
	Surface Mount Land Size	-
Package / Case Radial, Can - Snap-In	Mounting Type	Through Hole
	Package / Case	Radial, Can - Snap-In
Report errors?		Report errors?

B43508C5227M60 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43508C5227M60 Payment Methods





If you have any question about B43508C5227M60, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com