

B43508C5277M80

B43508C5277M80 Information

Heisener.com	 B43508C5277M80 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 270UF 20% 450V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43508C5277M80 Specifications

Anufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series B43508 Capacitance 270µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 460 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization General Purpose Ripple Current - Low Frequency I.31A @ 100Hz Ripple Current - High Frequency - Impedance 0.394" (10.00mm) Lied Spacing 1.378" Dia (35.00mm) Size / Dimension 1.378" Dia (35.00mm) Size / Dimension 1.378" Dia (35.00mm)		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43508Capacitance270µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)460 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.31A @ 100HzLifeght - Seated (Max)1.378" Dia (35.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43508C5277M80
Aluminum Electrolytic CapacitonsPackageRadial, Can - Snap-InPackageB43508SeriesB43508Capacitance270µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)640 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeRiple Current - Low Frequency.131A @ 100HzRiple Current - High Frequency640 mOhmsSize / Dimension1.378° Dia (35.00mm)Size / Dimension1.268° (32.20mm)Height - Seated (Max).1268° (32.20mm)Surface Mount Land Size.Package / CaseKadia, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43508Capacitance270µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)460 mOhm @ 100HzESR (Equivalent Series Resistance)3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarigationsGeneral PurposeRipple Current - Low Frequency640 mOhmsRipple Current - High Frequency-Impedance640 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.268" (32.20mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Package / CaseRadia, Can - Snap-In	Category	Capacitors
SeriesB43508Capacitance270µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)460 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.31A @ 100HzRipple Current - High Frequency-Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance270µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)460 mOhm @ 100HzESR (Equivalent Series Resistance)3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Mapedance640 mOhmsLied Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)-Surface Mount Land Size-Poactage / CaseRial, Can - Snap-In	Package	Radial, Can - Snap-In
Polerance±0%Voltage - Rated450VESR (Equivalent Series Resistance)460 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.31A @ 100HzRipple Current - High Frequency-Impedance640 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Package / CaseRatial, Can - Snap-In	Series	B43508
Voltage - Rated450VESR (Equivalent Series Resistance)460 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.31A @ 100HzRipple Current - High Frequency-Impedance640 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.268" (32.20mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In	Capacitance	270µF
Constraint460 mOhm @ 100HzESR (Equivalent Series Resistance)460 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.31A @ 100HzRipple Current - High Frequency640 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarPolarizationsGeneral PurposeApplications1.31A @ 100HzRipple Current - Low Frequency-Impedance640 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Voltage - Rated	450V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.31A @ 100HzRipple Current - High Frequency-Impedance640 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	460 mOhm @ 100Hz
PolarizationPolarPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance640 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	3000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.31A @ 100HzRipple Current - High Frequency-Impedance640 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency1.31A @ 100HzRipple Current - High Frequency-Impedance640 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
Ripple Current - High Frequency-Impedance640 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Applications	General Purpose
Impedance640 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	1.31A @ 100Hz
IOutputLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	640 mOhms
Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	1.378" Dia (35.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.268" (32.20mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
		Report errors?

B43508C5277M80 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43508C5277M80 Payment Methods





If you have any question about B43508C5277M80, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com