

B43508C9227M62

B43508C9227M62 Information

Heisener.com	Part Number Manufacturer Category Description Package		
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43508C9227M62 Specifications

Manufacturer Part NumberB43508C9227M62ManufacturerEPCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43508Capacitance220µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)500 Mrs @ 105°COperating Temperature40°C ~ 105°CPolarizon5000 Hrs @ 105°COperating Temperature90arApplicationsGeneral PurposeRipple Current - Low Frequency980mA @ 100HzLippedance.Lippedance.309 (10.00mm)Lippedance.309 (10.00mm)Lippedance.309 (10.00mm)Size / Dimension.181" Dia (30.00mm)Size / Dimension.181" Dia (30.00mm)Sirae Mount Land Size.Mounting Type.Pance.Ringel Charent Low Frequency.Sirae Mount Land Size.Sirae Mount Land Size.Sira		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43508Capacitance20µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)560 mOhm @ 100HzDerating Temper3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency980mA @ 100HzRipple Current - High Frequency-Impedance9300 Mrs @ 100HzLiad Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Hight - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeFhrough HolePackage / CaseKadia, Can - Snap-In	Manufacturer Part Number	B43508C9227M62
IdentifyAluminum Electrolytic CapacitonsPackageRadial, Can - Snap-InSeriesB43508Capacitance20\/FTolerance20\/FVoltage - Rated400VESR (Equivalent Series Resistance)600 mOhn @ 100HzDerating Temper3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationFeareal PurposeApplicationsGeneral PurposeRipple Current - Hog Frequency980mA @ 100HzRipple Current - High Frequency0394' (10.00mm)Lead Spacing0.394'' (10.00mm)Size / Dimension1.181'' Dia (30.00mL)Hight - Seated (Max).Surface Mount Land Size-Hounting TypeMounting TypePackage / CaseKaila, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43508Capacitance20µFTolerance400VVoltage - Rated600 mOhm @ 100 HzESR (Equivalent Series Resistance)500 mOhm @ 100 HzOperating Temperature3000 Hrs @ 105°COperating Temperature40°C ~ 105°CApplications6cneral PurposeRipple Current - Low Frequency980mA @ 100 HzImpedance70 mOhmsImpedance0394" (10.00mm)Size / Dimension1181" Dia (30.00mm)Size / Dimension1071" (72.20mm)Surface Mount Land Size-Mounting TypeFrough HolePackage / CaseKaila, Can - Snap-In	Category	Capacitors
SeriesB43508Capacitance220µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)560 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency980mA @ 100HzLiad Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Size / Dimension1.071" (27.20mm)Height - Seated (Max)-Mounting TypeThrough HolePackage / CaseKadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance220µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)560 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency980mA @ 100HzImpedance990 mOhmsSize / Dimension1.181° Dia (30.00mm)Size / Dimension1.071° (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKalia, Can - Snap-In	Package	Radial, Can - Snap-In
Tolrance±0%Voltage - Rated400VESR (Equivalent Series Resistance)560 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency980mA @ 100HzImpedance790 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeFackage / CaseRated Spacing-Stare Conservert-Stare Conservert-Surface Mount Land Size-Stare Mount Land Size-Stare Conservert-Stare Co	Series	B43508
Voltage - Rated400VESR (Equivalent Series Resistance)560 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency980mA @ 100HzImpedance-Impedance790 mOhmsIsze / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeFrequencyPackage / CaseRadial, Can - Snap-In	Capacitance	220µF
For ESR (Equivalent Series Resistance)560 mOhm @ 100HzESR (Equivalent Series Resistance)560 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency980mA @ 100HzRipple Current - High Frequency-Impedance790 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max).Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency980mA @ 100HzRipple Current - High Frequency-Impedance790 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)5.071" (27.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Voltage - Rated	400V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency980mA @ 100HzRipple Current - High Frequency-Impedance790 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	560 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency980mA @ 100HzRipple Current - High Frequency-Impedance790 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	3000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency980mA @ 100HzRipple Current - High Frequency-Impedance790 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)0.71" (27.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency980mA @ 100HzRipple Current - High Frequency-Impedance790 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a constraint of the product of t	Applications	General Purpose
Impedance790 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	980mA @ 100Hz
IILead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	790 mOhms
Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	1.181" Dia (30.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.071" (27.20mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report erro	Package / Case	Radial, Can - Snap-In
Reportent		Report errors?

B43508C9227M62 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43508C9227M62 Payment Methods





If you have any question about B43508C9227M62, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com