

## B43508E2158M60

#### B43508E2158M60 Information

Heisener.com	Part Number Manufacturer Category Description Package	B43508E2158M60 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 1500UF 20% 250V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### B43508E2158M60 Specifications

Manufacturer Part NumberB43508E2158M60ManufacturerEPCOS (TDK)CategoryCapacitorsCategoryCapacitorsPackageRadial, Can - Snap-InSeriesB43508Capacitance1500µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)75 mOhm @ 100HzDifterium @ Temp.3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationsGeneral PurposeRipple Current - Low Frequency2.95A @ 100HzLindequence110 mOhmsLad Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Size / Dimension2.244" (57.00mm)Mounting TypeThrough HoleRackage / CaseMounting Type	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43508Capacitance1500µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)75 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Imedance110 mOhmsLied Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeFhough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43508E2158M60
IdentifyAluminum Electrolytic CapacitonsPackageRadial, Can - Snap-InSeriesB43508Capacitance1500µFTolerance-20%Voltage - Rated50VESR (Equivalent Series Resistance)50 mOhm @ 100HzDerating Temper0000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Hogh Frequency2.95A @ 100HzImpedance110 mOhmsLad Spacing0.394" (10.0mm)Size / Dimension1.81" Dia (30.0mm)Size / Dimension2.244" (57.0mm)Muring TypeMountig TypePockage / CaseMaila, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43508Capacitance1500µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)75 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency2.95A @ 100HzImpedance110 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Size / Dimension2.44" (57.00mm)Surface Mount Land Size-Mounting TypeFinough HolePackage / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43508Capacitance1500µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)75 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency2.95A @ 100HzInpedance110 mOhmsSize / Dimension3.94" (10.00mm)Size / Dimension2.244" (57.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Hounting TypeThrough HolePackage / CaseRadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance1500μFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)75 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency2.95A @ 100HzInpedance110 mOhmsLad Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadia Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)75 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.95A @ 100HzImpedance110 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Series	B43508
Voltage - Rated250VESR (Equivalent Series Resistance)75 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.95A @ 100HzImpedance110 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Capacitance	1500µF
FSR (Equivalent Series Resistance)75 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.95A @ 100HzRipple Current - High Frequency-Impedance110 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In	Tolerance	$\pm 20\%$
Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.95A @ 100HzRipple Current - High Frequency-Impedance110 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Voltage - Rated	250V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.95A @ 100HzRipple Current - High Frequency-Impedance110 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	75 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.95A @ 100HzRipple Current - High Frequency-Impedance110 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	3000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency2.95A @ 100HzRipple Current - High Frequency-Impedance110 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	$-40^{\circ}\mathrm{C} \sim 105^{\circ}\mathrm{C}$
Ripple Current - Low Frequency2.95A @ 100HzRipple Current - High Frequency-Impedance110 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a constraint of a constrain	Applications	General Purpose
Impedance110 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	2.95A @ 100Hz
IILead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	110 mOhms
Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	1.181" Dia (30.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	2.244" (57.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
-	Package / Case	Radial, Can - Snap-In
Report error		Report errors?

#### B43508E2158M60 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

# B43508E2158M60 Payment Methods WIRE Transfer PayPal Methods B43508E2158M60 Shipping Methods Feelex. I CORO INFO

If you have any question about B43508E2158M60, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com