

B43508E2188M80

B43508E2188M80 Information

Heisener.com	B43508E2188M80 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 1800UF 20% 250V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43508E2188M80 Specifications

Manufacturer Part NumberB43508E2188M80ManufacturerEPCOS (TDK)CategoryCapacitorsCategoryCapacitorsPackageRadial, Can - Snap-InSeriesB43508Capacitance1800µFTolerance2050VVoltage - Rated250VESR (Equivalent Series Resistance)6500 Mm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeRipple Current - High Frequency.Impedance90 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Size / Dimension.Surface Mount Land Size.Mouning Type.Mouning TypeThrough HolePaceMouning TypePace.Report errer.	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43508Capacitance1800µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)65 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance90 mOhmsLead Spacing0.394" (10.00mm)Size / Dinension1.378" Dia (35.00mm)Sirface Mount Land Size-Mounting TypeFnough HolePackage / CaseRadia, Can - Snap-In	Manufacturer Part Number	B43508E2188M80
IdentifyAluminum Electrolytic CapacitonsPackageRadial, Can - Snap-InSeriesB43508Capacitance1800µFTolerance÷20%Voltage - Rated250VESR (Equivalent Series Resistance)65 mOhm @ 100HzDieraing Temper3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency-Kipple Current - High Frequency0.304"(10.00mm)Lead Spacing0.394"(10.00mm)Size / Dimension1.378"Dia (35.00m,10.0011)Hight - Seated (Max)2.055" (52.20mm)Surface Mount Land Size-Hounting TypeFnough HolePackage / CaseKadia, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43508Capacitance1800µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)65 mOhm @ 100HzDerating Temperature3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency2.75A @ 100HzRipple Current - High Frequency-Impedance0.394" (10.00mm)Size / Dimension1.378° Dia (35.00mm)Size / Dimension2.055" (52.20mm)Surface Mount Land Size-Mounting TypeFhough HolePackage / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43508Capacitance1800µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)65 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - High Frequency2.75A @ 100HzInpedance90 mOhmsSize / Dimension1.378" Dia (35.00mm)Size / Dimension2.055" (52.20mm)Height - Seated (Max)-Mounting TypeThrough HolePackage / CaseKadia, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance1800µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)65 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency2.75A @ 100HzInpedance90 mOhmsLad Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.055" (52.20mm)Surface Mount Land Size-Hounting TypeThrough HolePackage / CaseKali, Can - Snap-In	Package	Radial, Can - Snap-In
Tolarace±20%Voltage - Rated250VESR (Equivalent Series Resistance)65 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.75A @ 100HzImpedance90 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.055" (52.20mm)Surface Mount Land Size-Hounting TypeFhrough HolePackage / CaseRatial, Can - Snap-In	Series	B43508
Voltage - Rated250VESR (Equivalent Series Resistance)65 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.75A @ 100HzImpedance90 mOhmsIcad Spacing.338" I(10.00mm)Size / Dinension1.378" Dia (35.00mm)Height - Seated (Max)2.055" (52.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Capacitance	1800µF
FSR (Equivalent Series Resistance)65 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.75A @ 100HzRipple Current - High Frequency-Impedance90 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.055" (52.20mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.75A @ 100HzRipple Current - High Frequency-Impedance90 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.055" (52.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Voltage - Rated	250V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.75A @ 100HzRipple Current - High Frequency-Impedance90 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.055" (52.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	65 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.75A @ 100HzRipple Current - High Frequency-Impedance90 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.055" (52.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	3000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency2.75A @ 100HzRipple Current - High Frequency-Impedance90 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.055" (52.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency2.75A @ 100HzRipple Current - High Frequency-Impedance90 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.055" (52.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a constraint of the product of t	Applications	General Purpose
Impedance90 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.055" (52.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	2.75A @ 100Hz
IILead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.055" (52.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.055" (52.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	90 mOhms
Height - Seated (Max)2.055" (52.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	1.378" Dia (35.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	2.055" (52.20mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report error	Package / Case	Radial, Can - Snap-In
The point of the p		Report errors?

B43508E2188M80 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43508E2188M80 Payment Methods



If you have any question about B43508E2188M80, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com