



B43508F2397M80 Information

Heisener.com

Part Number B43508F2397M80
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 390UF 20% 250V SNAP

Package Radial, Can - Snap-In

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43508F2397M80 Specifications

Manufacturer Part Number B43508F2397M80 Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series B43508 Capacitance 390μF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) 300 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.3A @ 100Hz Ripple Current - High Frequency - Impedance 400 mOhms	*	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series B43508 Capacitance 390µF Tolerance ±20% Voltage - Rated ESR (Equivalent Series Resistance) 250V ESR (Equivalent Series Resistance) 300 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency - Impedance 400 mOhms	Manufacturer Part Number	B43508F2397M80
Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series B43508 Capacitance 390μF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) 300 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 400 mOhms	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43508Capacitance390μFTolerance $\pm 20\%$ Voltage - Rated250VESR (Equivalent Series Resistance)300 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105 °COperating Temperature -40 °C ~ 105 °CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency $1.3A$ @ 100 HzRipple Current - High Frequency-Impedance 400 mOhms	Category	Capacitors
SeriesB43508Capacitance390μFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)300 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.3A @ 100HzRipple Current - High Frequency-Impedance400 mOhms		Aluminum Electrolytic Capacitors
Capacitance390μFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)300 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.3A @ 100HzRipple Current - High Frequency-Impedance400 mOhms	Package	Radial, Can - Snap-In
Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) 300 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.3A @ 100Hz Ripple Current - High Frequency - Impedance 400 mOhms	Series	B43508
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 250V 250V 200 mOhm @ 100Hz 300 mOhm @ 100Hz 3000 Hrs @ 105°C Polar 200 C ~ 105°C Polar 300 Polar Applications General Purpose 1.3A @ 100Hz - 400 mOhms	Capacitance	390μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 300 mOhm @ 100Hz -40°C ~ 105°C -40°C ~ 105°	Tolerance	±20%
Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.3A @ 100Hz Ripple Current - High Frequency - Impedance 400 mOhms	Voltage - Rated	250V
Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance -40°C ~ 105°C Polar General Purpose 1.3A @ 100Hz -400 mOhms	ESR (Equivalent Series Resistance)	300 mOhm @ 100Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.3A @ 100Hz Ripple Current - High Frequency - Impedance 400 mOhms	Lifetime @ Temp.	3000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency 1.3A @ 100Hz Ripple Current - High Frequency - Impedance 400 mOhms	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 1.3A @ 100Hz - 400 mOhms	Polarization	Polar
Ripple Current - High Frequency - Impedance - 400 mOhms	Applications	General Purpose
Impedance 400 mOhms	Ripple Current - Low Frequency	1.3A @ 100Hz
	Ripple Current - High Frequency	-
Load Specing (10,00mm)	Impedance	400 mOhms
Lead Spacing 0.394 (10.00mm)	Lead Spacing	0.394" (10.00mm)
Size / Dimension 0.984" Dia (25.00mm)	Size / Dimension	0.984" Dia (25.00mm)
Height - Seated (Max) 1.268" (32.20mm)	Height - Seated (Max)	1.268" (32.20mm)
Surface Mount Land Size -	Surface Mount Land Size	-
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Radial, Can - Snap-In	Package / Case	Radial, Can - Snap-In
Report errors?		Report errors?

B43508F2397M80 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43508F2397M80 Payment Methods



















B43508F2397M80 Shipping Methods













If you have any question about B43508F2397M80, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com