

# B43510A3827M87

#### B43510A3827M87 Information

Heisener.com Endelserver Carls Serv	 B43510A3827M87 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 820UF 20% 385V SNAP Radial, Can - Snap-In - 4 Lead For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### B43510A3827M87 Specifications

Series B43510   Capacitance 820µF   Tolerance ±20%   Voltage - Rated 385V   ESR (Equivalent Series Resistance) 85 mOhm @ 100Hz   Lifetime @ Temp. 5000 Hrs @ 85°C   Operating Temperature 40°C ~ 85°C   Polar 6000 Hrs @ 00Hz   Application General Purpose   Ripple Current - Low Frequency 4.11A @ 100Hz   Impedance 110 mOhms   Liagh Spacing 0.984" (25.00mm)   Size / Dimension 1.378" Dia (35.00mm)   Surface Mount Land Size -   Mounting Type -   Package / Case Kadial, Can - Snap-In - 4 Lead	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 4 LeadSeriesB43510Capacitance820µFTolerance±20%Voltage - Rated385VESR (Equivalent Series Resistance)85 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 85°COperating Temperature90larApplicationsGeneral PurposeRipple Current - High Frequency4.11A @ 100HzRipple Current - High Frequency10 mOhmsLied Spacing0.984" (25.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.449" (62.20mm)Surface Mount Land Size-Mounting TypeFrough HolePackage / CaseRatial, Can - Snap-In - 4 Lead	Manufacturer Part Number	B43510A3827M87
Auminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 4 LeadSeriesB43510Capacitance820µFTolerance±20%Voltage - Rated855 VESR (Equivalent Series Resistance)85 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-1110 mOhmsLided Spacing0.984" (25.00mm)Size / Dimension1.378" Dia (35.00mm)Size / Dimension-378" Dia (35.00mm)Height - Seated (Max)2.449" (62.20mm)Surface Mount Land Size-Mounting TypeFirough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-In - 4 LeadSeriesB43510Capacitance820µFTolerance±20%Voltage - Rated385VESR (Equivalent Series Resistance)S5 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 85°COperating Temperature6000 Hrs @ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.11A @ 100HzRipple Current - High Frequency0.984" (25.00mm)Lied Spacing0.984" (25.00mm)Siz / Dimension1.378" Dia (35.00mm)Kirface Mount Land Size-Mounting TypeHrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Category	Capacitors
Series B43510   Capacitance 820µF   Tolerance ±20%   Voltage - Rated 385V   ESR (Equivalent Series Resistance) 85 mOhm @ 100Hz   Lifetime @ Temp. 5000 Hrs @ 85°C   Operating Temperature 40°C ~ 85°C   Polar 6000 Hrs @ 00Hz   Application General Purpose   Ripple Current - Low Frequency 4.11A @ 100Hz   Impedance 110 mOhms   Liagh Spacing 0.984" (25.00mm)   Size / Dimension 1.378" Dia (35.00mm)   Surface Mount Land Size -   Mounting Type -   Package / Case Kadial, Can - Snap-In - 4 Lead		Aluminum Electrolytic Capacitors
Capacitance820μFColerance±20%Voltage - Rated385VESR (Equivalent Series Resistance)85 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance110 mOhmsLead Spacing0.984" (25.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.449" (62.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Package	Radial, Can - Snap-In - 4 Lead
Tolerance±2%Voltage - Rated385VESR (Equivalent Series Resistance)85 mOhn @ 100HzLifetime @ Temp.5000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.11A @ 100HzRipple Current - High Frequency-Impedance110 mOhmsLead Spacing0.984" (25.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.449" (62.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Series	B43510
Voltage - Rated385VESR (Equivalent Series Resistance)85 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.11A @ 100HzRipple Current - High Frequency-Impedance110 mOhmsLead Spacing0.984" (25.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.449" (62.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In - 4 Lead	Capacitance	820µF
ESR (Equivalent Series Resistance) 85 mOhm @ 100Hz   Lifetime @ Temp. 5000 Hrs @ 85°C   Operating Temperature -40°C ~ 85°C   Polar Polar   Applications General Purpose   Ripple Current - Low Frequency 4.11A @ 100Hz   Ripple Current - High Frequency -   Impedance 110 mOhms   Size / Dimension 0.984" (25.00mm)   Size / Dimension 1.378" Dia (35.00mm)   Surface Mount Land Size -   Mounting Type Fhough Hole   Package / Case Ridal, Can - Snap-In - 4 Lead	Tolerance	$\pm 20\%$
Lifetime @ Temp.5000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.11A @ 100HzRipple Current - High Frequency-Impedance110 mOhmsLead Spacing0.984" (25.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.449" (62.20mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In - 4 Lead	Voltage - Rated	385V
Operating Temperature -40°C ~ 85°C   Polarization Polar   Applications General Purpose   Ripple Current - Low Frequency 4.11A @ 100Hz   Ripple Current - High Frequency -   Impedance 110 mOhms   Lead Spacing 0.984" (25.00mm)   Size / Dimension 1.378" Dia (35.00mm)   Height - Seated (Max) 2.449" (62.20mm)   Surface Mount Land Size -   Mounting Type Fhough Hole   Package / Case Radial, Can - Snap-In - 4 Lead	ESR (Equivalent Series Resistance)	85 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.11A @ 100HzRipple Current - High Frequency-Impedance110 mOhmsLead Spacing0.984" (25.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.449" (62.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Lifetime @ Temp.	5000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency4.11A @ 100HzRipple Current - High Frequency-Impedance110 mOhmsLead Spacing0.984" (25.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.449" (62.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Operating Temperature	$-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$
Ripple Current - Low Frequency4.11A @ 100HzRipple Current - High Frequency-Impedance110 mOhmsLead Spacing0.984" (25.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.449" (62.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Polarization	Polar
In our and programRipple Current - High Frequency-Impedance110 mOhmsLead Spacing0.984" (25.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.449" (62.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Applications	General Purpose
Impedance110 mOhmsLead Spacing0.984" (25.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.449" (62.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Ripple Current - Low Frequency	4.11A @ 100Hz
Lead Spacing0.984" (25.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.449" (62.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Ripple Current - High Frequency	-
Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.449" (62.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Impedance	110 mOhms
Height - Seated (Max)2.449" (62.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Lead Spacing	0.984" (25.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Size / Dimension	1.378" Dia (35.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Height - Seated (Max)	2.449" (62.20mm)
Package / Case Radial, Can - Snap-In - 4 Lead	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors	Package / Case	Radial, Can - Snap-In - 4 Lead
		Report errors?

#### B43510A3827M87 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE ELARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### B43510A3827M87 Payment Methods



If you have any question about B43510A3827M87, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com