

B43510A827M80 Information

Manufact Category Heisener.com

Part Number B43510A827M80
Manufacturer EPCOS (TDK)

Capacitors
Aluminum Electrolytic Capacitors

Description CAP ALUM 820UF 20% 420V SNAP

Package Radial, Can - Snap-In - 4 Lead

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43510A827M80 Specifications

Manufacturer Part Number B43510A827M80 Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In - 4 Lead Series B43510 Capacitance 820µF Tolerance ±20% Voltage - Rated 420V ESR (Equivalent Series Resistance) 150 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 4.36A @ 100Hz Ripple Current - High Frequency - Impedance 210 mOhms Lead Spacing 0.984" (25.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.843" (72.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead		
Category Capacitors Package Radial, Can - Snap-In - 4 Lead Series B43510 Capacitance 820µF Tolerance ±20% Voltage - Rated 420V ESR (Equivalent Series Resistance) 150 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 4.36A @ 100Hz Ripple Current - High Frequency - Impedance 210 mOhms Lead Spacing 0.984" (25.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.843" (72.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Manufacturer Part Number	B43510A827M80
Package Radial, Can - Snap-In - 4 Lead Series B43510 Capacitance 820µF Tolerance ±20% Voltage - Rated 420V ESR (Equivalent Series Resistance) 150 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 4.36A @ 100Hz Ripple Current - High Frequency - Impedance 210 mOhms Lead Spacing 0.984" (25.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.843" (72.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-In - 4 LeadSeriesB43510Capacitance\$20μFTolerance±20%Voltage - Rated420VESR (Equivalent Series Resistance)150 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.36A @ 100HzRipple Current - High Frequency-Impedance210 mOhmsLead Spacing0.984" (25.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.843" (72.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Category	Capacitors
Series B43510 Capacitance 820µF Tolerance ±20% Voltage - Rated 420V ESR (Equivalent Series Resistance) 150 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 4.36A @ 100Hz Ripple Current - High Frequency - Impedance 210 mOhms Lead Spacing 0.984" (25.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.843" (72.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead		Aluminum Electrolytic Capacitors
Capacitance 820μF Tolerance ±20% Voltage - Rated 420V ESR (Equivalent Series Resistance) 150 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 4.36A @ 100Hz Ripple Current - High Frequency - Impedance 210 mOhms Lead Spacing 0.984" (25.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.843" (72.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Package	Radial, Can - Snap-In - 4 Lead
Tolerance ±20% Voltage - Rated 420V ESR (Equivalent Series Resistance) 150 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 4.36A @ 100Hz Ripple Current - High Frequency - Impedance 210 mOhms Lead Spacing 0.984" (25.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.843" (72.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Series	B43510
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency - Impedance 210 mOhms Lead Spacing 0.984" (25.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case 150 mOhm @ 100Hz 600Hrs 6	Capacitance	820μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 4.36A @ 100Hz Ripple Current - High Frequency Impedance 210 mOhms Lead Spacing 0.984" (25.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Tolerance	±20%
Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polar Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Polar -40°C ~ 85°C Polar -40°C ~ 85°C -6000 Hrs @	Voltage - Rated	420V
Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing O.984" (25.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	ESR (Equivalent Series Resistance)	150 mOhm @ 100Hz
Polarization Applications General Purpose Ripple Current - Low Frequency 4.36A @ 100Hz Ripple Current - High Frequency Impedance 210 mOhms Lead Spacing 0.984" (25.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.843" (72.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Lifetime @ Temp.	5000 Hrs @ 85°C
Applications Ripple Current - Low Frequency 4.36A @ 100Hz Ripple Current - High Frequency Impedance 210 mOhms Lead Spacing 0.984" (25.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.843" (72.20mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency - Impedance 210 mOhms Lead Spacing 0.984" (25.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.843" (72.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Polarization	Polar
Ripple Current - High Frequency Impedance 210 mOhms Lead Spacing 0.984" (25.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.843" (72.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Applications	General Purpose
Impedance210 mOhmsLead Spacing0.984" (25.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.843" (72.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Ripple Current - Low Frequency	4.36A @ 100Hz
Lead Spacing 0.984" (25.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.843" (72.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Ripple Current - High Frequency	-
Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.843" (72.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Impedance	210 mOhms
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Lead Spacing	0.984" (25.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Size / Dimension	1.378" Dia (35.00mm)
Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Height - Seated (Max)	2.843" (72.20mm)
Package / Case Radial, Can - Snap-In - 4 Lead	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In - 4 Lead
		Report errors?

B43510A827M80 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43510A827M80 Payment Methods



















B43510A827M80 Shipping Methods













If you have any question about B43510A827M80, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com