

B43511A0108M007

B43511A0108M007 Information

Heisener.com	 B43511A0108M007 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 1000UF 20% 420V SNAP Radial, Can - Snap-In - 4 Lead For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43511A0108M007 Specifications

Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In - 4 Lead Series B43511 Capacitance 1000µF Tolerance ±20% Voltage - Rated 420V ESR (Equivalent Series Resistance) 160 mOhm @ 100Hz Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization General Purpose Ripple Current - Low Frequency 5.6A @ 100Hz Ripple Current - High Frequency - Impedance 0.984" (25.00mm) Lead Spacing 0.984" (25.00mm) Size / Dimension 1.378" Dia (35.00mm) Size / Dimension 3.228" (82.00mm) Height - Seated (Max) 3.228" (82.00mm) Surface Mount Land Size - Mounting Type Through Hole		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 4 LeadPackageB43511Capacitance1000µFTolerance±20%Voltage - Rated420VESR (Equivalent Series Resistance)160 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5.6A @ 100HzLifed Marce160 mOhmsLead Spacing0.984" (25.00mm)Size / Dimension1.378" Dia (35.00mm)Size / Dimension3.228" (82.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Manufacturer Part Number	B43511A0108M007
Aluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 4 LeadSeriesB43511Capacitance1000µFTolerance±20%Voltage - Rated20VESR (Equivalent Series Resistance)160 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency5.6A @ 100HzRipple Current - High Frequency-Inpedance160 mOhmsLead Spacing0.984" (25.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)3.228" (82.00mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In - 4 Lead	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-In - 4 LeadSeriesB43511Capacitance1000µFTolerance±20%Voltage - Rated60 mOhm @ 100HzESR (Equivalent Series Resistance)160 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature~40°C ~ 85°CPolarizationGeneral PurposeApplications5.6A @ 100HzRipple Current - Low Frequency.Inpedance160 mOhmsLad Spacing0.984" (25.00mm)Size / Dimension1.378" Dia (35.00mm)Size / Dimension3.228" (82.00mm)Surface Mount Land Size-Mounting TypeFhrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Category	Capacitors
SeriesB43511Capacitance1000µFTolerance±20%Voltage - Rated420VESR (Equivalent Series Resistance)160 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5.6A @ 100HzLied Spacing0.984" (25.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)3.228" (82.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead		Aluminum Electrolytic Capacitors
Capacitance 1000µF Tolerance ±20% Voltage - Rated 420V ESR (Equivalent Series Resistance) 160 mOhm @ 100Hz Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 5.6A @ 100Hz Impedance 160 mOhms Lead Spacing 0.984" (25.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 3.228" (82.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Package	Radial, Can - Snap-In - 4 Lead
Tolerance±20%Voltage - Rated420VESR (Equivalent Series Resistance)160 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5.6A @ 100HzImpedance160 mOhmsLead Spacing0.984" (25.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)3.228" (82.00mm)Surface Mount Land Size-Pockage / CaseReidial, Can - Snap-In - 4 Lead	Series	B43511
Voltage - Rated420VESR (Equivalent Series Resistance)160 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5.6A @ 100HzImpedance160 mOhmsLead Spacing0.984" (25.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)3.228" (82.00mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In - 4 Lead	Capacitance	1000µF
ESR (Equivalent Series Resistance)160 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5.6A @ 100HzBipple Current - High Frequency-Impedance160 mOhmsLead Spacing0.984" (25.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)3.228" (82.00mm)Surface Mount Land Size-Pounting TypeFarough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Tolerance	$\pm 20\%$
Lifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5.6A @ 100HzRipple Current - High Frequency-Impedance160 mOhmsLead Spacing0.984" (25.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)3.228" (82.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Voltage - Rated	420V
Answis -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 5.6A @ 100Hz Ripple Current - High Frequency - Impedance 160 mOhms Lead Spacing 0.984" (25.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 3.228" (82.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	ESR (Equivalent Series Resistance)	160 mOhm @ 100Hz
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5.6A @ 100HzRipple Current - High Frequency-Impedance160 mOhmsLead Spacing0.984" (25.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)3.228" (82.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Lifetime @ Temp.	12000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency5.6A @ 100HzRipple Current - High Frequency-Impedance160 mOhmsLead Spacing0.984" (25.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)3.228" (82.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency5.6A @ 100HzRipple Current - High Frequency-Impedance160 mOhmsLead Spacing0.984" (25.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)3.228" (82.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Polarization	Polar
Ripple Current - High Frequency-Impedance160 mOhmsLead Spacing0.984" (25.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)3.228" (82.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Applications	General Purpose
Impedance160 mOhmsLead Spacing0.984" (25.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)3.228" (82.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Ripple Current - Low Frequency	5.6A @ 100Hz
IILead Spacing0.984" (25.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)3.228" (82.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Ripple Current - High Frequency	-
Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)3.228" (82.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Impedance	160 mOhms
Height - Seated (Max)3.228" (82.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Lead Spacing	0.984" (25.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Size / Dimension	1.378" Dia (35.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Height - Seated (Max)	3.228" (82.00mm)
Package / Case Radial, Can - Snap-In - 4 Lead	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In - 4 Lead
		Report errors?

B43511A0108M007 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43511A0108M007 Payment Methods





If you have any question about B43511A0108M007, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com