



B43511A4108M80 Information

Heisener.com

Part NumberB43511A4108M80ManufacturerEPCOS (TDK)CategoryCapacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 1000UF 20% 350V SNAP

Package Radial, Can - Snap-In - 4 Lead

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43511A4108M80 Specifications

Manufacturer Part Number B43511A4108M80 Manufacturer EPCOS (TDK) Category Capacitors Package Radial, Can - Snap-In - 4 Lead Series B43511 Capacitance 1000µF Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) 90 mOhm @ 100Hz Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization General Purpose Ripple Current - Low Frequency 5.1A @ 100Hz Ripple Current - High Frequency - Impedance 110 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 3.236" (82.20mm) Surface Mount Land Size - Mounting Type Through Hole	2 icelli i i con premientono	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In - 4 Lead Series B43511 Capacitance 1000µF Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) 90 mOhm @ 100Hz Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 5.1A @ 100Hz Ripple Current - High Frequency - Impedance 110 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 3.236" (82.20mm) Surface Mount Land Size -	Manufacturer Part Number	B43511A4108M80
Aluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 4 LeadSeriesB43511Capacitance1000μFTolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)90 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5.1A @ 100HzRipple Current - High Frequency-Impedance110 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)3.236" (82.20mm)Surface Mount Land Size-	Manufacturer	EPCOS (TDK)
Package Radial, Can - Snap-In - 4 Lead Series B43511 Capacitance 1000μF Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) 90 mOhm @ 100Hz Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 5.1A @ 100Hz Ripple Current - High Frequency - Impedance 110 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 3.236" (82.20mm) Surface Mount Land Size -	Category	Capacitors
Series B43511 Capacitance 1000μF Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) 90 mOhm @ 100Hz Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 5.1A @ 100Hz Ripple Current - High Frequency - Impedance 110 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 3.236" (82.20mm) Surface Mount Land Size -		Aluminum Electrolytic Capacitors
Capacitance 1000μF Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) 90 mOhm @ 100Hz Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 5.1A @ 100Hz Ripple Current - High Frequency - Impedance 110 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 3.236" (82.20mm) Surface Mount Land Size -	Package	Radial, Can - Snap-In - 4 Lead
Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) 90 mOhm @ 100Hz Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 5.1A @ 100Hz Ripple Current - High Frequency - Impedance 110 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 3.236" (82.20mm) Surface Mount Land Size -	Series	B43511
Voltage - Rated ESR (Equivalent Series Resistance) 90 mOhm @ 100Hz Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 5.1A @ 100Hz Ripple Current - High Frequency Impedance 110 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) Surface Mount Land Size -	Capacitance	1000μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 110 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Surface Mount Land Size -	Tolerance	±20%
Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 1.378" Dia (35.00mm) Height - Seated (Max) Surface Mount Land Size 12000 Hrs @ 85°C -40°C ~ 85°C Polar General Purpose 5.1A @ 100Hz - 110 mOhms 0.886" (22.50mm) 1.378" Dia (35.00mm) 3.236" (82.20mm)	Voltage - Rated	350V
Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 110 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) Surface Mount Land Size -40°C ~ 85°C Polar Polar -40°C ~ 85°C Polar Oeneral Purpose 5.1A @ 100Hz - 110 mOhms 1.378" Dia (35.00mm) 3.236" (82.20mm)	ESR (Equivalent Series Resistance)	90 mOhm @ 100Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 5.1A @ 100Hz Ripple Current - High Frequency - Impedance 110 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 3.236" (82.20mm) Surface Mount Land Size -	Lifetime @ Temp.	12000 Hrs @ 85°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) Surface Mount Land Size -	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 110 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 3.236" (82.20mm) Surface Mount Land Size -	Polarization	Polar
Ripple Current - High Frequency	Applications	General Purpose
Impedance 110 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 3.236" (82.20mm) Surface Mount Land Size -	Ripple Current - Low Frequency	5.1A @ 100Hz
Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 3.236" (82.20mm) Surface Mount Land Size -	Ripple Current - High Frequency	-
Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)3.236" (82.20mm)Surface Mount Land Size-	Impedance	110 mOhms
Height - Seated (Max) Surface Mount Land Size 3.236" (82.20mm) -	Lead Spacing	0.886" (22.50mm)
Surface Mount Land Size -	Size / Dimension	1.378" Dia (35.00mm)
	Height - Seated (Max)	3.236" (82.20mm)
Mounting Type Through Hole	Surface Mount Land Size	-
	Mounting Type	Through Hole
Package / Case Radial, Can - Snap-In - 4 Lead	Package / Case	Radial, Can - Snap-In - 4 Lead
Report errors?		Report errors?

B43511A4108M80 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43511A4108M80 Payment Methods



















B43511A4108M80 Shipping Methods













If you have any question about B43511A4108M80, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com