

# B43511A5108M80

## B43511A5108M80 Information

	Container.com	 B43511A5108M80 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 1000UF 20% 450V SNAP Radial, Can - Snap-In - 4 Lead For the pricing/inventory/lead time, please contact		
	For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Qu	iote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# B43511A5108M80 Specifications

Category Capacitors   Aluminum Electrolytic Capacitors   Package Radial, Can - Snap-In - 4 Lead   Series B43511   Capacitance 1000µF   Tolerance ±20%   Voltage - Rated 450V   ESR (Equivalent Series Resistance) 160 mOhm @ 100Hz   Lifetime @ Temp. 12000 Hrs @ 85°C   Operating Temperature -40°C ~ 85°C   Polarization General Purpose   Applications General Purpose   Ripple Current - Low Frequency -   Impedance 160 mOhms   Lead Spacing 0.886" (22.50mm)   Size / Dimension 1.575" Dia (40.00mm)   Height - Seated (Max) 4.024" (102.20mm)   Surface Mount Land Size -   Mounting Type Through Hole   Package / Case Radial, Can - Snap-In - 4 Lead	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 4 LeadSeriesB43511Capacitance1000µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)160 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency5.8A @ 100HzRipple Current - High Frequency-Impedance160 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.575" Dia (40.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Manufacturer Part Number	B43511A5108M80
Auminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 4 LeadSeriesB43511Capacitance1000µFtolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)160 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency5.8A @ 100HzRipple Current - High Frequency-Impedance0.886° (22.50mm)Size / Dimension1.575° Dia (40.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeFinrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-In - 4 LeadSeriesB43511Capacitance1000µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)160 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplications5.8A @ 100HzRipple Current - Low Frequency5.8A @ 100HzRipple Current - High Frequency-Impedance0.886° (22.50mm)Size / Dimension1.575° Dia (40.00mm)Height - Seated (Max)4.024° (102.20mm)Surface Mount Land Size-Mounting TypeFhrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Category	Capacitors
Series B43511   Capacitance 1000µF   Tolerance ±20%   Voltage - Rated 450V   ESR (Equivalent Series Resistance) 160 mOhm @ 100Hz   Lifetime @ Temp. 12000 Hrs @ 85°C   Operating Temperature -40°C ~ 85°C   Polar General Purpose   Applications General Purpose   Ripple Current - Low Frequency -   Impedance 160 mOhms   Liad Spacing 0.886° (22.50mm)   Size / Dimension 1.575° Dia (40.00mm)   Height - Seated (Max) 4.024" (102.20mm)   Surface Mount Land Size -   Mounting Type Frough Hole   Package / Case Kadial, Can - Snap-In - 4 Lead		Aluminum Electrolytic Capacitors
Capacitance1000µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)160 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5.8A @ 100HzInpedance160 mOhmsLead Spacing0.886° (22.50mm)Size / Dimension1.575° Dia (40.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Package	Radial, Can - Snap-In - 4 Lead
Tolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)160 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5.8A @ 100HzImpedance160 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.575" Dia (40.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Series	B43511
Voltage - Rated450VESR (Equivalent Series Resistance)160 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5.8A @ 100HzImpedance160 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.575" Dia (40.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeFacuage / Case	Capacitance	1000µF
ESR I 60 mOhm @ 100Hz   Lifetime @ Temp. 12000 Hrs @ 85°C   Operating Temperature -40°C ~ 85°C   Polar Polar   Applications General Purpose   Ripple Current - Low Frequency 5.8A @ 100Hz   Impedance -   Lead Spacing 0.886" (22.50mm)   Size / Dimension 1.575" Dia (40.00mm)   Height - Seated (Max) 4.024" (102.20mm)   Surface Mount Land Size -   Mounting Type Through Hole   Package / Case Radial, Can - Snap-In - 4 Lead	Tolerance	$\pm 20\%$
Lifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5.8A @ 100HzRipple Current - High Frequency-Impedance160 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.575" Dia (40.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In - 4 Lead	Voltage - Rated	450V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5.8A @ 100HzRipple Current - High Frequency-Impedance160 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.575" Dia (40.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	ESR (Equivalent Series Resistance)	160 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5.8A @ 100HzRipple Current - High Frequency-Impedance160 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.575" Dia (40.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Lifetime @ Temp.	12000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency5.8A @ 100HzRipple Current - High Frequency-Impedance160 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.575" Dia (40.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency5.8A @ 100HzRipple Current - High Frequency-Impedance160 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.575" Dia (40.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Polarization	Polar
In a constraint of the product of t	Applications	General Purpose
Impedance160 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.575" Dia (40.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Ripple Current - Low Frequency	5.8A @ 100Hz
IILead Spacing0.886" (22.50mm)Size / Dimension1.575" Dia (40.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Ripple Current - High Frequency	-
Size / Dimension1.575" Dia (40.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Impedance	160 mOhms
Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Lead Spacing	0.886" (22.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Size / Dimension	1.575" Dia (40.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Height - Seated (Max)	4.024" (102.20mm)
Package / Case Radial, Can - Snap-In - 4 Lead	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors'	Package / Case	Radial, Can - Snap-In - 4 Lead
		Report errors?

### B43511A5108M80 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### B43511A5108M80 Payment Methods





If you have any question about B43511A5108M80, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com