



B43511A9188M80 Information

Heisener.com

Part Number B43511A9188M80
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 1800UF 20% 400V SNAP

Package Radial, Can - Snap-In - 4 Lead

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43511A9188M80 Specifications

| Manufacturer Part Number B43511A9188M80 Manufacturer EPCOS (TDK) Category Capacitors Package Radial, Can - Snap-In - 4 Lead Series B43511 Capacitance 1800µF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 50 mOhm @ 100Hz Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarr Polar Applications General Purpose Ripple Current - Low Frequency 7.8A @ 100Hz Ripple Current - High Frequency - Impedance 60 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.772" Dia (45.00mm) Height - Seated (Max) 4.024" (102.20mm) Surface Mount Land Size - Mounting Type Pagical Care, Seate A Lead | 1 | |
|---|------------------------------------|----------------------------------|
| Category Capacitors Package Radial, Can - Snap-In - 4 Lead Series B43511 Capacitance 1800μF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 50 mOhm @ 100Hz Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 7.8A @ 100Hz Ripple Current - High Frequency - Impedance 60 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.772" Dia (45.00mm) Height - Seated (Max) 4.024" (102.20mm) Surface Mount Land Size - Mounting Type Through Hole | Manufacturer Part Number | B43511A9188M80 |
| Package Radial, Can - Snap-In - 4 Lead Series B43511 Capacitance 1800μF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 50 mOhm @ 100Hz Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 7.8A @ 100Hz Ripple Current - High Frequency - Impedance 60 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.772" Dia (45.00mm) Height - Seated (Max) 4.024" (102.20mm) Surface Mount Land Size - Mounting Type Through Hole | Manufacturer | EPCOS (TDK) |
| PackageRadial, Can - Snap-In - 4 LeadSeriesB43511Capacitance1800μFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)50 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency7.8A @ 100HzRipple Current - High Frequency-Impedance60 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.772" Dia (45.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeThrough Hole | Category | Capacitors |
| Series B43511 Capacitance 1800µF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 50 mOhm @ 100Hz Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 7.8A @ 100Hz Ripple Current - High Frequency - Impedance 60 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.772" Dia (45.00mm) Height - Seated (Max) 4.024" (102.20mm) Surface Mount Land Size - Mounting Type Through Hole | | Aluminum Electrolytic Capacitors |
| Capacitance1800µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)50 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency7.8A @ 100HzRipple Current - High Frequency-Impedance60 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.772" Dia (45.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeThrough Hole | Package | Radial, Can - Snap-In - 4 Lead |
| Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 50 mOhm @ 100Hz Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 7.8A @ 100Hz Ripple Current - High Frequency - Impedance 60 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.772" Dia (45.00mm) Height - Seated (Max) 4.024" (102.20mm) Surface Mount Land Size - Mounting Type Through Hole | Series | B43511 |
| Voltage - Rated400VESR (Equivalent Series Resistance)50 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency7.8A @ 100HzRipple Current - High Frequency-Impedance60 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.772" Dia (45.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeThrough Hole | Capacitance | 1800μF |
| ESR (Equivalent Series Resistance) Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 7.8A @ 100Hz Ripple Current - High Frequency Impedance 60 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type 50 mOhm @ 100Hz 12000 Hrs @ 85°C -40°C ~ 85°C Polar -40°C ~ 85°C -40°C ~ 85°C | Tolerance | ±20% |
| Lifetime @ Temp. Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 7.8A @ 100Hz Ripple Current - High Frequency Impedance 60 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.772" Dia (45.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type 12000 Hrs @ 85°C -40°C ~ 85°C General Purpose 6 eneral Purpose 7.8A @ 100Hz 6 mOhms 1.772" Dia (45.00mm) 4.024" (102.20mm) Through Hole | Voltage - Rated | 400V |
| Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 7.8A @ 100Hz Ripple Current - High Frequency - Impedance 60 mOhms Lead Spacing 5ize / Dimension 1.772" Dia (45.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type -40°C ~ 85°C General Purpose 7.8A @ 100Hz 7.8A @ 100Hz 1.78A | ESR (Equivalent Series Resistance) | 50 mOhm @ 100Hz |
| Polarization Polar Applications General Purpose Ripple Current - Low Frequency 7.8A @ 100Hz Ripple Current - High Frequency - Impedance 60 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.772" Dia (45.00mm) Height - Seated (Max) 4.024" (102.20mm) Surface Mount Land Size - Mounting Type Through Hole | Lifetime @ Temp. | 12000 Hrs @ 85°C |
| Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 60 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.772" Dia (45.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type General Purpose 7.8A @ 100Hz - Hough Hole | Operating Temperature | -40°C ~ 85°C |
| Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 60 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.772" Dia (45.00mm) Height - Seated (Max) 4.024" (102.20mm) Surface Mount Land Size Mounting Type Through Hole | Polarization | Polar |
| Ripple Current - High Frequency Impedance 60 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.772" Dia (45.00mm) Height - Seated (Max) 4.024" (102.20mm) Surface Mount Land Size - Mounting Type Through Hole | Applications | General Purpose |
| Impedance60 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.772" Dia (45.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeThrough Hole | Ripple Current - Low Frequency | 7.8A @ 100Hz |
| Lead Spacing 0.886" (22.50mm) Size / Dimension 1.772" Dia (45.00mm) Height - Seated (Max) 4.024" (102.20mm) Surface Mount Land Size - Mounting Type Through Hole | Ripple Current - High Frequency | - |
| Size / Dimension1.772" Dia (45.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeThrough Hole | Impedance | 60 mOhms |
| Height - Seated (Max) Surface Mount Land Size Mounting Type 4.024" (102.20mm) - Through Hole | Lead Spacing | 0.886" (22.50mm) |
| Surface Mount Land Size - Mounting Type Through Hole | Size / Dimension | 1.772" Dia (45.00mm) |
| Mounting Type Through Hole | Height - Seated (Max) | 4.024" (102.20mm) |
| | Surface Mount Land Size | - |
| Padial Can Span In Al and | Mounting Type | Through Hole |
| rackage / Case Radiai, Can - Shap-in - 4 Lead | Package / Case | Radial, Can - Snap-In - 4 Lead |
| Report errors? | | Report errors? |

B43511A9188M80 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43511A9188M80 Payment Methods



















B43511A9188M80 Shipping Methods













If you have any question about B43511A9188M80, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com