

# B43511B9108M80

#### B43511B9108M80 Information

Heisener.com	 B43511B9108M80 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 1000UF 20% 400V SNAP Radial, Can - Snap-In - 4 Lead For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## B43511B9108M80 Specifications

ManufacturerEPCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 4 LeadSeriesB43511Capacitance1000µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)90 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance110 mOhmsLied Spacing0.886" (22.50mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 4 LeadSeriesB43511Capacitance1000µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)90 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance110 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Manufacturer Part Number	B43511B9108M80
Aluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 4 LeadSeriesB43511Capacitance1000µFtolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)90 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency4.8A @ 100HzRipple Current - High Frequency-Inmedance110 mOhmsLead Spacing0.886° (22.50mm)Size / Dimension1.378° Dia (35.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In - 4 Lead	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-In - 4 LeadSeriesB43511Capacitance1000μFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)90 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRiple Current - Low Frequency-Riple Current - High Frequency-Impedance110 mOhmsLiad Spacing0.886° (22.50mm)Size / Dimension1.378° Dia (35.00mm)Height - Seated (Max)-Surface Mount Land Size-Package / CaseRadial, Can - Snap-In - 4 Lead	Category	Capacitors
SeriesB43511Capacitance1000µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)90 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency4.8A @ 100HzLingdance110 mOhmsLead Spacing0.886° (22.50mm)Size / Dimension1.378° Dia (35.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can - Snap-In - 4 Lead		Aluminum Electrolytic Capacitors
Capacitance1000µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)90 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.8A @ 100HzLingedance110 mOhmsLead Spacing0.886° (22.50mm)Size / Dimension4.024° (102.20mm)Height - Seated (Max)-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In - 4 Lead	Package	Radial, Can - Snap-In - 4 Lead
Tolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)90 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance110 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Pokage / CaseRadial, Can - Snap-In - 4 Lead	Series	B43511
Voltage - Rated400VESR (Equivalent Series Resistance)90 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.8A @ 100HzImpedance110 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeFarcage / Case	Capacitance	1000µF
Constraint 90 mOhm @ 100Hz   ESR (Equivalent Series Resistance) 90 mOhm @ 100Hz   Lifetime @ Temp. 12000 Hrs @ 85°C   Operating Temperature -40°C ~ 85°C   Polarization Polar   Applications General Purpose   Ripple Current - Low Frequency 4.8A @ 100Hz   Impedance 110 mOhms   Lead Spacing 0.886" (22.50mm)   Size / Dimension 1.378" Dia (35.00mm)   Height - Seated (Max) 4.024" (102.20mm)   Surface Mount Land Size -   Mounting Type Through Hole   Package / Case Raial, Can - Snap-In - 4 Lead	Tolerance	$\pm 20\%$
Lifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.8A @ 100HzRipple Current - High Frequency-Impedance110 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Voltage - Rated	400V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.8A @ 100HzRipple Current - High Frequency-Impedance110 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	ESR (Equivalent Series Resistance)	90 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.8A @ 100HzRipple Current - High Frequency-Impedance110 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Lifetime @ Temp.	12000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency4.8A @ 100HzRipple Current - High Frequency-Impedance110 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency4.8A @ 100HzRipple Current - High Frequency-Impedance110 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Polarization	Polar
In a constraint of the product of t	Applications	General Purpose
Impedance110 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Ripple Current - Low Frequency	4.8A @ 100Hz
IILead Spacing0.886" (22.50mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Ripple Current - High Frequency	-
Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Impedance	110 mOhms
Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Lead Spacing	0.886" (22.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Size / Dimension	1.378" Dia (35.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Height - Seated (Max)	4.024" (102.20mm)
Package / Case Radial, Can - Snap-In - 4 Lead	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In - 4 Lead
		Report errors?

#### B43511B9108M80 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

### B43511B9108M80 Payment Methods





If you have any question about B43511B9108M80, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com