



B43511C108M80 Information

Heisener.com

Part Number B43511C108M80
Manufacturer EPCOS (TDK)
Category Capacitors

Capacitors
Aluminum Electrolytic Capacitors

Description CAP ALUM 1000UF 20% 420V SNAP

Package Radial, Can - Snap-In - 4 Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43511C108M80 Specifications

Manufacturer Part Number B43511C108M80 Manufacturer EPCOS (TDK) Category Capacitors Package Radial, Can - Snap-In - 4 Lead Series B43511 Capacitance 1000μF Tolerance ±20% Voltage - Rated 420V ESR (Equivalent Series Resistance) 160 mOhm @ 100Hz Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polar Applications Ripple Current - Low Frequency 5.3A @ 100Hz Ripple Current - High Frequency - Impedance 160 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 3urface Mount Land Size Mounting Type Through Hole	•	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In - 4 Lead Series B43511 Capacitance 1000µF Tolerance ±20% Voltage - Rated 420V ESR (Equivalent Series Resistance) 160 mOhm @ 100Hz Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 5.3A @ 100Hz Ripple Current - High Frequency - Impedance 160 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 4.024" (102.20mm) Surface Mount Land Size -	Manufacturer Part Number	B43511C108M80
Package Radial, Can - Snap-In - 4 Lead Series B43511 Capacitance 1000μF Tolerance ±20% Voltage - Rated 420V ESR (Equivalent Series Resistance) 160 mOhm @ 100Hz Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 5.3A @ 100Hz Ripple Current - High Frequency - Impedance 160 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 4.024" (102.20mm) Surface Mount Land Size -	Manufacturer	EPCOS (TDK)
Package Radial, Can - Snap-In - 4 Lead Series B43511 Capacitance 1000µF Tolerance ±20% Voltage - Rated 420V ESR (Equivalent Series Resistance) 160 mOhm @ 100Hz Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 5.3A @ 100Hz Ripple Current - High Frequency - Impedance 160 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 4.024" (102.20mm) Surface Mount Land Size -	Category	Capacitors
Series B43511 Capacitance 1000μF Tolerance ±20% Voltage - Rated 420V ESR (Equivalent Series Resistance) 160 mOhm @ 100Hz Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 5.3A @ 100Hz Ripple Current - High Frequency - Impedance 160 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 4.024" (102.20mm) Surface Mount Land Size -		Aluminum Electrolytic Capacitors
Capacitance 1000μF Tolerance ±20% Voltage - Rated 420V ESR (Equivalent Series Resistance) 160 mOhm @ 100Hz Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 5.3A @ 100Hz Ripple Current - High Frequency - Impedance 160 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 4.024" (102.20mm) Surface Mount Land Size -	Package	Radial, Can - Snap-In - 4 Lead
Tolerance ±20% Voltage - Rated 420V ESR (Equivalent Series Resistance) 160 mOhm @ 100Hz Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 5.3A @ 100Hz Ripple Current - High Frequency - Impedance 160 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 4.024" (102.20mm) Surface Mount Land Size -	Series	B43511
Voltage - Rated 420V ESR (Equivalent Series Resistance) 160 mOhm @ 100Hz Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 5.3A @ 100Hz Ripple Current - High Frequency - Impedance 160 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 4.024" (102.20mm) Surface Mount Land Size -	Capacitance	1000μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 160 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) Surface Mount Land Size 160 mOhms	Tolerance	±20%
Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 1.378" Dia (35.00mm) Height - Seated (Max) Surface Mount Land Size 12000 Hrs @ 85°C -40°C ~ 85°C Polar General Purpose 5.3A @ 100Hz - 160 mOhms 1.378" Dia (35.00mm) 4.024" (102.20mm) -	Voltage - Rated	420V
Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Signature Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size -40°C ~ 85°C Polar Folar Folar 100 mOhms 10	ESR (Equivalent Series Resistance)	160 mOhm @ 100Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 5.3A @ 100Hz Ripple Current - High Frequency - Impedance 160 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 4.024" (102.20mm) Surface Mount Land Size -	Lifetime @ Temp.	12000 Hrs @ 85°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 160 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 4.024" (102.20mm) Surface Mount Land Size -	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 160 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) Surface Mount Land Size -	Polarization	Polar
Ripple Current - High Frequency - Impedance 160 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 4.024" (102.20mm) Surface Mount Land Size -	Applications	General Purpose
Impedance 160 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 4.024" (102.20mm) Surface Mount Land Size -	Ripple Current - Low Frequency	5.3A @ 100Hz
Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 4.024" (102.20mm) Surface Mount Land Size -	Ripple Current - High Frequency	-
Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 4.024" (102.20mm) Surface Mount Land Size -	Impedance	160 mOhms
Height - Seated (Max) Surface Mount Land Size 4.024" (102.20mm) -	Lead Spacing	0.886" (22.50mm)
Surface Mount Land Size -	Size / Dimension	1.378" Dia (35.00mm)
	Height - Seated (Max)	4.024" (102.20mm)
Mounting Type Through Hole	Surface Mount Land Size	-
Woulding Type	Mounting Type	Through Hole
Package / Case Radial, Can - Snap-In - 4 Lead	Package / Case	Radial, Can - Snap-In - 4 Lead
Report errors?		Report errors?

B43511C108M80 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43511C108M80 Payment Methods



















B43511C108M80 Shipping Methods













If you have any question about B43511C108M80, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com