

B43511C108M87

Request a Quote

B43511C108M87 Information

Heisener.com	Part Number	B43511C108M87
	Manufacturer	EPCOS (TDK)
	Category	Capacitors Aluminum Electrolytic Capacitors
	Description	CAP ALUM 1000UF 20% 420V SNAP
	Package	Radial, Can - Snap-In - 4 Lead
		For the pricing/inventory/lead time, please contact
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43511C108M87 Specifications

Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Radial, Can - Snap-In - 4 Lead Package Radial, Can - Snap-In - 4 Lead Series B43511 Capacitors 1000µF Capacitance 1000µF Tolerance ±20% Voltage - Rated 420V ESR (Equivalent Series Resistance) 160 mOhm @ 100Hz Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Impedance 160 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 4.024" (102.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 4 LeadSeriesB43511Capacitance1000µFTolerance±20%Voltage - Rated420VESR (Equivalent Series Resistance)160 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency5.3A @ 100HzRipple Current - High Frequency-Impedance160 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Manufacturer Part Number	B43511C108M87
Aluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 4 LeadPackageB43511Capacitance1000μFTolerance-20%Voltage - Rated420VESR (Equivalent Series Resistance)160 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsS3A @ 100HzRipple Current - High Frequency-Impedance160 mOhmsLided Spacing0.886° (22.50mm)Size / Dimension1.378° Dia (35.00mm)Height - Seated (Max)-Surface Mount Land Size-Polaring TypeFacuencePackage / CaseRidal, Can - Snap-In - 4 Lead	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-In - 4 LeadSeriesB43511Capacitance1000μFTolerance±20%Voltage - Rated420VESR (Equivalent Series Resistance)160 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRiple Current - Low Frequency-Riple Current - High Frequency-Impedance160 mOhmsLiad Spacing0.886° (22.50mm)Size / Dimension1.378° Dia (35.00mm)Height - Seated (Max)-Surface Mount Land Size-Package / CaseThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Category	Capacitors
SeriesB43511Capacitance1000µFTolerance±20%Voltage - Rated420VESR (Equivalent Series Resistance)160 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5.3A @ 100HzLiadge Agacing0.886° (22.50mm)Size / Dimension1.378° Dia (35.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can - Snap-In - 4 Lead		Aluminum Electrolytic Capacitors
Capacitance1000µFTolerance±20%Voltage - Rated420VESR (Equivalent Series Resistance)160 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance160 mOhmsLead Spacing0.886° (22.50mm)Size / Dimension1.378° Dia (35.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Package	Radial, Can - Snap-In - 4 Lead
±20 Tolerance ±20% Voltage - Rated 420V ESR (Equivalent Series Resistance) 160 mOhm @ 100Hz Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polar Folar Applications General Purpose Ripple Current - Low Frequency 5.3A @ 100Hz Impedance 160 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 4.024" (102.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Series	B43511
Voltage - Rated420VESR (Equivalent Series Resistance)160 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5.3A @ 100HzImpedance160 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Capacitance	1000µF
Constraint160 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5.3A @ 100HzBipple Current - High Frequency-Impedance160 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Tolerance	±20%
Lifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5.3A @ 100HzRipple Current - High Frequency-Impedance160 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeFackage / CasePackage / CaseRadial, Can - Snap-In - 4 Lead	Voltage - Rated	420V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 5.3A @ 100Hz Ripple Current - High Frequency - Impedance 160 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 4.024" (102.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	ESR (Equivalent Series Resistance)	160 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5.3A @ 100HzRipple Current - High Frequency-Impedance160 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Lifetime @ Temp.	12000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency5.3A @ 100HzRipple Current - High Frequency-Impedance160 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Operating Temperature	$-40^{\circ}\mathrm{C} \sim 85^{\circ}\mathrm{C}$
Ripple Current - Low Frequency5.3A @ 100HzRipple Current - High Frequency-Impedance160 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Polarization	Polar
In a constraint of a constrain	Applications	General Purpose
Impedance160 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Ripple Current - Low Frequency	5.3A @ 100Hz
IILead Spacing0.886" (22.50mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Ripple Current - High Frequency	-
Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Impedance	160 mOhms
Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Lead Spacing	0.886" (22.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Size / Dimension	1.378" Dia (35.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Height - Seated (Max)	4.024" (102.20mm)
Package / Case Radial, Can - Snap-In - 4 Lead	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In - 4 Lead
		Report errors?

B43511C108M87 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43511C108M87 Payment Methods





If you have any question about B43511C108M87, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com