

B43511C4158M80

B43511C4158M80 Information

Heisener.com	 B43511C4158M80 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 1500UF 20% 350V SNAP Radial, Can - Snap-In - 4 Lead For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43511C4158M80 Specifications

Manufacturer Part Number B43511C4158M80 Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In - 4 Lead Series B43511 Capacitance B43511 Capacitance 1500µF Tolerance ±20% Voltage - Rated 500 V ESR (Equivalent Series Resistance) 60 mOhm @ 100Hz Lifetime @ remp. 12000 Hrs @ 85°C Operating Temperature 40°C ~ 85°C Polarization General Purpose Applications General Purpose Ripple Current - Low Frequency - Impedance 70 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.575" Dia (40.00mm) Size / Dimension 3.236" (82.20mm) Height - Seated (Max) 3.236" (82.20mm) Sizer Mount Land Size - Mounting Type Fhoregathera		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 4 LeadSeriesB43511Capacitance1500µFTolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)60 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency6.2A @ 100HzRipple Current - High Frequency-Impedance00 mOhmsLied Spacing0.886" (22.50mm)Size / Dimension1.575" Dia (40.00mm)Height - Seated (Max)3.236" (82.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Manufacturer Part Number	B43511C4158M80
Auminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 4 LeadSeriesB43511Capacitance1500µFTolerance±20%Voltage - Rated60 mOhm @ 100HzESR (Equivalent Series Resistance)60 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency6.2A @ 100HzLinedance70 mOhmsLidedspacing0.886° (22.50mm)Size / Dimension1.575° Dia (40.00mm)Height - Seated (Max)3.236° (82.20mm)Surface Mount Land Size-Mounting TypeFurough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-In - 4 LeadSeriesB43511Capacitance1500µFTolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)60 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplications6.2A @ 100HzRipple Current - Low Frequency6.2A @ 100HzLinedance70 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.575" Dia (40.00mm)Height - Seated (Max)3.236" (82.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Category	Capacitors
SeriesB43511Capacitance1500µFTolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)60 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance70 mOhmsLiad Spacing0.886° (22.50mm)Size / Dimension1.575° Dia (40.00mm)Size / Dimension3.236° (82.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead		Aluminum Electrolytic Capacitors
Capacitance1500µFTolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)60 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationReneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Jondshare90 MohmsLiad Spacing0.886° (22.50mm)Size / Dimension1.575° Dia (40.00mm)Size / Dimension3.236° (82.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In - 4 Lead	Package	Radial, Can - Snap-In - 4 Lead
Tolerance±20%Tolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)60 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency6.2A @ 100HzRipple Current - High Frequency-Impedance70 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.575" Dia (40.00mm)Height - Seated (Max)3.236" (82.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Series	B43511
Voltage - Rated350VESR (Equivalent Series Resistance)60 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency6.2A @ 100HzImpedance70 mOhmsIngedance0.886" (22.50mm)Size / Dimension1.575" Dia (40.00mm)Height - Seated (Max)3.236" (82.20mm)Surface Mount Land Size-Hounting TypeThrough HolePackage / CaseRatial, Can - Snap-In - 4 Lead	Capacitance	1500µF
ESR (Equivalent Series Resistance)60 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency6.2A @ 100HzMipedance70 mOhmsLead Spacing0.886° (22.50mm)Size / Dimension1.575° Dia (40.00mm)Height - Seated (Max)3.236° (82.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In - 4 Lead	Tolerance	$\pm 20\%$
Lifetime @ Temp.12000 Hrs @ 85°CDperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency6.2A @ 100HzRipple Current - High Frequency-Impedance70 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.575" Dia (40.00mm)Height - Seated (Max)3.236" (82.20mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In - 4 Lead	Voltage - Rated	350V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency6.2A @ 100HzRipple Current - High Frequency-Impedance70 mOhmsLead Spacing0.886° (22.50mm)Size / Dimension1.575° Dia (40.00mm)Height - Seated (Max)3.236° (82.20mm)Surface Mount Land Size-Mounting TypeFackage / CaseRakage / CaseRakial, Can - Snap-In - 4 Lead	ESR (Equivalent Series Resistance)	60 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency6.2A @ 100HzRipple Current - High Frequency-Impedance70 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.575" Dia (40.00mm)Height - Seated (Max)3.236" (82.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Lifetime @ Temp.	12000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency6.2A @ 100HzRipple Current - High Frequency-Impedance70 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.575" Dia (40.00mm)Height - Seated (Max)3.236" (82.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Operating Temperature	$-40^{\circ}\mathrm{C} \sim 85^{\circ}\mathrm{C}$
Ripple Current - Low Frequency6.2A @ 100HzRipple Current - High Frequency-Impedance70 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.575" Dia (40.00mm)Height - Seated (Max)3.236" (82.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Polarization	Polar
In a constraint of the product of t	Applications	General Purpose
Impedance70 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.575" Dia (40.00mm)Height - Seated (Max)3.236" (82.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Ripple Current - Low Frequency	6.2A @ 100Hz
IILead Spacing0.886" (22.50mm)Size / Dimension1.575" Dia (40.00mm)Height - Seated (Max)3.236" (82.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Ripple Current - High Frequency	-
Size / Dimension1.575" Dia (40.00mm)Height - Seated (Max)3.236" (82.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Impedance	70 mOhms
Height - Seated (Max)3.236" (82.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Lead Spacing	0.886" (22.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Size / Dimension	1.575" Dia (40.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Height - Seated (Max)	3.236" (82.20mm)
Package / Case Radial, Can - Snap-In - 4 Lead	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors	Package / Case	Radial, Can - Snap-In - 4 Lead
1		Report errors?

B43511C4158M80 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43511C4158M80 Payment Methods





If you have any question about B43511C4158M80, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com