



B43511C567M80 Information

Heisener.com

Part Number B43511C567M80

Manufacturer EPCOS (TDK)

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 560UF 20% 420V SNAP

Package Radial, Can - Snap-In - 4 Lead

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43511C567M80 Specifications

Manufacturer Part Number B43511C567M80 Manufacturer EPCOS (TDK) Category Capacitors Package Radial, Can - Snap-In - 4 Lead Series B43511 Capacitance 560μF Tolerance ±20% Voltage - Rated 420V ESR (Equivalent Series Resistance) 270 mOhm @ 100Hz Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization General Purpose Ripple Current - Low Frequency 3.3A @ 100Hz Ripple Current - High Frequency - Lead Spacing 290 mOhms Lead Spacing 1.378° Dia (35.00mm) Bizje / Dimension 1.378° Dia (35.00mm) Height - Seated (Max) 2.449° (62.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	•	
Category Capacitors Package Radial, Can - Snap-In - 4 Lead Series B43511 Capacitance 560µF Tolerance ±20% Voltage - Rated 420V ESR (Equivalent Series Resistance) 270 mOhm @ 100Hz Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3.3A @ 100Hz Ripple Current - High Frequency - Impedance 290 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.449" (62.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Manufacturer Part Number	B43511C567M80
Package Radial, Can - Snap-In - 4 Lead Series B43511 Capacitance 560µF Tolerance ±20% Voltage - Rated 420V ESR (Equivalent Series Resistance) 270 mOhm @ 100Hz Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3.3A @ 100Hz Ripple Current - High Frequency - Impedance 290 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.449" (62.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Manufacturer	EPCOS (TDK)
Package Radial, Can - Snap-In - 4 Lead Series B43511 Capacitance 560μF Tolerance ±20% Voltage - Rated 420V ESR (Equivalent Series Resistance) 270 mOhm @ 100Hz Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3.3A @ 100Hz Ripple Current - High Frequency - Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.449" (62.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Category	Capacitors
Series B43511 Capacitance 560μF Tolerance ±20% Voltage - Rated 420V ESR (Equivalent Series Resistance) 270 mOhm @ 100Hz Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3.3A @ 100Hz Ripple Current - High Frequency - Impedance 290 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.449" (62.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead		Aluminum Electrolytic Capacitors
Capacitance 560μF Tolerance ±20% Voltage - Rated 420V ESR (Equivalent Series Resistance) 270 mOhm @ 100Hz Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3.3A @ 100Hz Ripple Current - High Frequency - Impedance 290 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.449" (62.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Package	Radial, Can - Snap-In - 4 Lead
Tolerance ±20% Voltage - Rated 420V ESR (Equivalent Series Resistance) 270 mOhm @ 100Hz Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3.3A @ 100Hz Ripple Current - High Frequency - Impedance 290 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.449" (62.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Series	B43511
Voltage - Rated420VESR (Equivalent Series Resistance)270 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.3A @ 100HzRipple Current - High Frequency-Impedance290 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.449" (62.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Capacitance	560μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature -40°C ~ 85°C Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 270 mOhm @ 100Hz 12000 Hrs @ 85°C -40°C ~ 85°C Polar -40°C ~ 85°C -40	Tolerance	±20%
Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 290 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Voltage - Rated	420V
Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 290 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	ESR (Equivalent Series Resistance)	270 mOhm @ 100Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3.3A @ 100Hz Ripple Current - High Frequency - Impedance 290 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.449" (62.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Lifetime @ Temp.	12000 Hrs @ 85°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 290 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.449" (62.20mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 290 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.449" (62.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Polarization	Polar
Ripple Current - High Frequency Impedance 290 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.449" (62.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Applications	General Purpose
Impedance 290 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.449" (62.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Ripple Current - Low Frequency	3.3A @ 100Hz
Lead Spacing0.886" (22.50mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.449" (62.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Ripple Current - High Frequency	-
Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.449" (62.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Impedance	290 mOhms
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Lead Spacing	0.886" (22.50mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Size / Dimension	1.378" Dia (35.00mm)
Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Height - Seated (Max)	2.449" (62.20mm)
Package / Case Radial, Can - Snap-In - 4 Lead	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In - 4 Lead
		Report errors?

B43511C567M80 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43511C567M80 Payment Methods





















B43511C567M80 Shipping Methods













If you have any question about B43511C567M80, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com