

B43511C9108M80

est a Quote

B43511C9108M80 Information

Heisener.com	Part Number	B43511C9108M80	
	Manufacturer	EPCOS (TDK)	
	Category	Capacitors Aluminum Electrolytic Capacitors	
	Description	CAP ALUM 1000UF 20% 400V SNAP	- 19 <u>6</u>
	Package	Radial, Can - Snap-In - 4 Lead	- 263
		For the pricing/inventory/lead time, please contact	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Reque
	For Reference Only	Manufacturer Category Description Package	For Reference Only Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors Description Package Radial, Can - Snap-In - 4 Lead For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43511C9108M80 Specifications

Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In - 4 Lead Series B43511 Capacitance 1000µF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 90 mOhm @ 100Hz Derating Temperature 40°C ~ 85°C Polarization General Purpose Applications General Purpose Ripple Current - Low Frequency 5.6A @ 100Hz Impedance 110 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 4.024" (102.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 4 LeadSeriesB43511Capacitance1000µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)90 mOhm @ 100HzDerating Temperature12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - High Frequency-Impedance110 mOhmsLead Spacing0.886° (22.50mm)Size / Dimension1.378° Dia (35.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeFrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Manufacturer Part Number	B43511C9108M80
Auminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 4 LeadSeriesB43511Capacitance1000µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)90 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency-6Impedance110 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In - 4 Lead	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-In - 4 LeadSeriesB43511Capacitance1000µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)90 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplications5.6A @ 100HzRipple Current - Low Frequency5.6A @ 100HzRipple Current - High Frequency-Impedance1.01 mOhmsLiad Spacing0.886° (22.50mm)Size / Dimension1.378° Dia (35.00mm)Height - Seated (Max)4.024° (102.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Category	Capacitors
Series B43511 Capacitance 1000µF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 90 mOhm @ 100Hz Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature 40°C ~ 85°C Polar General Purpose Applications General Purpose Ripple Current - Low Frequency - Impedance 110 mOhms Lead Spacing 0.886° (22.50mm) Size / Dimension 1.378° Dia (35.00mm) Height - Seated (Max) 4.024" (102.20mm) Surface Mount Land Size - Mounting Type Frough Hole Package / Case Kadial, Can - Snap-In - 4 Lead		Aluminum Electrolytic Capacitors
Capacitance1000µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)90 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5.6A @ 100HzIngedance110 mOhmsLead Spacing0.886° (22.50mm)Size / Dimension4.024" (102.20mm)Bright - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Package	Radial, Can - Snap-In - 4 Lead
Tolerance±2%Voltage - Rated400VESR (Equivalent Series Resistance)90 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5.6A @ 100HzImpedance110 mOhmsLacd Spacing0.886" (22.50mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Series	B43511
Voltage - Rated400VESR (Equivalent Series Resistance)90 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5.6A @ 100HzImpedance110 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeFrequencyPackage / CaseRational Can Shap-In - 4 Lead	Capacitance	1000µF
Constraint 90 mOhm @ 100Hz ESR (Equivalent Series Resistance) 90 mOhm @ 100Hz Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polar Polar Applications General Purpose Ripple Current - Low Frequency 5.6A @ 100Hz Impedance 110 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 4.024" (102.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Tolerance	$\pm 20\%$
Lifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5.6A @ 100HzRipple Current - High Frequency-Impedance110 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In - 4 Lead	Voltage - Rated	400V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 5.6A @ 100Hz Ripple Current - High Frequency - Impedance 110 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 4.024" (102.20mm) Surface Mount Land Size - Mounting Type Fhrough Hole Package / Case Radial, Can - Snap-In - 4 Lead	ESR (Equivalent Series Resistance)	90 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5.6A @ 100HzRipple Current - High Frequency-Impedance110 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Lifetime @ Temp.	12000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency5.6A @ 100HzRipple Current - High Frequency-Impedance110 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency5.6A @ 100HzRipple Current - High Frequency-Impedance110 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Polarization	Polar
In our and provide a strengtRipple Current - High Frequency-Impedance110 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Applications	General Purpose
Impedance110 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Ripple Current - Low Frequency	5.6A @ 100Hz
IILead Spacing0.886" (22.50mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Ripple Current - High Frequency	-
Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Impedance	110 mOhms
Height - Seated (Max)4.024" (102.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Lead Spacing	0.886" (22.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Size / Dimension	1.378" Dia (35.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Height - Seated (Max)	4.024" (102.20mm)
Package / Case Radial, Can - Snap-In - 4 Lead	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors'	Package / Case	Radial, Can - Snap-In - 4 Lead
		Report errors?

B43511C9108M80 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43511C9108M80 Payment Methods





If you have any question about B43511C9108M80, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com