



### B43511C9827M80 Information

Heisener.com

Part Number B43511C9827M80
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

**Description** CAP ALUM 820UF 20% 400V SNAP

Package Radial, Can - Snap-In - 4 Lead

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **B43511C9827M80 Specifications**

Manufacturer Part Number         B43511C9827M80           Manufacturer         EPCOS (TDK)           Category         Capacitors           Aluminum Electrolytic Capacitors           Package         Radial, Can - Snap-In - 4 Lead           Series         B43511           Capacitance         \$20µF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         110 mOhm @ 100Hz           Lifetime @ Temp.         12000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         4.3A @ 100Hz           Ripple Current - High Frequency         -           Impedance         130 mOhms           Lead Spacing         0.886" (22.50mm)           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         3.236" (82.20mm)           Surface Mount Land Size         -           Mounting Type         Through Hole	<b>4</b>	
Category         Capacitors           Package         Radial, Can - Snap-In - 4 Lead           Series         B43511           Capacitance         \$20µF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         110 mOhm @ 100Hz           Lifetime @ Temp.         12000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         4.3A @ 100Hz           Ripple Current - High Frequency         -           Impedance         130 mOhms           Lead Spacing         0.886" (22.50mm)           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         3.236" (82.20mm)           Surface Mount Land Size         -           Mounting Type         Through Hole	Manufacturer Part Number	B43511C9827M80
Package         Radial, Can - Snap-In - 4 Lead           Series         B43511           Capacitance         820μF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         110 mOhm @ 100Hz           Lifetime @ Temp.         12000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         4.3A @ 100Hz           Ripple Current - High Frequency         -           Impedance         130 mOhms           Lead Spacing         0.886" (22.50mm)           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         3.236" (82.20mm)           Surface Mount Land Size         -           Mounting Type         Through Hole	Manufacturer	EPCOS (TDK)
Package         Radial, Can - Snap-In - 4 Lead           Series         B43511           Capacitance         820μF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         110 mOhm @ 100Hz           Lifetime @ Temp.         12000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         4.3A @ 100Hz           Ripple Current - High Frequency         -           Impedance         130 mOhms           Lead Spacing         0.886" (22.50mm)           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         3.236" (82.20mm)           Surface Mount Land Size         -           Mounting Type         Through Hole	Category	Capacitors
Series         B43511           Capacitance         820µF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         110 mOhm @ 100Hz           Lifetime @ Temp.         12000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         4.3A @ 100Hz           Ripple Current - High Frequency         -           Impedance         130 mOhms           Lead Spacing         0.886" (22.50mm)           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         3.236" (82.20mm)           Surface Mount Land Size         -           Mounting Type         Through Hole		Aluminum Electrolytic Capacitors
Capacitance820μFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)110 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.3A @ 100HzRipple Current - High Frequency-Impedance130 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)3.236" (82.20mm)Surface Mount Land Size-Mounting TypeThrough Hole	Package	Radial, Can - Snap-In - 4 Lead
Tolerance ±20%  Voltage - Rated 400V  ESR (Equivalent Series Resistance) 110 mOhm @ 100Hz  Lifetime @ Temp. 12000 Hrs @ 85°C  Operating Temperature -40°C ~ 85°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 4.3A @ 100Hz  Ripple Current - High Frequency -  Impedance 130 mOhms  Lead Spacing 0.886" (22.50mm)  Size / Dimension 1.378" Dia (35.00mm)  Height - Seated (Max) 3.236" (82.20mm)  Surface Mount Land Size -  Mounting Type Through Hole	Series	B43511
Voltage - Rated400VESR (Equivalent Series Resistance)110 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.3A @ 100HzRipple Current - High Frequency-Impedance130 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)3.236" (82.20mm)Surface Mount Land Size-Mounting TypeThrough Hole	Capacitance	820μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  12000 Hrs @ 85°C  Operating Temperature  -40°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  4.3A @ 100Hz  Ripple Current - High Frequency  - Impedance  130 mOhms  Lead Spacing  0.886" (22.50mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  110 mOhm @ 100Hz  12000 Hrs @ 85°C  -40°C ~ 85°C  Polar  -40°C ~ 85°C  -60erral Purpose  4.3A @ 100Hz  -100Hz  -100H	Tolerance	±20%
Lifetime @ Temp.  12000 Hrs @ 85°C  Operating Temperature  -40°C ~ 85°C  Polarization  Polar  Applications  General Purpose  Ripple Current - Low Frequency  4.3A @ 100Hz  Ripple Current - High Frequency  - Impedance  130 mOhms  Lead Spacing  0.886" (22.50mm)  Size / Dimension  1.378" Dia (35.00mm)  Height - Seated (Max)  3.236" (82.20mm)  Surface Mount Land Size  - Mounting Type  Through Hole	Voltage - Rated	400V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 4.3A @ 100Hz Ripple Current - High Frequency Impedance 130 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 3.236" (82.20mm) Surface Mount Land Size Mounting Type Through Hole	ESR (Equivalent Series Resistance)	110 mOhm @ 100Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 4.3A @ 100Hz Ripple Current - High Frequency - Impedance 130 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 3.236" (82.20mm) Surface Mount Land Size - Mounting Type Through Hole	Lifetime @ Temp.	12000 Hrs @ 85°C
Applications  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  Lead Spacing  0.886" (22.50mm)  Size / Dimension  1.378" Dia (35.00mm)  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  General Purpose  4.3A @ 100Hz  -  130 mOhrs  1.378" Dia (35.00mm)  3.236" (82.20mm)  Through Hole	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  130 mOhms  Lead Spacing  0.886" (22.50mm)  Size / Dimension  1.378" Dia (35.00mm)  Height - Seated (Max)  3.236" (82.20mm)  Surface Mount Land Size  Mounting Type  Through Hole	Polarization	Polar
Ripple Current - High Frequency Impedance 130 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 3.236" (82.20mm) Surface Mount Land Size - Mounting Type Through Hole	Applications	General Purpose
Impedance130 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)3.236" (82.20mm)Surface Mount Land Size-Mounting TypeThrough Hole	Ripple Current - Low Frequency	4.3A @ 100Hz
Lead Spacing 0.886" (22.50mm)  Size / Dimension 1.378" Dia (35.00mm)  Height - Seated (Max) 3.236" (82.20mm)  Surface Mount Land Size -  Mounting Type Through Hole	Ripple Current - High Frequency	-
Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)3.236" (82.20mm)Surface Mount Land Size-Mounting TypeThrough Hole	Impedance	130 mOhms
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  3.236" (82.20mm)  - Through Hole	Lead Spacing	0.886" (22.50mm)
Surface Mount Land Size - Mounting Type Through Hole	Size / Dimension	1.378" Dia (35.00mm)
Mounting Type Through Hole	Height - Seated (Max)	3.236" (82.20mm)
	Surface Mount Land Size	-
Package / Case  Radial Can - Span-In - 4 Lead	Mounting Type	Through Hole
radia, can Shap in 1 Dead	Package / Case	Radial, Can - Snap-In - 4 Lead
Report errors?		Report errors?

### **B43511C9827M80 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **B43511C9827M80 Payment Methods**



















## B43511C9827M80 Shipping Methods













If you have any question about B43511C9827M80, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com