



B43516A5277M000 Information

Heisener.com

Part Number B43516A5277M000
Manufacturer EPCOS (TDK)

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 270UF 20% 450V SNAP 4LD

Package Radial, Can - Snap-In - 4 Lead

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43516A5277M000 Specifications

Manufacturer Part Number B43516A5277M000 Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In - 4 Lead Series B43516 Capacitance 270μF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 360 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.57A @ 100Hz Ripple Current - High Frequency - Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In - 4 Lead Series B43516 Capacitance 270μF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 360 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.57A @ 100Hz Ripple Current - High Frequency - Impedance 520 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Manufacturer Part Number	B43516A5277M000
Package Radial, Can - Snap-In - 4 Lead Series B43516 Capacitance 270µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 360 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.57A @ 100Hz Ripple Current - High Frequency - Impedance 520 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Manufacturer	EPCOS (TDK)
Package Radial, Can - Snap-In - 4 Lead Series B43516 Capacitance 270μF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 360 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.57A @ 100Hz Ripple Current - High Frequency - Impedance 520 mOhms Lead Spacing 0.886° (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Category	Capacitors
Series B43516 Capacitance 270μF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 360 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.57A @ 100Hz Ripple Current - High Frequency - Impedance 520 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead		Aluminum Electrolytic Capacitors
Capacitance 270μF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 360 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.57A @ 100Hz Ripple Current - High Frequency - Impedance 520 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Package	Radial, Can - Snap-In - 4 Lead
Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 360 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.57A @ 100Hz Ripple Current - High Frequency - Impedance 520 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Series	B43516
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance S20 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 400 C ~ 105°C General Purpose General Purpose 1.57A @ 100Hz 1.57	Capacitance	270μF
ESR (Equivalent Series Resistance) 360 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency 1.57A @ 100Hz Ripple Current - High Frequency Impedance 520 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.57A @ 100Hz Ripple Current - High Frequency Impedance 520 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Voltage - Rated	450V
Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.57A @ 100Hz Ripple Current - High Frequency - Impedance 520 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	ESR (Equivalent Series Resistance)	360 mOhm @ 100Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.57A @ 100Hz Ripple Current - High Frequency - Impedance 520 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Lifetime @ Temp.	3000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency 1.57A @ 100Hz Ripple Current - High Frequency	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance S20 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Polarization	Polar
Ripple Current - High Frequency Impedance 520 mOhms Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Applications	General Purpose
Impedance520 mOhmsLead Spacing0.886" (22.50mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 4 Lead	Ripple Current - Low Frequency	1.57A @ 100Hz
Lead Spacing 0.886" (22.50mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Ripple Current - High Frequency	-
Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Impedance	520 mOhms
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Lead Spacing	0.886" (22.50mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Size / Dimension	1.378" Dia (35.00mm)
Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 4 Lead	Height - Seated (Max)	1.654" (42.00mm)
Package / Case Radial, Can - Snap-In - 4 Lead	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In - 4 Lead
·		Report errors?

B43516A5277M000 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43516A5277M000 Payment Methods



















B43516A5277M000 Shipping Methods













If you have any question about B43516A5277M000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com